


computing today

MAR 1979


50p

**TANGERINE
DREAM
UPMARKET
VDU**



**S100
PRINTER
TRITON EXPANSION
STOMPER-A NEW GAME
MICROBIOLOGY-THE 6800**

Pet program supermarket



At last a whole menu of programs to feed your PET at prices which knock the bottom out of traditional software costs.

Our 16 page catalogue lists nearly 130 programs from £3 to £50 (including VAT). These cover Business Routines, Programming Aids to help you make the most of your PET and some super games to play with it. Here are just a few examples.

TRY THESE PROGRAMS AT YOUR NEAREST PET DEALER

| | | |
|---------------------------|---------------------------|--------------------|
| Addressbook £6 | Linear Programming £8 | Sales Analysis £10 |
| 6502 Assembler Editor £25 | Linear Regression £5 | Statistics £7 |
| Backgammon £8 | Line Renummer £15 | Stock Control £12 |
| Bridge Challenger £10 | Microchess £14 | Super Startrek £8 |
| Civil War £7.50 | Music £10 | Tax 78/79 £8 |
| Data File Handler £12 | Payroll £25 | VAT Pack £17.50 |
| Discounted Cashflow £8 | Percentage Costing £49.50 | |
| Graphics Package £12 | Pet Basic Tutorial £15 | |

All our prices include VAT.

For further details of these and the other ninety programs in our free catalogue, complete the coupon or call us today. We also accept credit card orders over the telephone.

Petsoft Specialists in personal computer programs,

PO Box 9, Newbury, Berks. RG13 1PB England.
Tel: 0635-201131 or 01-752 0814. Telex: 8951672

Petsoft A member of the ACT Computer Group.
PET is the trade mark of Commodore.

To Petsoft

My name is _____

My PET lives at: _____

PO Box 9, Newbury, Berks. RG13 1PB, England.
MY PET NEEDS FEEDING Please rush me a copy of your free 12 page catalogue of PET programs without obligation.

computing today

VOL. 1 NO. 1
MARCH '79

EDITOR: Gary Evans.
EDITORIAL DIRECTOR: Halvor W Moorshead.
EDITORIAL ASSISTANTS: Rick Maybury, Ian Graham, Henry Budgett.
ART DIRECTOR: Diego Rincon.
PRODUCTION: Pete Howells, Paul Edwards, Tony Strakas.
PROJECT DEVELOPMENT: Ray Marston (Editor), Steve Ramsahadeo.
READER SERVICES: Alan Carlton (Man).
ADVERTISING: Chris Surgenor (Man), David Dinfield, Joy Cheshire.



CONTENTS

| | |
|---|-----------|
| NEWS | 5 |
| <i>Whats new this month?</i> | |
| NEXT MONTH'S ETI | 9 |
| <i>News of the April issue of our sister magazine</i> | |
| TANGERINE REVIEW | 11 |
| <i>An upmarket VDU investigated</i> | |
| BITS, BYTES AND BAUDS | 15 |
| <i>The jargon of computers explained</i> | |
| TRITON COMPETITION RESULTS | 22 |
| <i>Have you won a TRITON?</i> | |
| NEXT MONTH'S CT | 24 |
| <i>What have we got planned?</i> | |
| INTRODUCING BASIC | 25 |
| <i>Teach yourself computer talk</i> | |
| S100 PRINTER: PROJECT | 29 |
| <i>Low cost hard copy</i> | |
| CARD SHARP | 42 |
| <i>A games program that tests your memory</i> | |
| ASIAN COMPUTERS | 47 |
| <i>Low cost computers from the Far East</i> | |
| MICROBIOLOGY | 49 |
| <i>A detailed look at the 6800 and 6500 MPUS</i> | |
| TRITON MOTHERBOARD AND 8K RAM CARD: PROJECT | 55 |
| <i>Increase the power of your TRITON</i> | |
| HARD LINES | 64 |
| <i>Hardware tips from readers</i> | |
| SOFT SPOT | 68 |
| <i>Software programs and ideas</i> | |

EDITORIAL

With this issue Computing Today goes from its embryonic state as a supplement in ETI to a fully fledged magazine in its own right. With all the advantages in space and resources this brings we shall continue the trend set in the early stages of the Computing Today supplements plus a lot more.

The contents of this first issue reflect the diverse nature of the computing field with items ranging from detailed hardware features to a tutorial series on the BASIC language.

Our two constructional projects are, we believe, the first such projects to appear in a computing magazine with all the details necessary to complete the design within the pages of the journal. The S100 printer will provide valuable hardcopy at a price far below many commercial alternatives while the TRITON expansion will extend the capabilities of the already versatile DIY computer published in our sister magazine ETI.

On the software side we continue with our tutorial series on BASIC and publish a couple of programs written in this language. One of these is purely for fun, the intriguing Stomper, game while the other emphasises the educational potential of the computer with a Geography Test program.

Between these major items is spread a host of other features. Microbiology, with a detailed look at the 6800 MPU and an item looking at what the gentlemen from the Far East are doing with MPUs.


We hope you'll like the contents of this first issue but if we've got it wrong please write and tell us so. To those of you who have got systems we'd like to ask the question "what are you doing with them" — please write and tell us.

Gary Evans

Computing Today International is normally published on the third Friday of the month prior to the cover date.
COPYRIGHT: All material is subject to world wide Copyright protection. All reasonable care is taken in the preparation of the magazine to ensure accuracy but CT cannot be held responsible for it legally. Where errors do occur a correction will be published as soon as possible afterwards.

EDITORIAL AND ADVERTISEMENT OFFICE
25-27 Oxford Street, London W1R 1RF. Telephone 01-434 1781/2 Telex 8811896

This Is The Famous



SPECIFICATIONS

The £99.95 ELF 11 computer features an RCA COSMAC COS/MOS 1802 8-bit microprocessor addressable to 64K bytes with DMA, interrupt, 16 registers, ALU, 256 byte hex keyboard fully decoded so there's no need to waste memory with keyboard scanning circuits, built-in power regulator, 5 slot plug-in expansion bus (less connectors), stable crystal clock for timing purposes and a double-sided, plated-through pc board plus RCA 1861 video IC to display any segment of memory on a video monitor or TV screen along with all the logic and support circuitry you need to learn every one of the RCA 1802's capabilities.

£99.95

PLUS 8% V.A.T.

ELF 11 Computer

Stop reading about computers and get your hands on one! With ELF 11 and our new Short Course by Tom Pittman, you can master computers in no time at all! ELF 11 demonstrates all 91 commands an RCA 1802 can execute and the Short Course quickly teaches you how to use each of the 1802's capabilities.

ELF 11's video output lets you display an alphanumeric readout or graphics on any T.V. screen or video monitor and enjoy the latest T.V. games.

But that's not all, once you've mastered computer fundamentals ELF 11 can give you POWER with add-ons that are among the most advanced found anywhere. American IEEE chapters plus hundreds of universities and major corporations have chosen the ELF 11 to introduce their students and personnel to microprocessor computing!

Learn The Skill That May Soon Be Far More Important Than Your College Degree!

The ability to use a computer may soon be more important to your earning power than college degree. Without a knowledge of computers you are always at the mercy of others when it comes to solving highly complex business, engineering, industrial and scientific problems. People who understand computers can command MONEY and to get in on the action, you must learn computers. Otherwise you will be left behind.

ELF 11 is the F.A.S.T. Way to Learn Computer Fundamentals!

Regardless of how minimal your computer background is now, you can learn to programme a computer in almost no time at all. That's because Netronics has developed a special Short Course on Microprocessor And Computer Programming in non-technical language that leads you through every one of the RCA COSMAC 1802's capabilities so you'll understand everything ELF 11 can do and how to get ELF 11 to do it!

All 91 commands that an 1802 can execute are explained to you, step-by-step. The text, written for Netronics by Tom Pittman, is a tremendous advance over every other programming book in print.

Keyed specifically to the ELF 11, it's loaded with "hands on" illustrations. When you're finished, ELF 11 and the 1802 will no longer hold any mysteries for you. In fact, not only will you be able to use a personal computer creatively, you'll also be able to understand computing articles in the technical press.

If you work with large computers, ELF 11 and our Short Course will help you to understand what makes them tick.

A DYNAMITE PACKAGE FOR JUST £99.95 plus 8% V.A.T.

With ELF 11, you learn to use machine language — the fundamental language of all computers. Higher level languages such as FORTRAN and BASIC must be translated into machine language before a computer can understand them. With ELF 11 you build a solid foundation in computers so you really know what you're doing, no matter how complicated things get.

Video output also makes ELF 11 unique among computers selling for such a low price. Attached to your T.V. set, ELF 11 becomes a fabulous home entertainment centre. It's capable of providing endless hours of fun for both adults and children of all ages! ELF 11 can create graphics, alphanumeric displays and fantastic video games.

Only a low cost R.F. Modulator is required to connect ELF 11 to your T.V. aerial socket! (To order one see coupon below.)

H.L. Audio, 138 Kingsland Road, London E2 8BY

H. L. AUDIO LTD., DEPT. ET1, 138 KINGSLAND ROAD, LONDON E2 8BY

NOW AVAILABLE FOR ELF 11

- ☐ Tom Pittman's Short Course on Microprocessor & Computer Programming teaches you just about everything there is to know about ELF 11 or any RCA 1802 computer. Written in non-technical language, it's a learning breakthrough for engineers and laymen alike. £5.00 post paid!
- ☐ Deluxe metal cabinet with plexiglas dust cover for ELF 11 £29.95 plus £1.50 p&p. R.F. modulator for use with T.V. set £3.00 post paid.
- ☐ GIANT BOARD kit with cassette I/O, RS 232-C, TTY I/O, 8-bit P.I.O. decoders for 14 separate I/O instructions and a system monitor/editor. £39.95 plus £1.00 p&p.
- ☐ KLUGE (prototype) BOARD accepts up to 36 IC's £17.00 plus 50p p&p.
- ☐ 4K static RAM kit. Addressable to any 4K page to 64K £89.95 plus £1.56 p&p.
- ☐ Gold plated 86 pin connectors (one required for each plug-in board). £5.70 post paid.
- ☐ Professional ASC11 Keyboard kit with 128 ASC11 upper/lower case set. 96 printable characters, onboard regulator, parity, logic selection and choice of 4 handshaking signals to mate with almost any computer. £64.95 post paid.
- ☐ Deluxe metal cabinet for ASC11 Keyboard £19.95 plus £1.50 p&p.
- ☐ ELF 11 Tiny BASIC on cassette tape. Commands include SAVE, LOAD, X = 0, 26 variables A-Z, LET, IF, THEN, INPUT, PRINT, GO TO, GO SUB, RETURN, END, REM, CLEAR, LIST, RUN, PLOT, PEEK, POKE. Comes fully documented and includes alphanumeric generator required to display alphanumeric characters directly on your T.V. screen without additional hardware. Also plays tick-tack-toe plus a drawing game that uses ELF 11's hex keyboard as a joystick. 4K memory required. £14.95 post paid.
- ☐ Tom Pittman's Short course on Tiny BASIC for ELF 11 £5.00 post paid.
- ☐ Expansion Power Supply (required when adding 4K RAM) £19.95.
- ☐ ELF BUG TM Deluxe System Monitor on cassette tape. Allows displaying the contents of all registers on your T.V. at any point in your programme. Also displays 24 bytes of memory with full addresses, blinking cursor and auto scrolling. A must for the serious programmer! £14.95 post paid.
- COMING SOON:** A/D, D/A converter, Light Pen, Controller Board, Colour Graphics & Music System and more!

*Plus VAT at 8% on price and postage

H. L. AUDIO LTD. DEPT. ET1

138 KINGSLAND ROAD
LONDON E2 8BY
(TEL 01-739 1582)
Sole European Distributors for Netronics
R&D Ltd. U.S.A.

YES! I want to run programmes at home and have enclosed ☐ £109.56 including postage and V.A.T. for RCA COSMAC ELF 11 kit ☐ £5.94 including postage and V.A.T. for power supply (required) ☐ £5.95 including postage and V.A.T. for RCA 1802 Users Manual ☐ £5.95 including postage and V.A.T. for Short Course On Microprocessor and Computer programming ☐ I want mine wired and tested with power supply, RCA 1802 Users Manual and Short Course included for just £164.10 including postage and V.A.T. ☐ I am also enclosing payment (including postage and V.A.T.) for the items checked at the left.

Total enclosed

USE YOUR ☐ ACCESS ☐ BARCLAYCARD
Interbank
Account No

Signature ☐ CREDIT CARD PHONE ORDERS ACCEPTED. 01-739 1582

PRINT

Name

Address


Exp date

DEALER ENQUIRIES INVITED

CALL OR WRITE FOR WIRED PRICES

SEND TODAY

News



HOT PRINTER

An 80-character thermal graphics printer able to print at speeds up to 480 full lines per minute with high resolution, has been introduced by Hewlett-Packard. It is believed to be the fastest full-line thermal graphics printer presently available.

Intended for use in a quiet environment, the printer is simple to operate. Designated Model 9876A, it contains a standard ASCII 128-character set featuring both upper and lower case, and control characters. Each character is composed on

a 5 x 7 matrix of 300-micron square dots. Two row positions above and below each character allow for special marks or ascending and descending characters.

Seven additional character sets, which exist in the printer at all times, can be accessed through software. These include French, German, Katakana, Spanish, Danish/Norwegian and Swedish/Finnish. Also, the user can create up to seven new characters at a time by defining special dot patterns which are then stored in the printer's memory.

SMART THINKING

The question of how we measure the intelligence of a machine is one that many people are giving a lot of thought to nowadays.

Dr. Chris Evans of the NPL has come up with six areas into which he feels a machine's ability should be broken down into and the overall intelligence computed from these. Rather like IQ tests measuring different areas of human performance.

We shan't go into much detail as to what Chris Evans means by each heading but perhaps it will set some of you thinking enough to write to us with your views.

Dr. Evans believes that a machine performance should be broken down into the following areas.

1. The machine's ability to capture data from its environment.
2. The machine's ability to store information.
3. The processing speed of the machine.
4. The speed at which the software of the machine may be changed.
5. The efficiency of the machine's software.
6. The range of the machine's software.

Any comments?

PET TO TELETYPEWRITER 33 BI-DIRECTIONAL INTERFACE

This interface package is a combination of hardware and software which provides two-way communication between a Commodore Pet and a Model 33 Teletypewriter. This not only provides the Pet with a printer, but, where the Teletypewriter is suitably equipped, with paper tape input and output and a full-size keyboard. Comprehensive documentation is included.

Hardware

The standard package is designed for a 20 milliamp current loop, but compatibility with 60 mA or RS232 can be provided by special order.

Connectors are provided to the Pet user port and the second cassette port but, by request, the package will be adapted to operate via the IEEE port. It is also possible to arrange for a second cassette unit to be operated simultaneously with the Teletypewriter.

A 'D' type connector to the Model 33 is fitted as standard.

Software

Two machine-coded programs are included in the package. One resides in the second cassette buffer, the other reserves RAM at the top of 8K and the coding resides there, so that the second cassette unit can be used. By special order programs can be provided for Pets fitted with extra memory.

After the interface program has been run, any programs may be loaded. These programs may send to and receive from the Teletypewriter by including short sub routines provided in the package. Detailed instructions are included.

A BASIC program is available as an extra giving a routine to list an entire program on the printer without operator intervention.

Allen Computers,
16 Hainton Avenue,
Grimsby,
South Humberside DN32 9AS.

NASCOM 1 AT MICRODIGITAL



The Microcomputer only shop providing a complete service from a single chip to a commercial data processing installation. Well worth a visit for a look around and a chat.

nm

NASCOM I.....£178.20

From 10th February 1979.
Includes VAT and carriage.

The Nascom I was exceptional value for money at the old price, now it is unbeatable. The Nascom I is the best possible introduction to the world of personal computing, yet it has the power and flexibility to be expanded into a full data processing system.

The specification includes powerful Z80 processor, parallel I/O controller with two 8 bit ports. UART driving cassette interface or most serial peripherals, video output to plug in the ariel socket of your T.V., 2K bytes of RAM (1K user and 1K video), proven 1K byte monitor program in EPROM and a spare EPROM socket.

The kit is complete, all that is required is a power supply a domestic T.V. and a domestic cassette recorder.

POWER SUPPLIES

There are two power supplies available, a 3 amp supply which will power the basic kit and some expansion and an 8 amp supply with toroidal transformer which will power a very large system. Both supplies can be mounted in the vero frame.

3 amp P.S.U. kit.....£26.46
8 amp P.S.U. kit.....£64.80

EXPANSION

Nascom I is expanded by connection to a buffer board which creates a 77 way bus structure "NASBUS" into which expansion boards plug directly. The bus structure is carried along a motherboard which allows future boards to be added and to keep your computer neat the Nascom I, power supply, buffer board, mother board and expansion boards can all be mounted in a vero frame.

Buffer Board.....£35.10
Mother board.....£10.26
Mini Motherboard.....£3.13
Vero frame.....£31.86

NASBUS

The 77 way Nasbus has the following advantages:—

1. Uses standard Veroboard as a motherboard and Standard 0.1" single sided edge connectors for expansion cards. These components are readily and cheaply available.
2. The bus structure leaves 8 spare data lines and 4 spare address lines for future use of 16 bit processors.
3. The power lines are regulated, on board regulators are therefore not needed which obviates the necessity for fan assisted cooling.

All prices include VAT and Carriage

4. All cards use lower power, low noise shottky buffering which means the bus is quiet and does not need sophistications like active termination or interleaved ground planes.
5. Expansion boards are standard 8" x 8" vero DIP boards which are economic and give a good useable area.

MEMORY

The memory expansion board can carry 16 dynamic RAM chips, these can be either 4K bit or 16K bit chips and the board is offered with 8, 16 or 32K bytes of RAM. The 16K board can be expanded to 32K by plugging in 8 more 4116 chips.

The memory expansion board also has room for 4 2708 UVEPROMS each of 1K bytes and a lot of pre-programmed systems software is available to fit these sockets.

8K RAM board kit.....£91.80
16K RAM board kit.....£151.20
32K RAM board kit.....£216.00
Set 8 x 4116.....£75.60
Additional 2708.....11.34

INPUT/OUTPUT

For people wanting to use more peripherals than the standard kit allows for, Nascom are producing an I/O board which can carry a counter timer chip and a number of PIO's and UARTS. This will be available in March.

I/O board.....£37.80
CTC.....£8.64
UART.....£5.94
PIO.....£8.64

BASIC

To allow high level language programming Nascom have produced a 2K Tiny basic and a 3K Super Tiny Basic in 2 or 3 2708 EPROMS respectively. Also available is an 8K Microsoft precision floating point basic in 8 2708's which will be available in April on a single 64K bit ROM to fit the EPROM board.

Tiny Basic.....£27.00
Super Tiny Basic.....£37.80
8K Basic (8 x 2708).....£108.00
8K Basic (ROM).....£43.20

EPROM BOARD

Available in March this board will carry 8 x 2708 UVEPROMS and the 64K bit ROM containing basic. The board can also be used for burning in 2708 UVEPROMS.

EPROM BOARD.....£43.20

GRAPHIC BOARD

Allows high resolution graphics on your Nascom I. Contains 4K of RAM.

Graphics board.....£102.60

MONITOR

Nascom have written a new monitor, T4 the most powerful yet available for this machine it contains many desirable features not found on any other monitor. T4 comes in 2 x 2708 to plug into the main Nascom I board.

Nasbug T4.....£27.00

FIRMWARE

A powerful editor assembler zeap 15 available to run under Nasbug in 3 x 2708 or on tape. ICL Dataskill have produced a letter Editor available in 2 x 2708.

Zeap (tape).....£32.40
Zeap (Eprom).....£48.60
Letter Editor.....£75.60

THE FUTURE

In the near future a mini-floppy disk system will be available with either single or double drive. These will probably offer in excess of 1/2 a megabyte and 1 megabyte respectively at prices that will allow even the hobbyist to have a large data base. To take full advantage of the business and scientific uses opened up by disks Nascom intend to release several high level languages. Looking further forwards Nascom is a developing product, and the fact that many thousands are now in use will ensure that the latest in computer technology will be available at a competitive price.

OPENING HOURS: 9-5.30 Monday to Saturday.
Friendly, expert staff always on hand!

Phone in your Access/Barclaycard Number on 051-236-0707

or complete this order form

PLEASE SEND ME:

.....
.....
.....
.....

.....
.....

I ENCLOSE:

CHEQUE/POSTAL ORDER NO.....
BARCLAYCARD NO.....
ACCESS CARD NO.....
NAME.....
ADDRESS.....

COMPLETE AND POST TO

MICRODIGITAL LTD. 25 BRUNSWICK STREET LIVERPOOL L2 0BJ Tel: 051-236 0707

News

CUSTOMS CURRENCY CONVERSION

Dear Sir,

Ref: Letter, page 24, Computing Today, February edition, from Customs and Excise.

I once ordered some goods from an American firm as a result of their advert in a British magazine, unfortunately this firm stated the value on the Customs declaration slip to be "20" with no units. As the package originated in America, British Customs decided that this meant \$20 whereas the value stated on the invoice inside the packet was £20 as I had paid by Sterling cheque.

Now of course I am guilty of "making a false statement on a customs declaration" despite the fact that I made no statement at all and neither did the American company make any false statement, nevertheless Customs and Excise form Judge and Jury and I am clobbered for a "penalty" for my wrongdoing.

Would-be purchasers from America be warned, not only can you be "done" for VAT and duty but also for a penalty payment as well, purely due to some overworked customs official quoting the rule book.

Yours sincerely,
Peter G. Dunkley.


GROWING UP WITH NASCOM

The NASCOM 1 DIY computer kit has been with us for some time now and was reviewed in the first of the Computing Today supplements printed in ETI. Until recently however there has not been any expansion for the basic NASCOM set up available. That has changed now. NASCO who manufacture the NASCOM 1 have introduced a buffer board plus expansion memory cards along with a Tiny BASIC in EPROM that many people have been eagerly awaiting. Meanwhile Comp. Components have introduced an S100 adaptor for the NASCOM 1 that will allow boards to this popular BUS

HEATH KIT KAT

The latest catalogue from Heathkit has a number of additions to their range of personal computer kits on display. Among them are floppy disks for both the H8 and H11A systems and what looks like the bargain of the year — the H14 line printer.

The printer has both upper and lower case capability and prints the standard 96 character ASCII set as a 5 × 7 dot matrix. Line length is selectable at 80, 96 or 132 characters while line spacing is six lines per inch with eight software selectable. Baud rates are between 110 and 9600. The printer allows the use of edge punched fan paper forms from 2.5in. to 9.5in. in width. In kit form this cornucopia of facilities will cost



you just over £300. We've ordered one and will let you know in how many bits the kit is when it arrives.

Meanwhile if you want to know more about Heathkit's range of computers send them 20p for their special computer brochure. Heath (Gloucester) Ltd., Gloucester GL2 6EE.

MORE BIG RAM

Motorola have announced a 65,536 × 1 dynamic RAM.

The next entry in the 64K dynamic RAM race, the Motorola MCM6664, has the impressive set of credentials that is typical of this new generation RAM.



- Single plus 5 volt power supply
- 150 ns maximum access time
- 250 mW maximum power dissipation
- 16 pin 300-mil wide dual-in-line package
- fully TTL compatible

NEW FROM KALAMAZOO

The introduction of the K2000 small business computer marks the entry of Kalamazoo into the so-called "silicone chip" field. A fraction of the cost of a larger, main-frame computer, the K2000 brings advanced technology within the reach of smaller concerns.

With the K2000, however, Kalamazoo is offering more than just a computer. The company is selling a system: not just the hardware, but with it systems thoroughly researched in the market place, based on 80 years' business systems experience, mostly gained in the service of smaller companies. The K2000 has been designed to make systems work — not (as is often the case) the other way round.


With the system Kalamazoo will provide a total service — hardware, maintenance of that hardware, software, including the tailor-making of systems to suit individual needs, the implementation of those systems, and training: not only for operators but also for middle and senior management personnel, to enable the latter to evaluate the system and obtain maximum benefit from the use of a computer.



Jwm
Electronics

Announce the expandable system for the NASCOM 1* VDU

Microcomputer Accessories



Kit 1 provides 64 graphics pre-programmed on a 2708 EPROM. Other features include inverse video (black characters on white background) and flash (adjustable flash rate). Available now. Price £32.50.

Kit 2 when used in conjunction with kit 1 provides 1Kb of programmable colour graphics. Also included is a colour/audio R.F. modulator enabling direct connection to a colour TV aerial socket (NTSC or PAL). Available April. Price £52.20.

Kit 3 is a programmable sound effects generator which can be used by itself or with kit 2 to provide audio from a TV loudspeaker. The generator can provide "bell" sounds for keyboard, etc. Available April. Price £18.96.

*Conversion boards will shortly become available for other systems.

Keep your Programs in order! Use our Machine Code Programming Sheets, A4 size available now in pads of 100 sheets. Suitable for any micro being programmed in machine code. Price £1.75 each.

All kits supplied include fibre-glass PCB, all components and full documentation. Ready made kits available at £2 extra. Please add 8% VAT and 50p postage/packing.

J.W.M. (Electronics) Ltd., 60 Balcombe Street, London, N.W.1

**TEL. 01-262 2936
01-402 9244**

electronics today

international




What to look for in the April issue: On sale March 2nd

Amp Survey

Build-it-yourself hi-fi continues to flourish, and new designs appear almost daily. Power amplifiers are a favourite in the field, and their numbers, by now, are legion.

Unfortunately there is no way for the home constructor to 'listen in' to a module before he builds it, and thus he is left to fall back on the spec. sheets. Fine if you like it, rotten if you don't.

Next month we're surveying the field, giving full details of all the models we can find, and putting the market leaders against top quality commercial equipment to find out how they sound.



MAINS SEEKER

So you are about to drill the living room wall to hang up those shelves you promised the wife 7 years ago. Black & Decker in hand you advance to the plaster. Wait a minute there a mains socket right beneath.

Doubt sets in — to drill or not to drill — that is the question. Which way do the wires run? Will you black out the entire Universe if you try it? How can you find those wires?

Simple really — just read ETI next month when we have a neat little project to show you exactly where the mains wires lie!



OCTAVE SHIFTER

A superb little circuit to add that instant 'jump' to guitar playing. Operated by a footswitch the effect has a unique sound all its own — not to be missed — no strings attached to this one.

3080

Well ten of them anyway The 3080 is a much under-rated device, and next month's IETs circuit man Tim Orr hopes to put that right with ten ways to use device, all comprehensively explained to help you design the other 3070 circuits yourself.

AMBUSH



Your starship crashes through the void — running between the lines of enemy dreadnoughts to deliver medical supplies to the seiged plant of Tora. In order to preserve energy your ship has no weapons, only its shields and its speed.

Missiles can appear from any direction, and to destroy them you must actuate your shields at the precise moment of impact, thereby conserving power and allowing the engines to keep you moving at Warp Factor 20.

Can you make it through the Ambush and make Capt. Kirk look a cissy?

L.P. ENTERPRISES

Room ET

313 Kingston Road, Ilford

Essex IG1 1PJ, England

From the representatives in Europe . . . for America's leading Micro-computer magazines and books, for the hobbyist, educationist and professional alike, we bring you a little light browsing! Reading maketh a full man . . . Francis Bacon (1561-1626).

| | |
|---|--------|
| Introduction to Microcomputers | |
| Volume 0 The Beginners Book | £5.95 |
| Volume 1 Basic Concepts | £6.30 |
| Volume 2 Some Real Microprocessors (without binder) | £18.95 |
| Volume 2 Some Real Microprocessors (with binder) | £24.70 |
| Volume 3 Some Real Support Devices (without binder) | £11.95 |
| Volume 3 Some Real Support Devices (with binder) | £17.70 |
| 6 Updating supplements for Vol. 2 (for 1 year) | £18.95 |
| 6 Updating supplements for Vol. 2 (for 1 year) | £18.95 |
| 6 Updating supplements for Vol. 2 (for 1 year) | £30.00 |
| 6 Updating supplements for Vol. 3 (for 1 year) | £30.00 |
| 1 Updating supplement for Vol. 2 or Vol. 3 | £5.75 |
| 1 Updating supplement for Vol. 2 | £4.00 |
| 1 Updating supplement for Vol. 3 | £4.00 |

| | |
|-----------------------------------|-------|
| 6800 Programming for Logic Design | £6.30 |
| 8080 Programming for Logic Design | £6.30 |
| Z80 Programming for Logic Design | £6.30 |

| | |
|---|--------|
| Basic Computer Games | £5.50 |
| What To Do After You Hit Return | T.B.A. |
| 8080 Galaxy Game | £7.85 |
| The Colossal Computer Cartoon Book | £3.95 |
| Computer Rage (A Board Game) | £6.95 |
| Artist and Computer | £3.95 |
| Games with a Pocket Calculator | £1.75 |
| Games, Tricks and Puzzles for a Hand Calculator | £2.49 |

| | |
|-------------------------------|-------|
| Z80 Instruction Handbook | £3.50 |
| 8080 Programmers Pocket Guide | £1.95 |
| 8080 Hex Code Card | £1.95 |
| 8080 Octal Code Card | £1.95 |

| | |
|-----------------------------------|--------|
| Dr. Dobbs Journal Vol. 1 | £10.00 |
| Best of Byte | £8.95 |
| Scelbi Byte Primer | £9.95 |
| Best of Creative Computing Vol. 1 | £6.95 |
| Best of Creative Computing Vol. 2 | £6.95 |
| Best of Micro | £5.50 |

| | |
|--|-------|
| 8080A/8085 Assembly Language Programming | £6.45 |
| 6800 Assembler Language Programming | £6.45 |
| 8080 Software Gourmet Guide and Cookbook | £7.95 |
| 6800 Software Gourmet Guide and Cookbook | £7.95 |

| MAGAZINE SUBSCRIPTIONS | U.K. price | Overseas price |
|--|---------------|-------------------|
| Subscriptions start within 3 weeks | | |
| Personal Computing (12 per year) | £16.00 | £17.00 |
| Interface Age (12 per year) | £20.00 | £20.50 |
| Dr. Dobbs Journal (10 per year) | £13.00 | £13.50 |
| Computer Music Journal (4 per year) | £8.50 | £9.00 |
| People's Computers (6 per year) | £8.00 | £8.50 |
| RYTE (12 per year) | £21.00 | £21.00 |
| Creative Computing (12 per year) | £16.00 | £16.50 |
| Calculators and Computers (7 per year) | £10.00 | £10.50 |
| Kilobaud (12 per year) | £20.00 | £21.00 |
| 73 (12 per year) | £20.00 | £21.00 |
| MICRO-6502 Journal (12 per year) | £11.50 | £12.50 |

| | |
|---------------------------------------|-------|
| First Book of Kim | £6.50 |
| Microprocessors from Chips to Systems | £7.95 |
| Microprocessor Interfacing Techniques | £7.95 |
| Z80 Microcomputer Handbook | £7.50 |
| T.V. Typewriter Cookbook | £7.50 |
| T.T.L. Cookbook | £7.50 |
| CMOS Cookbook | £7.95 |
| IC OP Amp Cookbook | £9.50 |
| RTL Cookbook | £4.25 |

| | |
|--|-------|
| Some Common BASIC Programs | £6.30 |
| Computer Programs that Work (in BASIC) | £2.55 |

| | |
|---|-------|
| Introduction to Personal and Business Computing | £4.95 |
| Getting Involved with Your Own Computer | £4.75 |
| Your Home Computer | £7.95 |
| How to Profit from your Personal Computer | £5.50 |
| Reference Book of Personal & Home Computing | £4.95 |
| Hobby Computers are Here | £3.95 |
| New Hobby Computers | £3.95 |
| Understanding Microcomputers and small Computer Systems | £7.95 |

| | |
|------------------------|-------|
| Instant BASIC | £7.50 |
| My Computer Like Me | £2.75 |
| When I speak in BASIC | £6.50 |
| Basic BASIC | £6.00 |
| Advanced BASIC | £6.00 |
| Introduction to PASCAL | £4.00 |

| | |
|---|--------|
| Accounts Payable and Account Receivable | £10.95 |
| Payroll with Cost Accounting | £10.95 |
| General Ledger | £10.95 |

| | |
|--|--------|
| BASIC Software Library | |
| Vol. 1: Business and Games Programs | £17.50 |
| Vol. 2: Maths, Engineering, Statistical Programs | £17.50 |
| Vol. 3: Advanced Business Programs | £26.95 |
| Vol. 4: General Purpose Programs | £7.95 |
| Vol. 5: Experimenters Programs | £7.95 |
| Vol. 6: Miniature Business System | £32.50 |
| Vol. 7: Chess, Medical, Word Processing Programs | £26.95 |

| | |
|--|--------|
| 8080 Standard Monitor | £9.95 |
| 8080 Standard Editor | £9.95 |
| 8080 Standard Assembler | £9.95 |
| Special package: 8080 Assembler, Editor, Monitor | £20.00 |
| Tiny Assembler for 6800 Systems | £5.75 |

| MAGAZINE BACK ISSUES | |
|---------------------------------|-------|
| Personal Computing | £1.75 |
| Interface Age | £2.25 |
| Dr. Dobbs Journal | £1.75 |
| ROM | £1.75 |
| Computer Music Journal | £2.50 |
| People's Computers | £1.75 |
| BYTE | £2.25 |
| Creative Computing | £1.75 |
| Calculators and Computers | £2.25 |
| Kilobaud | £2.25 |
| 73 | £2.25 |
| Micro-6502 Journal | £1.50 |
| Magazine Storage Box (Holds 12) | £1.25 |

HOW TO ORDER

Please note our prices include postage and packing, but not insurance, if wanted add 12p for every £10 of books ordered. Make cheques, PO's etc. payable to:-

L.P. Enterprises.

CREDIT CARDS accepted
BARCLAYCARD VISA/ACCESS
DINERS CLUB/AMERICAN EXPRESS

Phone: 01-553 1001 for Credit Card orders (24-hour service)

Send to address above
Indicate Payment Method:

All Orders must be Prepaid
Total Enclosed £

My cheque, P.O., I.M.O. is enclosed in **Sterling** on **U.K. Bank**

Charge to Barclaycard/Visa/Access/Diners/American Express

Credit Card No. Expiry Date

Name

Address


POSTCODE

Signature

All publications are published in U.S.A. and shipped air-freight by **L. P. Enterprises**. In unusual cases, processing may exceed 30 days.
* At time of going to press, price of binders unknown. Telephone enquiries welcome.

TRADE ENQUIRIES WELCOME

Tangerine Dream



With the current crop of single chip VDUs on the market the Tangerine 1648, with its mass of TTL devices, may seem out of place. This is not the case. The Tangerine offers a flexibility that is just not possible with the cheaper of the single chip VDUs, while the more flexible programmable devices will take some time to filter through to the amateur market and will be expensive at that.

TANGERINE SPECIFICATION

Before going on to describe the kit in detail a quick look at just what the Tangerine offers is in order. The display format is 16 lines of 48 characters. This format is rewirable

to 16×44 in case of TV overscan, a common phenomenon that results in some VDUs losing the first and last characters of each line in the borders of the TV screen. Although a cure can usually be effected by adjustment of the TV's internal controls, most people are reluctant to go »»»




Figure 1 Add-On Graphics Circuit

delving into the insides of their TV making this variable line length a useful feature.

The character set comprises the 96 standard ACSII set displayed as a 9×7 dot matrix with downshift for certain lower case characters. The Tangerine's I/O interface can be configured as either RS232 or as a 20-60 mA current loop serial port. Baud rates are selectable between 75 and 19200, including of course 110 and 300.

Video output from the board is provided as a composite video output. There is also a modulated signal suitable for direct injection to the aerial socket of a standard domestic TV.

IN CONTROL

A number of control facilities are provided by the Tangerine. These are carriage return, line feed, bell, clear page, cursor up, left, right and home. Each of these control characters is wireable to any control character. The bell output is generated on board and consists of a 100 mS burst of approximately 1 kHz at 3 V p-p no-load.

The Tangerine is made up from a number of circuit blocks. The UART and associated circuitry takes care of the parallel to serial and serial to parallel conversions. The on board RAM stores the character field as it is entered and is read out during a TV frame to build up the on screen display. The TV display is produced by a character generator ROM which in conjunction with control logic ensures that the character specified by the RAM is built up on screen. Another section of the VDU takes care of the cursor position. This position may either be altered in the normal way by a character input being detected (it is then incremented by one) or on command from the display

control logic, which upon detecting a cursor control character will alter the cursor's position accordingly.

PACKAGE DEAL

Now to the kit itself. The Tangerine comes beautifully packaged, à la MEK D2, in a ring binder that carries all the documentation plus the PCB and components neatly sandwiched between its pages. This is not a kit for those who have never pointed a soldering iron in anger before, indeed the first thing pointed out in the construction section of the manual is that if the potential constructor is not confident in his ability to assemble the VDU he should return it for a refund, a ready built kit or find a friend to build it for him.

Having said that, anyone who can solder well should be able to build this kit with very few problems. The instructions are clear and unambiguous while the PCB is a high quality plated through product with a special mask that will prevent solder going where it shouldn't.

The documentation supplied with the Tangerine deserves a special mention. As remarked on above the standard of the text describing the construction of the unit is clear and precise. In addition to this section there is a detailed description of the complete circuit and how it works. Together with the complete circuit diagram and board overlay also provided this makes understanding what is happening inside the Tangerine possible. This knowledge is invaluable during fault finding or modification of the basic machine. Such a refreshing change from those scruffy, half complete notes and circuit diagrams that one so often comes across nowadays.

When construction is complete it is only necessary to

Tangerine Dream




Figure 2 Keyboard Test Circuit

connect up a 5 V 800 mA, 12 V and -12 V 50 mA supply and the VDU is ready for operation. Connection details for the various options given above are provided and hooking the Tangerine up to your micro should present no problems.

In addition to the standard micro-VDU-TV set combination, the manual details a number of other applications. Driving seven segment LEDs and operating mains controlled devices are two of the options described.


Items in this section also include hints on how to make up for the fact that as the VDU is of the memory mapped type, there is no addressable cursor. Follow the software hints in this section and that can be overcome. Connecting the Tangerine in a parallel mode is also detailed along with an interesting section on adding a home made graphics ROM.

ROUNDING OFF

The Tangerine represents a high quality VDU system that provides a versatility in operation that is not found in many of the other VDUs on the market. The quality of components is high and when complete the Tangerine should go on to give reliable service for a long time. **CT**

TANGERINE

COMPUTER SYSTEMS LIMITED



**NEW!
READY BUILT
MODULES
NOW
AVAILABLE IN
7 DAYS, KITS
FROM
STOCK**

A fully compatible terminal when used with a keyboard and domestic TV (or monitor), that can replace any serial terminal for a fraction of the cost.

Apart from the regular features that most VDUs have, the 1648 can perform the following;

- ★ Fully controllable cursor.
- ★ Generates 16 lines of 44/48 (selectable) characters in both upper and lower case with any keyboard, even those without an 'alpha' facility.
- ★ Break and repeat also provided.
- ★ RS232 and full current loop I/O provided.
- ★ Full control character decoding – selectable by the user to perform cursor movements, bell, page clear, and for switching any other peripherals with suitable interfacing.
- ★ 10 switchable Baud rates.

All VDUs are supplied with an A4 size ring binder containing 50 pages of comprehensive manual with large A3 fold-out Circuit Diagram and Component layout. Details of graphics, and other applications are also included.

COMING SOON!

We shall be announcing soon the details of our Professional Keyboard available in both kit and ready built versions, with a numeric pad option. Reed keys are used exclusively, it is therefore exceptionally reliable and robust.

Other products to be announced are:

- ★ **Z80** based single-board microcomputer.
- ★ **6800** based single-board microcomputer.
- ★ **3CRT Controller**, an economy VDU module using software to control its functions – also Teletext compatible, with full graphics.
- ★ **Addition Graphics module** for the 1648.
- ★ **Addition Hex Keypad**, for machine coding.
- ★ **Addition μ modem**, for cassette interfacing.
- ★ **Prom Programmer**.
- ★ **Complete monitor-less terminal**.

CUT OUT AND SEND TODAY

TANGERINE COMPUTER SYSTEMS LIMITED

Rivermill Lodge, London Road, St. Ives, Huntingdon, PE17 4BR. Tel: 0480 65666.

Please send the following,

- ☐ Further information.
- ☐ 1648 VDU Kit at £129.50 inc. pp + VAT £10.36.
- ☐ 1648 VDU Built and tested at £154.50 inc. pp + VAT £12.36.

Name:

Address:

Business telephone:

Home telephone: Date:

I enclose a cheque No: for the sum of

£.....INC VAT.

Signature:

Overseas customers should send a bank draft on a London Bank. Include sufficient postage for air/surface mail for 1.3 Kg.

The exciting new
TRITON
 Personal Computer
 exclusively from:

TRANSAM

Complete kit of parts available only £286 (+ VAT)

Basic in Rom: a powerful 2k Tiny basic resident on board, makes Triton unique, easy to use and versatile.

Graphics: 64 Graphic characters as well as full alpha numerics.

Single Board: Holds up to 8k of memory, 4k RAM and 4k ROM, supplied with 3k ROM and 2k RAM.

Memory Mapping: 2 mode VDU, I/O or memory mapped for animated graphics.

Cassette Interface: crystal controlled Modem tape I/O with auto start/stop + "named" file search.

UHF TV Interface: On board uhf modulator, plugs into TV aerial socket.

Comes Complete with KEYBOARD, CASE, POWER SUPPLY, THRO-HOLE PLATED QUALITY P.C.B., FULL DOCUMENTATION POWERFUL 1k MONITOR & 2k TINY BASIC PLUS ALL COMPONENTS INCL. IC SOCKETS. NOTE TV SET & CASSETTE NOT INCLUDED.

EXPANSION: expand your triton simply and easily with our new 8-slot mother-board — complete with its own p.s.u. takes 8 plug in eurocards. Plug in 8k ram card now available.

All components can be bought separately and eleven packs can be purchased on an easy-to-buy scheme. See catalogue.

The P.C.B. alone is £50 + VAT plus £1 for packing and postage.

VAT rate is 8% on all kit components.

TRANSAM

TRANSAM COMPONENTS LTD.
 12 CHAPEL STREET
 LONDON, NW1 TEL: 402 8137

NEXT TO EDGWARE ROAD TUBE STATION MET LINE
 TRITON COMPUTER IS THE TRADE MARK OF
 TRANSAM COMPONENTS LTD



EXPANSION MOTHERBOARD £50

8k STATIC RAM BOARD £97

Full details available in our brand new 1979 computer products catalogue — so order your copy now!

TRANSAM

I am interested in the Triton

Name _____

Address (please print) _____

To TRANSAM COMPONENTS LTD.
 12 CHAPEL STREET, NW1

Please send me the following:

1. A copy of your latest catalogue
I enclose 30p + S.A.E 9" x 7" ☐
2. A copy of the Triton Manual
I enclose £5 + 70p P & P. ☐
3. A complete kit of parts for
Triton Computer, £286 + VAT
+ £4 P & P ☐
4. A Printed Circuit Board
£50 + VAT & £1 P & P ☐

CT1



BARCLAYCARD, ACCESS,
 VISA & MASTER CHARGE
 ARE WELCOME SEND
 YOUR CARD NUMBER WITH
 ORDER



TOTAL ENCLOSED £ _____
 Cheque, Money Order, etc

Bits, Bytes and BAUDs

It seems that every radio amateur is talking about some kind of data transmission or other. There are two standard ways of sending data over radio used by amateurs today. Baudot, named after its inventor, was the earliest form of Teletype code and is still used internationally today, both in commercial and amateur service.

Baudot

Baudot comprises of five "bits" or levels of information per character, which are sent one bit at a time. Each bit is in either the "on" or "1" state or the "off" or "0" state, and in Teletype this represented by a "mark" or "space". "Mark" refers back to the days when morse was recorded on paper tape, and refers to the line being energized, thus marking the paper. Space indicates no current.

Over radio circuits, these marks and spaces are translated into audio tones, such as 2125 Hz and 2975 Hz. The difference between the frequencies of these tones is called the "shift".

If the bits from each character were just sent out right after the bits from the previous, very careful count would have to be kept at the receiving end to determine which was the last bit of one character and the first bit of the next. In practice this would lead to the impossible situation where one noise burst would lead to the destruction of the entire message!

To counteract this problem, "start" and "stop" bits were introduced. A start bit is always a one-bit transition from mark to space and back. This tells the receiving machine to receive the next five bits and decode them as data. When the data bits are sent, the sending machine restores the line to the mark condition, where it will stay until the next start pulse comes along. This means that when the machines are sitting idle, there is always current on the line. When you are sending at the maximum rate, there is always at least 1½ bits of STOP time (STOP time is when the line is MARKING after each character). This allows the receiving machine to get ready for the next character.

This START/STOP mode of operation is the simplest form of mechanical telegraphy signal, and most widely used at slow and medium speeds. Since any timing errors in the receiving machine are compensated for in the STOP time, there is no need to synchronise machines, other than their speed. For this reason, this method is called ASYNCHRONOUS transmission.

Asynchronous

Asynchronous transmission has few disadvantages — and they only become apparent at very high speeds. One such problem is the inefficiency of wasting time sending the START and STOP bits, when they are not needed for data

purposes. However, at speeds used by amateurs, this is a small price to pay for the integrity of data.

One problem that became apparent with the proliferation of computers, and special codes for weather symbols, etc., was the limited number of codes able to be transmitted by Baudot. If you figure it out, there is a maximum of 2^5 , or 32 codes possible with Baudot, so how do we code anything beyond that? The answer lies in the use of the LTRS (letters) and FIGS (figures) keys. These keys give the Baudot system 64 characters. Each key has two characters, lower and upper.

When the LTRS key is pressed, a character is sent which tells the receiving end that the codes that follow are ordinary letters. When it is desired to send numbers you have to precede them with the FIGS character. Each of these FIGS and LTRS signals is a full character and takes a whole seven-and-a-half bit time to send. As you can see, this could severely reduce the actual speed of transmission if you had a lot of letters interspersed with a lot of numbers or figures.

This became apparent over years of use, and led to the introduction of ASCII, the second code used by amateurs (American Standard Code for Information Interchange). This code can legally be used by Canadian amateurs but is restricted in many other parts of the world, including the U.S. It consists of eight bits, of which seven are actual data and one is a PARITY BIT, or check bit. This PARITY BIT is either sent as a MARK or SPACE, to make the number of MARK bits EVEN. By counting the number of MARK bits and checking to see if the number of them is EVEN, the receiving station has a pretty good idea if any data has been damaged by noise. Not all systems use the parity bit, in which case it is usually a MARK. The actual character coding only uses five bits still, and the sixth bit tells whether or not the code sent is a letter or a figure; its presence as a MARK indicates that this character is a figure. Thus FIGS and LTRS keys are not needed.

This leaves one bit to be discussed, and this is called the CONTROL bit. This bit must be a MARK for all PRINTING functions, i.e. all normal characters that will be printed at the other end. If you want to send a code into a computer, for instance, to tell it that the words to follow constitute the address of a message, you can send a character that could normally be a part of the message, but drop the CONTROL bit. The computer will not include the character in the message, but will understand that you want to tell it that the address of the message follows. This can be very handy as it means you can send control codes into a computer and not have to worry about the computer accidentally reading out part of the message as a control code. In the older Baudot system you had to make up weird combinations of three or four characters that could not normally be found in common English.

Some examples of common usage:



| ASCII | BAUDOT | MEANING |
|-----------|----------------|----------------|
| control D | "NNN" | end of message |
| control P | "figs figs HH" | end of address |

Distributor

So we have a Teletype machine sitting there waiting for some signals to turn it on. As you will know, all the action starts when the line goes open for a moment (9.09 milliseconds at 110 baud). This moment is called the *start time*, and it readies the machine to receive the character. From hereon I will refer to a speed of *110 baud* when I mention any timings, since this is a standard speed in data communications. Immediately after the *start bit* has finished, there follow eight bits of data. Each one of these data bits is strobed into the machine by a *rotating distributor* which was started by the start bit. The result is that the code bars will be set or reset in the machine at the correct time. For instance, when the signal condition representing the first bit is presented to the machine along the signal line, the distributor arm will be touching the connection to the circuitry for the first bit and it will be conditioned to either *mark* or *space* by the signal. At the end of this bit, the arm will have moved around to the beginning of the copper plate that is connected to the circuitry for the second bit, and so this circuitry will be conditioned to either the mark or space state by the signal from the line. And so, in this manner, the state of each bit along the line will be sent to a different part of the Teletype machine by the rotating distributor, and at the start of the stop bits, the machine will mechanically turn the data into a printable character.

The keyboard works in a similar manner, except in reverse. As soon as you press a key, in effect you are setting eight little switches to either the closed or open state. Moments later, the keyboard rotator starts rotating (what else would you expect it to do?) and sends the condition of each of these switches in turn as either a mark or space along the line, each bit taking the customary 9.09 milliseconds.

Definitions

What I have described above is the simplest form of serial-to-parallel conversion and parallel-to-serial conversion. In modern telecommunications equipment, these mechanical functions are replaced by solid-state logic. After telling you that, I think a few definitions are in order. *Parallel data* is data that is presented simultaneously on eight wires. These wires, for instance, could be connected to the eight switches on the keyboard that I mentioned earlier. It would be the simplest thing in the world to just connect these wires to the eight electromagnets that condition the mechanical bars of the printer, and in fact this is done in some computer sites where there are short distances involved. This is called *parallel transmission*. However, things being what they are in the business world, money comes first, and it would be eight times as expensive to string eight channels across the country as just one, so the serialization idea came into effect. *Serial data* just means that the bits are sent out one after another all on one wire as described above.

I mentioned earlier that this *serial, asynchronous* method is used most universally on low speed circuits. The reason is that mechanical equipment proliferates and this cannot be adjusted as finely as electronic equipment. The reason for the two start bits is to allow the mass of the rotor to come to rest and stay there awhile before going off on another trip around the circuit. Because the receiving machine starts each cycle at the same time as the sending

machine, a slight variation in the speed of the receiving machine would not be serious.

Rate

Each bit in the above example takes 9.09 milliseconds to send, so it would seem only logical that to get the number of bits per second one would simply divide this into one second, and arrive at 110. However, it is not that simple. There is such a quantity, but it is called the *baud rate*. The actual name "bits per second" has been defined as the number of data bits that can be sent at this speed. As you will remember, for every eight bits just to keep the machine happy. These bits cannot be counted as data bits because they cannot be visibly seen to do anything at the other end. While the system is sending 110 bits per second, only eighty of them are data bits, so if you were to refer to this speed in bits per second, the value would be eighty BPS.

At slow speeds, this terminology is rarely used, since the *baud rate* is more meaningful in *asynchronous transmission*, because it relates more closely to the scientific quantities involved, whereas a businessman would be more interested in how soon he could get the latest Dow-Jones figures, so he would be more interested in the bit rate. To the uninitiated, it is just like comparing RMS power to music power, or peak power, by the hi-fi salesman.

As speeds get faster, mechanical monsters are replaced with solid-state equipment. Since there is no moving rotor to slow down and start again, many of these machines reduce the number of stop bits to one. The machine knows that the tenth bit after one start bit will be the start bit of the next character. In this case, the baud rate would be only slightly higher than the bits per second rate because 33 per cent of the dummy bits have been eliminated.

To take this one step further, you could completely eliminate the start and stop bits. When you do this, however, you are changing things just a little too far, and you do not have asynchronous transmission anymore. You now have *synchronous transmission*. This is only used at very high speeds because any small error, would require the resending of the whole block of data.

Modem

Now that you know what a teletype signal is, how it becomes a series of pulses, and how these pulses are timed, wouldn't it be nice if you could send them to somebody and have some device at the other end make them into teletype signals again?

Well, this is accomplished by a device called a Modem. The word MODEM is a contraction of MODulator-DEModulator. The modulator portion takes the teletype signal from the teletype machine and converts it to two tones. When there is no current in the loop, a tone designated a "space" is sent. When current flows, a tone designated as "mark" is sent.

On the normal amateur teletype channels, such as on the short wave bands, these two tones are 2125 Hz and 170 or 850 Hz above it. (Both with respect to the carrier frequency, which is usually suppressed). At this point I would like to break from standard nomenclature. On UHF and VHF, we have the unique ability to communicate full-duplex (both ways at the same time). If both stations are using the same tones, difficulties will arise because under some circumstances a receiver may pick up signals from its own transmitter causing a garbled printout at the originating station. This problem arose many years ago in the North American TWX network (Teletype Writer Xchange) service. A standard was devised using two separate pairs of tones, one for use by the

ORIGINATING station, and one for the use ANSWERING station. When stations are listening for calls, they are in the ANSWER mode, listening on the pair of tones that the ORIGINATING station is sending on. (1270 Hz mark/1070 Hz space).

While the originating station is sending using 1270 Hz and 1070 Hz, it is also listening on the answer mode transmit frequencies of 2225 Hz for a mark and 2025 Hz for a space.

If station A originates a message to station B, and station B decides he is getting a wrong message, or the printout at his end is garbled, station B can talk back to station A without waiting for him to end his message.

Remember a while ago I talked about the parity bit? If a computer is sending some data to another computer, this full-duplex arrangement will allow the receiving computer to tell the sending computer about any parity errors as soon as they occur. On receipt of this interrupt, the sending computer needs only to re-send the bits that the listener did not get correctly, without having to wait until the end and re-send the whole block.

Another use of this full duplex operation is the so-called ECHO feature used by most computers. When you send a character to a computer, the computer "echoes back" the character. The character prints on your printer only after it has been to the computer and back, via the full-duplex modems. You can thus immediately tell what the computer received — a feature very handy if you are loading programs and want to be sure that the remote computer got your typing correctly.

We have explained the various forms of mechanical telegraphy that have evolved and how signals from these devices can be sent over very long distances by wire and radio. Until the era of the microcomputer, these signalling

Bits, Bytes and BAUDs

systems were limited in their use by the amateur to the sending of messages (and sometimes very cleverly-shaded pictures, using light and dark letter and figure combinations) between two points. Despite the limitations of the Baudot code, and the relative inflexibility of discrete logic, amateurs the world over developed systems for automatically turning on their machines, if and when they were specifically called. Thus, the "autostart" net was formed, a relatively little-known net that generally meets 75kHz up from the bottom edges of some amateur bands, notably 20 and 80 metres.

However, these logic circuits can be very frustrating and time-consuming to design — a fact which has been greatly helped by the availability of the microprocessor to amateurs.

Going back to the previous example of RTTY, an autostart unit consists of many TTL chips, some for decoding the incoming RTTY, some for timing, others for comparing the characters received with the station's call-sign etc. Once the unit is built, it represents an investment of one to two-hundred dollars in a little black box that can only act as an autostart unit. Suppose the amateur then wants to add a Baudot-to-ASCII converter to his setup — he must invest another \$100 in a unit that will perform that service for him, and so on until he has a station full of black boxes that are, all together, probably worth more than his main r.f. transceiver.

Now, with a microcomputer he can replace all those gadgets, save himself a lot of money, and at the same time have a very flexible station that can be easily re-programmed at any time to operate in a slightly or a »

HAPPY MEMORIES

| | |
|------------------|------------------|
| 21L02 450ns 80p | 2114 450ns £5-25 |
| 21L02 250ns 95p | 2114 300ns £6-00 |
| 4116 250ns £9-25 | 2708 450ns £6-75 |

TRS-80 16K Memory Upgrade Kit £75
Full instructions included

S100 16K Static RAM Kit 450ns £195
Bank select, 4K boundaries, all sockets, components and instructions included

ASCII Keyboards from the USA £48-50
59 keys, 128 characters, alpha-lock, repeat, pos. and neg. strobe, send SAE for data sheet

Science of Cambridge Mk 14:
Set of 18 Texas low-profile sockets £2-80

Texas low-profile DIL sockets:
pins 8. 14. 16. 18. 20. 22. 24. 28. 40.
pence 10. 11. 12. 17. 18. 20. 22. 28. 38.

Antex 1mm bits CCN or CX17 45p

Call or write for 74LS price list

VAT included. 20p p+p under £10 order

5 Cranbury Terrace, Southampton,
Hants, SO2 0LH Tel: (0703) 39267

BUILD THE 12,000 ALREADY SOLD NASCOM I COMPUTER

nm

NEW LOW PRICE
£165 + 8% VAT
POST FREE

KITS IN STOCK:

● BRITISH DESIGN ● U.K. BEST SELLING KIT

FULL AFTER SALES SERVICE & GUARANTEE

FEATURES: WE ARE THE SOLE APPROVED LONDON STOCKIST & NATIONAL DISTRIBUTOR
FREE B-BUG WITH EVERY KIT

- Supplied in kit form for self-assembly
- Full documentation supplied
- Fully screened double-sided plated through hole printed circuit board
- Full 48 key keyboard included
- 2K x 8 Ram
- 1K x 8 monitor program providing
- Powerful Mostek Z80 CPU
- 16 x 48 character display interface to std unmodified TV
- TV display memory mapped for high speed access
- On board expansion to 2K x 8 Eprom
- On board expansion for additional 161 0 lines
- Memory may be expanded to full 60K



SOFTWARE

- 1K x 8 monitor program providing
- 8 operating commands: supporting Mem examine, modify, tabulate, copy, break, single step, execute tape, load, tape dump
- Reflective monitor addressing for flexible monitor expansion through user programs
- Monitor sub routines include: delay ASCII coding, binary to hex conversion, clr screen, scroll up, string print, cursor shift and many others

EXPANSION

| | |
|---|---------|
| Expansion buffer board | £25.00 |
| MEMORY KITS (inclusive all hardware) | |
| 8K | £85.00 |
| 16K | £140.00 |
| 32K | £200.00 |
| I/O board with decoders and all hardware except ICS | £35.00 |
| Will accept up to 3 PIOs, 1 CTC and 1 UART. | |

OTHER HARDWARE

| | |
|---|--------|
| 3A power supply for up to 4K expansion | £19.90 |
| 3A power supply for up to 4K expansion MKII | £24.50 |
| 8A power supply for larger than 32K expansion | £60.00 |
| Expansion card frame | £29.50 |
| E Prom Programmer | £40.00 |
| E Prom Eraser | £25.00 |
| Keyboard Cabinet | £3.50 |
| Programming Manual | £4.00 |

NEW 1.4 Operating System in (2) 2708 EPROMS upwards compatible from T2 & B Bug £25.00
TINY BASIC £25.00
SUPER TINY BASIC (with Editor & Machine Utility routines) £35.00
ZEAP ASSEMBLER EDITOR £32.00

● VAT 8% all items except books ● Demonstrations continuous daily We welcome export — Educational and Industrial Enquiries
FREE BROCHURE — SEND S.A.E. 9 1/2 x 6 1/2 STAMP 12 1/2p.

HENRY'S
RADIO

All mail to:
Henry's Radio
404 Edgware Rd
London W2
Phone (01) 723 1008



completely different manner. The whole idea of the microcomputer is that the actual wired hardware is shared between the many functions of the station and it is the easily-changed program that connects the system up in the manner desired for a particular operation.

What is a microcomputer?

Basically, a microcomputer is a device for taking bits of information out of a "memory", performing a series of operations on these bits of information (called "data") as directed by the program, and putting the data back into memory, either in the same place or a different place, as the circumstances require. Sometimes the memory that it is working on is actually a set of flip-flops attached to some external device, sometimes the memory is "core" memory, sometimes it is one of its own internal registers. Either way, there is usually an input, some arithmetic or logic operations, and an output. Sometimes the data are written back into the same memory location as they were read from, thus destroying the original contents of that location, and sometimes they are written into a different location, so that the original data are preserved.

In each case described above, what is happening is a transfer of data. It can be said that *every instruction that a computer performs is a transfer of one kind or another*. The data may be modified *logically* (see Fig. 1) or *arithmetically* (see Fig. 2), but they are always transferred.

What's in a microcomputer?

As we can see from above, *memory* is always handy to have around. Without it, the microcomputer cannot store a program or data.

We also see that we must have some way of getting information from memory into the computer, and getting the results out of the computer and storing them in memory. This is called I/O (Input/Output).

In order to perform arithmetic and logical changes to the data, while it is flowing from memory, through the processor and out again to the memory, we need an *Arithmetic-Logic Unit (ALU)*.

Finally, we need a master controller to put the whole act together and keep everything running smoothly. This is the *control* section.

In most microprocessor units (MPUs) available today, all of the above functions except memory have been included on the one chip (e.g. M6800, 8080, Z80, etc.) — see last month's Microbiology article for more information. All that is required is to add memory, put a program in it, and you have a microcomputer. (Actually, some chips have memory built right onto them, so that the whole system can be made very cheaply, but this is presently restricted to units that are made in the thousands because of the extremely high cost of mask-programming the computers when they are made.)

Fig. 1. 'AND'ing two memory locations together.

Computer compares each bit in location A to each bit in location B — if they are both in '1' then result is 1

| | | | |
|--------------------------------------|------------|---------------------|---|
| 1 | 0 | 0 | . |
| 0 | 1 | 0 | |
| 1 | 1 | 1 | |
| 1 | 1 | = | 1 |
| 0 | 1 | 0 | |
| 0 | 1 | 0 | |
| 1 | 0 | 0 | |
| 0 | 1 | 0 | |
| LOCATION A | LOCATION B | RESULTING PRODUCT R | |
| Mathematical Notation $A \cap B = R$ | | | |

Fig. 2. Arithmetic adding of two memory locations.

Computer adds each bit in location A to the corresponding bit in location B. If they are both 1, a carry is generated to the next bit down.

| | | | | | | | | |
|-----------------------------------|---|---|---|---|---|---|---|---|
| LOCATION A | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 1 |
| LOCATION B | + | 0 | 1 | 0 | 1 | 1 | 0 | 0 |
| LOCATION B | = | 0 | 1 | 1 | 0 | 0 | 0 | 1 |
| Mathematical Notation $a + B = C$ | | | | | | | | |

Bytes, words and data path width

The commonly-used microprocessors are generally "8-bit" machines. This means that every memory location, or *address*, can be visualised as being eight separate flip-flops, each of which can be set to the "1" state (ON) or the "0" state (OFF). Also, every circuit in the I/O and ALU sections is duplicated eight times, so each bit coming out of memory or going back into it is operated on by its own, dedicated circuits. Thus the operations happen concurrently, or in *parallel*. *Data path width* is the number of bits that can be acted upon in this parallel manner by a microcomputer.

Just as you may have already guessed, there also exist serial machines which do not have the multiple circuitry, and must handle data a bit at a time. These machines do have a place in data processing and are not to be scoffed at because of their apparent lack of sophistication, because in many applications they are fast enough for the job and they save the cost of the extra circuitry. (A few dollars a unit can really add up if you make several thousand units.)

Where the numbers fit in

This is all very well, but a computer's not much good unless you can put numbers in and get numbers out. So far, all we've got is a bunch of flip-flops that can be set and cleared in a zillion different ways like Christmas tree lights. The key to the whole matter is in the so-called *binary numbering system*.

When we were children, we learned how to count up to ten. When we reached ten, we had to remember that we had been through our hand once, and start again at 1 — but this time it was 1 for the one in our head and 1 for the finger, making eleven. When we grew older, we realised that the world doesn't end when we have ten fingers up and ten imaginary fingers stored in our head, and thus we mastered the magical transition from ninety-nine to a hundred, this time storing the big 1 in our toes.

This is fine for us humans, but the poor little computer only has one finger. However, to make up for this handicap, he is blessed with eight hands, each with one finger.

The finger (bit) can either be up (1) or down (0). Let's see how he counts.

| | | | | | | | | | |
|-----------------|---|---|---|---|---|---|---|---|---|
| Finger number | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | (We always start at zero when dealing with computers) |
| Human Count: | | | | | | | | | |
| U = Finger up | | | | | | | | | |
| D = Finger down | | | | | | | | | |
| 0 | D | D | D | D | D | D | D | D | |
| 1 | D | D | D | D | D | D | D | U | |
| 2 | D | D | D | D | D | D | U | D | |
| 3 | D | D | D | D | D | U | U | U | |
| 4 | D | D | D | D | U | U | D | D | |
| 5 | D | D | D | U | U | D | U | D | |
| 6 | D | D | U | U | D | U | U | D | |
| 255 | U | U | U | U | U | U | U | U | |

Every time the maximum number is reached in a column, we carry one into the next column on the next count. Isn't this just the same as carrying into the tens column when we get to nine, or the hundreds when we get to ninety-nine?

As you can see, our clever little computer can count up to 255 in human terms. (This is actually a count of 256, since we started from zero.)

So a computer with an eight-bit data path can store a number up to 255. What about a computer that has 12 or 16 bits? Well, we see that in the case of 8 bits, the value 2^8 is 256 — our old friend!

If we look at 2^{12} , we see that a twelve-bit machine can store a number as big as 4096. This is still not very impressive, and we must go to a 16-bit machine before we get a nice big figure, 65,536.

Let's assume we don't want to spend the extra money for a 16-bit machine to give us the 65,536 (usually referred to as 65K) storage capability, but we might occasionally want to do arithmetic using sums this large. The answer is to break up the numbers into two chunks (bytes) of 8 bits each, called the lower byte and the upper byte, and make up a 16-bit word. This is all very well, but we still need to add the numbers 8 bits at a time. This is usually taken care of by a bit called the *carry*. The carry bit is made a 1 if the addition of the two 8-bit numbers in the lower byte makes a number that is too large to store in an 8-bit memory location. What happens in this case is that the carry, if a 1, is added to the sum of the two upper bytes that are added after the lower byte, so that the result of adding the two 16-bit numbers is another 16-bit number.

The use of only 8 bits is called *single-precision* arithmetic.

Bits, Bytes and BAUDs

Where a number is stored as two bytes, the term is *double precision*. If the programmer thinks that he might be dealing with numbers that may be too large to store in two bytes, he may use three bytes or more, each addition process being linked to the one previously done on the byte before it by the carry bit. (For this reason, the carry bit is sometimes called the *link*.) This is known as *multiple precision* arithmetic, but is very rarely used.




Fig. 3 — Data flow through microcomputer

Memory addressing

Every memory location can store 8 bits of data, and can be uniquely addressed by the bits put out by the computer on its address lines. (See next month's article on bus structure, peripherals, and I/O transfers). A memory address is purely a number assigned to a specific location so that the computer can remember where it stored things.

If we use an 8 bit data address, we can reference only 256 locations, which is hardly enough to be of any

ELECTROVALUE

APPOINTED NATIONAL DISTRIBUTORS

NASCOM 1

MICROPROCESSOR KITS

- ★ For Delivery from Stock
- ★ Full supporting Programme of NASCOM Equipment
- ★ Quantity Discounts
- ★ Service you will Appreciate

Franchised
Distributors for
SIEMENS
MOTOROLA
MICROPROCESSORS
ISKRA
RADIOHM
and other brand names
famous for reliability

PRICE LIST AND INFORMATION
Gladly sent on request. Your name will be fed to our computer for use immediately our new catalogue is ready.

ELECTROVALUE LTD

Dept. PC 12, 28 St Judes Rd, Englefield Green, Egham, Surrey TW10 0HB.
Phone Egham (389 from London; STD 0784-3) 3603; Telex 264475.
Northern Branch [Personal shoppers only] 680 Burnage Lane, Burnage, Manchester M19 1NA
Phone [061] 432 4945.

IN SCOTLAND

IN SCOTLAND

NASCOM 1

Z80 Microcomputer kit

Undoubtedly the finest value for money kit available anywhere. Fully socketed.

INTERFACE FOR:

TV (UHF)
TV Monitor
Cassette
Teletype
32k Ram expansion board

May be seen working
9 a.m. - 5 p.m. Mon.-Fri.

Callers welcome

Price £197.50 + VAT (8%)

Buffer Boards and Memory now available.

Callers welcome



STRATHAND
44 ST. ANDREW'S SQ.
GLASGOW G1 5PL
041-552 6731

Callers welcome



Tel. order welcome with Access and Barclaycard

practical value. Most microcomputers have a 16-bit program counter register (memory address of the next instruction to be executed), index register (used for referencing data in tables) and stack pointer (used for remembering where temporary values are stored) — all of which can be manipulated as two 8-bit registers and added as 16-bit numbers.

The next article in this series will show how the microprocessor interacts with its memory via the address and data lines, how peripheral devices are connected, and how transfers take place to peripherals using both interrupts and programmed transfers.

Last month reference was made to such terms as memory address, peripheral address, etc. We saw how an address can be represented as various combinations of bits, and how a 16-bit address has become a popular standard for both mini- and micro-computers, giving 65,536 available addresses, or 64K. ("K" is generally assumed to represent 1024 when talking in terms of memory size.

The Pigeon-Hole

It is sometimes difficult for the layman to understand the concept of memory addresses, and how the computer generates and the memory decodes them. The easiest way to visualise them is to think of a pigeon-hole system as would be used in a hotel for keeping messages for guests. Each box has a number assigned to it. When the desk clerk wants to leave a message for a guest, he simply puts in into a hole with the guest's room number marked beside the hole. Now let us assume that the pigeon-holes have only enough room for one message — i.e. when the clerk puts a second message into the hole, the first one falls behind the board and is lost. If he wants to read something from the last message for a guest, he simply goes to the location (room number) associated with that guest and retrieves the message. Naturally, if he wants to read the third last message that was put into the pigeon-hole he can't, because it has been lost.

An Electronic Pigeon-Hole

A memory system has the same kind of philosophy. You can store only one message (in a computer's case, a fixed number of bits) in any location. If you put another byte into that location, you will destroy the first. You can read it any number of times, however, because each time that you read it, it automatically gets put back into the same memory location for future use, until somebody writes a new byte into that location.

Now let's look at what hardware our system needs. The average MPU can address 65,536 bytes of memory, so it

must have 16 lines coming from it, each being a 1 or 0, to indicate which of the 64K addresses it wants to use. Using a typical MPU chip, such as the 6800, we will need eight data bits to pass the data over from the MPU to the peripheral or vice versa.

We will also need some control signals to tell the peripherals (including memory) to look for their address, and what to do if they find it. Such signals are called "clock", "read", and "write".

Memory Addressing

As a general convention, the address lines can be called A0 to A15, and the data lines will be called D0 to D7.

It is not necessary for every chip in a memory system to decode each one of the 16 address lines. What generally happens is that chips are arranged in convenient blocks, such as may be convenient to fill a particular size of memory board. In this case, logic circuitry on the board looks at all 16 bits (less the number required to address the individual locations on the board) and inhibits all chips on the board when the address signalled by the MPU is outside the range of that board.

A block of memory is assigned a starting address (the bus address of the lowest byte on that block) when the system is built. This is usually done with jumpers soldered to the board, or with DIP switches. In figure 2A, address bits A12 through A15 are assigned to determine the board number. As you can see, there are four bits, giving 16 combinations. Each of these combinations can have 4K addresses, which gives us our 64K (65,536) maximum addresses.

Let's assume that the memory has A12 to A15 set to all zeroes. Since we have specified that this board will be the lowest in memory, then it will respond. However, the chips on the board respond to 1024 addresses. If we just address this board and let the chips decode their 1024 addresses, we will get four chips all thinking that they are being addressed. To prevent this, we take the leftover bits A10 and A11 and use the four combinations of these two bits to select one of four groups of eight chips. Each chip is connected to one data line, the eight chips operating in parallel thus hold the eight bits of each byte.

Reading and Writing

We now see how the MPU can select a group of eight chips of the many on the bus. These selected chips will respond by either putting the eight bits that are stored in their addressed locations onto the bus, or by taking what is on the bus and storing it.

This can be controlled in many ways. Some systems have two separate signals, READ and WRITE. READ, when present, indicates to the peripheral that the MPU wants to input data, so it will put them onto the bus when selected. WRITE, when present, indicates to the peripheral that it should take the information from the bus and store it in its addressed location.

Which Way is Up

At this point a word of warning about READ and WRITE, INPUT and OUTPUT. To avoid the confusion that may arise because the MPU INPUTS while the peripheral is OUTPUTTING, a general convention exists which says that the words INPUT (or READ) and OUTPUT (or WRITE) are always used with respect to the MPU. In other words, OUTPUT data always flow from the MPU to a peripheral, during a WRITE operation, whereas INPUT data always flow from a peripheral to the MPU, during a READ operation. There is one exception to this rule, during NON-PROCESSOR TRANSFERS, which will be dealt with in the next article in this series.

| SIGNALS USED | EQUIVALENT | BUS OPERATION |
|----------------|------------|---|
| CONTROL | HEY! | CLOCK ALERTS ALL PERIPHERALS (INCLUDING MEMORY) TO LOOK FOR THEIR ADDRESS |
| ADDRESS | YOU! | ADDRESS LINES GIVE OUT A SPECIFIC ADDRESS |
| CONTROL & DATA | DO THIS! | DATA ARE EITHER TAKEN FROM OR PUT ONTO THE BUS LINES, DEPENDING ON THE STATUS OF READ/WRITE LINES |

| ADDRESS RANGE | 2 ⁷ | 2 ⁶ | 2 ⁵ | 2 ⁴ | 2 ³ | 2 ² | 2 ¹ | 2 ⁰ | |
|---------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-------|
| \$0000-03FF | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | ROW 0 |
| \$0400-07FF | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | ROW 1 |
| \$0800-0BFF | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | ROW 2 |
| \$0C00-0FFF | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | 2102 | ROW 3 |

Fig 2. Memory block addressing for a typical 4K × 8 board using 2102 (1K × 1) static RAMs. Board is set up as lowest of 16 possible places in a 64K system.

Fast Memory, Slow Memory, and Timing

There are two basic schools of thought on how a peripheral device such as memory should respond to a computer. One way is called a SYNCHRONOUS bus, the other is called ASYNCHRONOUS. Both have their advantages and disadvantages. A SYNCHRONOUS bus is one, such as is used in the 6800 MPU, in which a peripheral is given a precise amount of time to respond to a request from I/O. This time is fixed by the system clock. If the peripheral fails to respond properly during this time, the MPU carries on regardless, not knowing that its commands have not been carried out. Failure of a peripheral to do its job within the allocated time can result in totally unpredictable errors. For this reason, if a SYNCHRONOUS system has various memories attached to it, some very fast to respond, and some comparatively slow, the whole system will have to be slowed down so that the slowest device can operate reliably. The main advantage of this type of system is that it is far cheaper than the ASYNCHRONOUS bus. In the latter, a system is designed with various devices that are called MASTERS* and others that are called SLAVES. (For our present purposes, the MPU is the MASTER and the memory is the SLAVE). This system works in a HANDSHAKE fashion, i.e. one in which the MASTER, who controls the bus, sends out an address, a command, and a MASTER SYNC pulse. The MASTER SYNC pulse is similar to the clock pulse on a SYNCHRONOUS bus, except that as soon as MASTER SYNC is sent, the MASTER turns off its own internal clock. Thus, no more MASTER SYNC pulses are sent, and the bus sits in a state of limbo. When the peripheral is ready, it puts its information on the data bus (or takes information put there by the MASTER) and sends a signal called SLAVE SYNC. Upon receipt of SLAVE SYNC, the MASTER then carries on its work, normally issuing another MASTER SYNC to another address and so on. In this way, slow memories can take a long time to respond, while advantage can be taken of the extra speed of fast memories.

I/O to Slower Peripherals

So far, the only peripherals that have been mentioned are the various memory banks. Memory is fine, but it is so expensive (relatively) that it is only economically feasible to use it for data and programs that are currently being used, and to which access is very quickly needed (in the order of 1-2 μ S). To store programs and data, we use such peripheral devices as tape drives (cassettes, 8-tracks, formatted etc.) discs (floppy, cartridge, multi-platter), paper tape, etc. For data that are not needed as quickly (in the order of 200-300 mS) such offline storage is useful because, even though it is extremely slow to get data from, it allows storage of from 200k bytes to many megabytes which would be prohibitively expensive using core or solid-state memory.

As an example of an I/O transfer, let's use a paper-tape punch on a model 33 teleprinter (TTY). That's about the

slowest peripheral that you can get. I mentioned above that, in the case of an ASYNCHRONOUS bus, the MASTER can be made to wait while a SLAVE goes through its cycle. This is fine if the SLAVE delays the MASTER for a few hundred nanoseconds, or even a few microseconds, but the difference between that and the nine milliseconds required to send one byte to a TTY machine makes it very clumsy to hold up the bus for that long. Also, if the bus in question were to be SYNCHRONOUS, it means that the computer would have to be slowed down to fractions of a thousand times its normal speed — a ludicrous proposition.

What actually happens is that the data for punching are sent to a DATA REGISTER, which appears as a single memory address on the bus. Associated with each DATA REGISTER will be a STATUS REGISTER at another (usually the next sequential) memory address. The purpose of the STATUS REGISTER is to allow the MPU to monitor the progress of the data transfer to the slow device. Let's assume that bit 0 of the STATUS REGISTER indicates that the device which sends to the TTY is sitting idle. We can test for this condition in our program by doing a READ at the STATUS REGISTER address and seeing if this bit is set. We can then do a write of the data that we wish to send to the TTY at the DATA REGISTER address. The logic in the TTY interface will then clear bit 0 of the STATUS REGISTER and start sending the data, bit-by-bit, to the TTY. While this is happening, the MPU is free to address memory and other peripherals, and carry on executing a program. The program, for example, could be calculating an employee's paycheque, while the printer is printing that of the last employee to be processed. Such a program is called a FOREGROUND program. Every once in a while, the program can switch over to another program, called a BACKGROUND program, which checks to see if the PRINTER READY bit (bit 0) is set in the printer interface STATUS REGISTER, and if it is, sends the next data byte to the interface and switches the computer back into FOREGROUND mode. This can go on until the processor runs out of data to process, in which case it just keeps waiting for the printer interface to become idle before it can send another byte.

Why Just Sit There?

As you can see, the above way of doing things gives us the use of the processor while waiting for the peripherals, but we still have to waste time occasionally checking to see if the printer interface is ready. Wouldn't it be nice if the printer interface had some way of telling us when it's ready, so we don't have to keep checking? Well, such a system exists. This is called an INTERRUPT PROCESS, and together with DIRECT MEMORY ACCESS and the use of the console TTY, forms the content of the next article in this series.

CT

*MASTER, SLAVE, MASTER SYNC, and SLAVE SYNC are terms and signals used on the DEC UNIBUS. They are used here as representative terms only.

TRITON

Competition Result

The TRITON cross number competition, that appeared in the second of the Computing Today supplements that appeared in ETI, attracted a large number of entries. This fact plus the large number of correct answers pleased us as we had set the competition with the aim that it should be both fun to do and not require a Degree in Computer Science to complete. Judging by the response it seems as if we have met these goals.

There could only be one winner and the lucky person's name was pulled out of the hat in early January. The winner was Mr. N. J. McAndrew of Colchester who was invited to the prize giving ceremony at Transam's Chapel Street shop a few days later. The bubbly flowed and the lucky Mr. McAndrew took his TRITON off into the pouring rain to begin construction in a few days off work courtesy British Rail.

CT



Below Margaret Hewitt picks out the winner of the competition watched by Mike Hughes (foreground), designer of the Triton, and Gary Evans. Right, the winner receiving his Triton computer, the presentation being made by Nigel Stride and Graham Clifton of Transam, the two gentlemen at the centre of the photograph.



| | | | | | | | | |
|------|------|------|------|------|------|------|------|------|
| 1 8 | 0 | 2 8 | 0 | | 3 3 | | 4 1 | |
| 2 | | 2 | | 5 3 | 2 | 6 7 | 7 6 | 7 |
| 2 | | 8 5 | 9 5 | 5 | | 4 | | 7 |
| 10 4 | 11 0 | 9 | 6 | | 12 1 | 1 1 | 13 2 | 7 |
| | 0 | | 14 0 | 0 | 7 | | 1 | |
| 15 6 | 8 | 16 0 | 0 | | 17 8 | 18 2 | 2 2 | 19 8 |
| 1 | | 1 | | 20 1 | 1 | 0 | | 2 |
| 21 5 | 22 7 | 1 | 23 6 | 0 | | 0 | | 1 |
| | 4 | | 4 | | 24 2 | 1 | 0 | 2 |

W-J E

2708 EPROM PROGRAMMER

Program your own
2708s in approx. 5 mins.

9 5/8" x 7" STAND-ALONE UNIT
COMPLETE WITH

★ 1K x 8 NMOS STATIC RAM

★ 5 DIGIT 7 SEGMENT DISPLAY
FOR ADDRESS AND DATA

★ HEXADECIMAL
KEYPAD FOR
DATA ENTRY


★ POWER SUPPLY
CONNECTOR —
requires
30V unreg. 50mA
12V reg. 75mA
5V reg. 0.5A
—5V reg. 50mA

★ SLIDE SWITCH, SELECT 2708 or 2704

★ RESET KEY

★ ZERO INSERTION FORCE SOCKET TO HOLD EPROM

★ 7 CONTROL KEYS—
Program, Verify, Copy,
Clear, Write Buffer,
Read Prom, Read Buffer



COMPLETE UNIT
ASSEMBLED & TESTED
AS ILLUSTRATED

£130


OPTIONAL
POWER SUPPLY
UNIT

£25

Prices include postage, packing & VAT

WARD-JANES ELECTRONICS LTD.
THE GREEN, WELLINGBOROUGH RD.
RUSHDEN, NORTHANTS
Telephone: Rushden (09334) 59263

A more interesting way to learn



what is a microprocessor?

If you are considering buying a Micro-computer, Development System, or just want to learn more about this exciting technology, then this short introduction to Microprocessors is for you. Comprising of a 72-page book keyed to over two hours of cassette tapes the many aspects of Microprocessors are explained, including Binary and Hexadecimal counting, Internal structure, Operation, Programming Techniques, Devising a program, etc. Learn at your own pace with this valuable addition to your reference library.

To Technical Book Services
P.O. Box 79
Maidenhead, Berks SL6 2EG

ORDER FORM

Please send me copy/copies of What is a microprocessor?
@ £10.75 each inclusive. I enclose remittance £.....

Name


(Print Please)

Address

Registered office: 21 Mincing Lane, London EC1 Registered No 12225

computing today

WHAT'S IN THE APRIL ISSUE



COMPUTER SURVEY

The number of small systems on the market has increased greatly over the past year and the choice of a machine to suit your application.

The April issue of Computing Today surveys some of the more popular small computers and presents in a clear, concise, fashion the capabilities and facilities offered by the different products.

NASCOM ADD ONS

The NASCOM 1 computer has been one of the most successful of the DIY computer kits on the market recently NASCOM introduced a number of extras that allow the basic machine's potential to be considerably enhanced.

We take a look at the expansion board and RAM card as well as the TINY BASIC Nascom are now offering.

EXPANDA PET


The commodore PET has been with us for over a year now but peripherals for the computer have been slow to appear. One of the essential devices in many applications is a floppy disk to provide a system of mass storage that is faster in operation than the tape system of the standard machine.

Next month we review the Compu/Think disk drive and diskmon operating system that will plug straight into your PET.

"YOU CAN TAKE A HORSE TO WATER, BUT SELF-ILLUMINATING DISPLAYS MUST BE L.E.D." !!



"I DON'T CARE IF 'PLAYBOY' MAGAZINE DOES HAVE BUNNY GIRLS - I DON'T LIKE IT!!"



AMBUSH GAME


The April issue of our sister magazine, ETI, carries a project called Ambush. Ambush is an

exciting space war game. Computing Today will carry a program that will allow those of you who don't dabble in electronics to play Ambush on your computer.

CONSUMER SHOW

The recent Winter Consumer Electronic Show in Las Vegas saw the introduction of many new MPU based products including a chess challenger that talks.

Gerald Chevin was there for Computing Today and his report appears in the April issue.



Plus all the regular features, news, softspot, hardlines and next month, a new regular letters page.

Beginning BASIC

Phil Cornes continues with our series introducing the BASIC language.

We hope you got on all right with last time's homework; some sample answers and another question are presented at the end of this article. By now, some of you must be thinking that it is all very well to be able to do vast amounts of calculation and decision making but as yet not a single answer has been printed out by the computer so that we can see the results of our labours. We will rectify this point straight away and go on to look at the main output of the BASIC language.

PRINT

The output statement of the BASIC language is the PRINT statement and an example of its use is given below—

```
10 Y = 1
20 A(Y) = Y*Y
25 PRINT A(Y)
30 IF Y = 5 THEN 9999
40 Y = Y + 1
50 GOTO 20
9999 END
```

This you should recognise as our $Y = X^2$ program from last time to which a PRINT statement has been added as line 25. Now line 20 calculates the value of A(Y).

The output from this program would be as follows—

```
1
4
9
16
25
```

each output being printed below the previous output in a vertical column.

We are going to spend some time on the PRINT statement as what you have just seen is the PRINT statement in only its simplest form, and it has several. Suppose, for example, that we wished to print a table with two columns, the first containing the value of X, the second the value of X^2 for values of X between 1 and 5. This is more or less what our program now does, except that values of X are not yet printed. If we replace line 25 with the following—

```
25 PRINT Y,A(Y)
```

then the output when the program was run would be—

```
1      1
2      4
3      9
4     16
5     25
```

which is just what we wanted. In effect, what happens is that the computer can split each output line on the VDU or teletype into 4 or 5 sections (depending on the number of characters per line) each about 16 characters long. Each of these is called a PRINT ZONE. Whenever a new line is begun on the output peripheral, the first item to be printed starts at the beginning of the first print zone on that line. When (as in our new line 25) a comma is encountered in a PRINT statement, it tells the computer that even though it has already output some data, there is more to follow on the same line so the computer will advance its cursor (the cursor points to the position on a line at which the next character will be printed) across the page to the beginning of the next totally empty print zone. The idea of "totally empty" print zone is brought in here because if you have print zones 16 characters wide and the output for the first print zone contains 18 characters (and so overflows into print zone 2) the next output will start at the beginning of print zone 3 as part of print zone 2 is already occupied.

There is another way of using the same idea as follows—

```
50 .....
60 Y = 2
70 PRINT Y,
80 Y = 3 + Y + Y
90 PRINT Y
100 .....
```

Notice here the comma after the "Y" in the print statement of line 70. As we have already said, this tells the computer that there is more data to follow on the same output line in the next empty print zone, so the output peripheral will wait while the calculation of line 80 is done then this result will be printed by the PRINT statement of line 90 alongside the first value of Y. One further point to note is that there is no comma following the "Y" in line 90, so if there is any subsequent output in the program it will now begin on a new line as the current line is finished with.

The next thing to note is that the PRINT statement has the ability to output messages as well as numerical answers so that, for example, you could get the computer to output— TODAY IS 'WEDNESDAY'

The actual PRINT statement necessary to achieve this would have the following format— 50 PRINT "TODAY IS 'WEDNESDAY' "

You should be able to see from this example that the message has been enclosed within inverted commas in the PRINT statement, and these tell the computer to output whatever is between them direct and not to try to find a numerical value for it. The only character which cannot be placed within the inverted commas for printing is the inverted comma itself. Therefore, if you wish to put a quote into a PRINT statement, you have to use the apostrophe instead, as in the example given.

Consider the following.

```
20 .....
30 X = 3*4/2
```



```
40 PRINT "THE VALUE OF 'X' IS";X
50 .....
```

Line 30 calculates a value for X, line 40 then goes on to PRINT the answer preceded by the message (note the comma). The output looks like this—

```
THE VALUE OF 'X' IS      6
```

Notice the gap between the message and the answer. This arises because there are 19 characters in the message and with print zones 16 characters wide we just overflow into print zone 2 so the numerical value of X is printed in print zone 3. Ideally, we would like the output to appear as follows.

```
THE VALUE OF 'X' IS 6
```

and as you may have guessed this is possible on most machines by replacing the comma with a semi-colon—

```
40 PRINT "THE VALUE OF 'X' IS";X
```

The semi-colon has a similar effect to the comma in that it tells the computer that there is more output to follow on the same line, but the semi-colon differs in that it does not refer to print zones, but tells the computer to use close spacing between items to be printed (this can vary from 0 to 2 spaces depending on your machine).

FOR NEXT

It would be useful if there was an instruction in which we could state "execute this part of the program a number of times and then carry on with the rest of the program." Well (as you might have guessed from the sub-heading) there is such a statement in BASIC, the FOR NEXT statement which has the following general format.

```
FOR (variable) = (lower limit)TO(upper
limit)STEP(increment)
NEXT(value of variable)
```

For example—

```
10 FOR Y = 2TO 6 STEP 1
20 .....
30 .....
40 .....
50 NEXT Y
60 .....
```

Here Y will take all values from 2 (lower limit) to 6 (upper limit) in steps of the increment (in this case, 1) so that the first time line 10 is executed, Y takes the value 2 and the program continues on until we reach line 50 (NEXT Y). We then go back to line 10 and STEP the variable by the increment and carry on to line 50 again. This looping continues until the value of the variable is greater than or equal to the value of the upper limit at which time the FOR NEXT loop is finished with. In our example, program execution would continue with line 60.

The lower limit, upper limit and increment can all be either constants, variables or expressions, so that—

```
FOR Q = A/B TO 19/C STEP R
NEXT Q
```

is a valid FOR NEXT statement.

One point worthy of note at this time is that there are two different ways of implementing a FOR NEXT loop on a computer, both of which are equally usable provided that you know which you have available.

Consider the following program—

```
10 FOR D = 2 TO 1 STEP 1
20 PRINT "TEST IN NEXT STATEMENT"
30 GOTO 9999
40 NEXT D
50 PRINT "TEST IN FOR STATEMENT"
9999 END
```

which statements will be executed in the running of this program? There are two possibilities. There are—

```
10 20 30 9999
or
10 50 9999
```

Why the difference? Well, you should see if you look back that at some point in the execution of a FOR NEXT loop, we ask the question "is the value of the variable greater than or equal to the upper limit". If it is, then we have finished with the loop; if it isn't, then we go round the loop again.

The difference in the two executions is dependant upon whether we ask this question in the FOR statement or the NEXT statement.

Assume we ask the question in the FOR statement, then line 10 will make D equal to the lower limit (in this case 2) and we then compare this with the upper limit and find that it is already greater. So we have finished with our FOR NEXT loop. Control then branches to line 50 to PRINT the message, and ENDS in line 9999.

If, on the other hand, we ask the question in the NEXT statement, then line 10 assigns the lower limit value of 2 to D and control passes to line 20 which forms part of the loop. Even if our test would fail, we go through the loop at least once before we find this out. Many writers consider it to be a 'bad' interpreter that operates in this manner (test in NEXT statement), but in practice I have never encountered any difficulties, and I have found that most of the computers I have used do operate this way.

There is one other point we need to consider about the last program, and that is line 30. It is quite permissible in BASIC to interrupt a FOR NEXT loop before it is completed by branching out of it to some other part of the program, but it is not permissible to branch into a FOR NEXT loop in such a way that the NEXT statement is encountered before the FOR statement: so that, if we were to add—

```
5 GOTO 40
```

to the above program, the computer would throw it out.

Another point to note is that FOR NEXT loops can be nested one within another. For example—

```
10 FOR X = 1 TO 5 STEP 1
20 FOR Y = 1 TO 3 STEP 1
30 PRINT X*Y,
40 NEXT Y
50 PRINT
60 NEXT X
70 END
```


(Note that the FOR NEXT statement in Y is completely enclosed by the FOR NEXT statement in X. This is known as nesting.)

If you were to run this program, you would find that it would produce the following output—

```

1      2      3
2      4      6
3      6      9
4      8      12
5     10     15
  
```

a simple multiplication table.

Initially, lines 10 and 20 set X and Y to 1, line 30 multiplies X and Y together and prints the result. (Notice the final comma in the PRINT statement.) We then jump back to line 20 and increase Y to 2 and print the new value of X*Y alongside the first. This is repeated for Y = 3. When we hit line 40 for the third time, it is ignored, and we go on to execute line 50. All this does, in effect, is to close the print statement of line 30 so that the next output will start on a new line.

Line 60 now takes us back to line 10, where X is increased to 2. Line 20 (when entered from above) now resets Y to 1, and the whole process is repeated with values of Y = 1; 2 and 3 again, and X = 2, producing a second line of output. The third, fourth and fifth lines of output are then produced in the same way using values of X of 3, 4 and 5 and then the program ends.

That's all for this month. Next month we go on to look at some new ways of assigning values to variables and some functions.

Here are possible answers to last times homework, and another question to be answered next month.

TAKE A CARD, ANY CARD

```

10 A = 1
20 R = RND(52)
  
```

```

30 A(A) = R
40 IF A = 52 THEN END
50 A = A + 1
60 GOTO 20
  
```

THE NEW ROUTINE

```



10 A = 1
20 R = RND(52)
30 B = 1
40 IF A(B) = R THEN 20
50 IF B = A THEN 80
60 B = B + 1
70 GOTO 40
80 A(A) = R
90 IF A = 52 THEN END
100 A = A + 1
110 GOTO 20
  
```

THE BRITISH SHUFFLE

```

10 A = 1
20 A(A) = A
30 IF A = 52 THEN 60
40 A = A + 1
50 GOTO 20
60 B = 1
70 R = RND(52)
80 X = A(R)
90 A(R) = A(B)
100 A(B) = X
110 IF B = 52 THEN END
120 B = B + 1
130 GOTO 70
  
```

And this month's homework is to introduce FOR NEXT loops into the above program (The British Shuffle) so as to eliminate some of the IF THEN loops, and also get the program to PRINT out the cards it generates. **CT**



SOFTY the all in one Development and Training Aid with Software-Firmware Copier and Programmer

- ★ Execute programmes on TV screen by resident microprocessor. Programme will halt and display contents of all internal registers at set break points.
 - ★ Develop your firmware on TV screen with true memory mapped hex' display with block shift, displacement calculations, insertion and deletion, byte matching and other assembler functions.
 - ★ Produce your firmware with high speed on board EPROM programmer, approx 2 mins for 2708. Also handles 2704 and 2716.
 - ★ Replaces monitor or debug programme.
 - ★ Plus many other standard features including high speed cassette interface, user programmable function keys, zero insertion force socket.
- Universal Monitor which can be directly connected to ANY external microprocessor in system situ for firmware development. (written by resident micro and executed by external micro).

SOFTY is equivalent to Development Systems costing thousands of pounds. Yet **SOFTY** only costs you for kit and full instructions — £125 + 8% VAT, Built and Tested — £145 + 8% VAT
requires only power supply — full details on request

NASCOM 1 NOW AT THE NEW PRICE OF £165 + 8% VAT

FEATURES

- ★ Supplied in kit form for self-assembly
- ★ Full documentation supplied
- ★ Fully screened double-sided plated through hole printed circuit board



- ★ Full 48 key keyboard included
- ★ 2K x 8 Ram
- ★ 1K x 8 monitor program in Eprom
- ★ Powerful Mostek Z80 CPU
- ★ 16 x 48 character display interface to std unmodified T.V.
- ★ T.V. display memory mapped for high speed access
- ★ On board expansion to 2K x 8 Eprom
- ★ On board expansion for additional 16I/O lines
- ★ Memory may be expanded to full 60K (plus 4K existing on board)

SOFTWARE FEATURES

- ★ 1K x 8 monitor providing
- ★ 8 operating commands, supporting. Mem examine/modify, tabulate, copy break, single step execute tape, load, tape dump
- ★ Reflective monitor addressing for flexible monitor expansion through user programs
- ★ Monitor sub-routines include — delay ASCII coding, binary to hex conversion, clr screen, scroll up, string print, cursor shift and many others.

Standard Features

- Uses the ultra powerful 6502 microprocessor
- 8K Microsoft BASIC-in-ROM
- Full feature BASIC runs faster than currently available personal computers and all 8080-based business computers
- 4K static RAM on board expandable to 8K
- Full 53-key keyboard with upper-lower case and user programmability
- Kansas City standard audio cassette interface for high reliability
- Full machine code monitor and I/O utilities in ROM
- Direct access video display has 1K of dedicated memory (besides 4K user memory), features upper case, lower case, graphics and gaming characters for an effective screen resolution of up to 256 by 256 points. Normal TV's with overscan display about 24 rows of 24 characters, without overscan up to 30 x 30 characters

Requires only a +5V at 3 amps and a ASTEC Videomonitor or a TV and an ASTEC Modulator (see below)

Available during March 79

Order today with No Deposit or Obligation to avoid shortage disappointments

ASTEC SWITCH MODE



POWER SUPPLIES
— MORE WATT PER £

+5V 10A — £63.25*
+5V 20A — £89.75*
+5V 5A
+12V 1A £78.90*
-12V 1A

full range of voltages available



ASTEC 12" MONITOR

UNCASED — £49.95 + VAT
CASED — £59.95 + VAT



Astec modulator UM1111 — E36
General — £2.50 + VAT
Astec modulator UM1233 — E36
Good — £4.00 + VAT

visit our showroom and get hands on experience!

Full data on any of the above on request

All despatch costs inclusive

* Please add 8% VAT unless specified Cheques & P.O.'s to

VEOTIME PRODUCTS

56 Queens Road, Basingstoke, Hants. RG21 1RE.

Tel: 0256 56417. Tlx 858747

(Trade & Export enquiries welcome)



PET CORNER

Lotus now carry an exciting range of products for your CBM PET.

Memory Expansion

- ★ Mounts inside PET
- ★ Runs from PET's own power supply
- ★ Takes 10 minutes to fit
- ★ Includes memory test program
- ★ 6 month warranty

16k £276 + VAT

24k £337 + VAT

32k £394 + VAT

DUAL DRIVE MINIFLOPPY

- ★ Dual minifloppy with 100K per disk side — 200K online.
- ★ DISKMON in ROM on controller board, plugs into Expandapet.
- ★ DISKMON automatically reorganizes free space after SAVE or ERASE.
- ★ Full disc software support.
- ★ FORTRAN & PLM compilers in February.
- ★ 90-day warranty on hardware.
- ★ Initial quantities limited.
- ★ Available early January.
- ★ Phone or write for full details.
- ★ Needs minimum 16K Expandapet expansion memory.

DKH641 Dual Minifloppy System

£916.00 plus 8% VAT

MUSIC BOX

Turns your PET into a programmable musical instrument. You can record and play up to 90 pages, 16 notes per page, change tempo, key, etc.

£37.50 inc. VAT & P&P

T.I.S. WORKBOOKS

A set of 5 workbooks to give you a full understanding of all the ins and outs of your PET more fully than any previous manuals.

£15.95 per set. inc. P&P

Dustcover £17.95 inc. VAT & P&P

Lots of software and other goodies.

Send large SAE.

LOTUS

Tel: 01-981 3993
Telex: 261426
Attn. Lotus Sound

The Age of Affordable Personal Computing Has Finally Arrived

Ohio Scientifics


Superboard II

Full 8K basic and 4K user RAM

Built and tested

£263.84

+ 8% VAT



Ohio Scientific has made a major breakthrough in small computer technology which dramatically reduces the cost of personal computers. By use of custom LSI micro circuits, we have managed to put a complete ultra high performance computer and all necessary interfaces, including the keyboard and power supply, on a single printed circuit board. This new computer actually has more features and higher performance than some home or personal computers that are selling today for up to \$2000. It is more powerful than computer systems which cost over \$20,000 in the early 1970's.

This new machine can entertain your whole family with spectacular video games and cartoons, made possible by its ultra high resolution graphics and fast BASIC. It can help you with your personal finances and budget planning, made possible by its decimal arithmetic ability and cassette data storage capabilities. It can assist you in school or industry as an ultra powerful scientific calculator, made possible by its advanced scientific math functions and built-in "immediate" mode which allows complex problem

solving without programming! This computer can actually entertain your children while it educates them in topics ranging from naming the President of the United States to tutoring trigonometry all possible by its fast extended BASIC graphics and data storage ability.

The machine can be economically expanded to assist in your business, remotely control your home, communicate with other computers and perform many of the other tasks via the broadest lines of expansion accessories in the microcomputer industry.

This machine is super easy to use because it communicates naturally in BASIC, an English-like programming language. So you can easily instruct it or program it to do whatever you want, *but you don't have to*. You don't because it comes with a complete software library on cassette including programmes for each application stated above. Ohio Scientific also offers you hundreds of inexpensive programs on ready-to-run cassettes. Program it yourself or just enjoy it, the choice is yours.

Standard Features

- Uses the ultra powerful 6502 microprocessor
- 8K Microsoft BASIC-in-ROM
- Full feature BASIC runs faster than currently available personal computers and all 8080-based business computers.
- 4K static RAM on board expandable to 8K
- Full 53-key keyboard with upper-lower case and user programmability
- Kansas City standard audio cassette interface for high reliability
- Full machine code monitor and I/O utilities in ROM
- Direct access video display has 1K of dedicated memory (besides 4K user memory), features upper case, lower case, graphics and gaming characters for an effective screen resolution of up to 256 by 256 points. Normal TV's with overscan display about 24 rows of 24 characters, without overscan up to 30 x 30 characters.

Extras

- Available expander board features 24K static RAM (additional mini-floppy interface, port adapter for printer and modem and OSI 48 line expansion interface).
- Assembler/editor and extended machine code monitor available.

Fully built and tested. Requires only +5V at 3 amps and a videomonitor or TV and RF converter to be up and running.

There is enormous interest in Superboard, so order early if you wish to avoid inevitably long delivery dates later this year.

FREE 15-DAY TRIAL

Lotus Sound have had so many enquiries with questions about various aspects of Superboard II that in order to save time and ensure your satisfaction we are offering to return the full price to anyone who returns their machine, in good order, within 15 days of delivery.

SOUND

4 MORGAN ST., LONDON E3 5AB

(Phone for appointment)

Commands

| CONT | LIST | NEW | NULL | RUN |
|------------|-----------|------------|-----------|-------|
| Statements | | | | |
| CLEAR | DATA | DEF | DIM | END |
| GOTO | GOSUB | IF...GOTO | IF...THEN | INPUT |
| NEXT | ON...GOTO | ON...GOSUB | POKE | PRINT |
| REM | RESTORE | RETURN | STOP | READ |

Expressions

Operators

-, +, *, /, ↑, NOT, AND, OR, >, <, <>, >=, <=, =

RANGE 10⁻³² to 10⁺³²

Functions

| | | | | | |
|--------|---------|--------|--------|--------|--------|
| ABS(X) | ATN(X) | COS(X) | EXP(X) | FRE(X) | INT(X) |
| LOG(X) | PEEK(I) | POS(I) | RND(X) | SGN(X) | SIN(X) |
| SPC(I) | SQR(X) | TAB(I) | TAN(X) | USR(I) | |

String Functions

| | | | | | |
|----------------|----------|----------|---------------|----------|----------------|
| ASC(X\$) | CHR\$(I) | FRE(X\$) | LEFT\$(X\$,I) | LEN(X\$) | MID\$(X\$,I,J) |
| RIGHT\$(X\$,I) | | | STR\$(X) | | VAL(X\$) |

Plus variables, arrays and good editing facilities.

To: LOTUS SOUND

4 MORGAN ST., LONDON E3 5AB

Please send me Ohio Scientific Superboard Computer(s)
I enclose cheque / PO for £


Name

Address

CT3

PROJECT: S100 Printer

Low cost hard copy is a reality with our S100 printer project.



While the cost of the large-scale integrated electronics built into computers has dropped, that of the mechanical peripheral devices has not followed this trend. Most printers cost several hundred, if not thousands, of dollars, so when we were shown a new mechanism which costs around £40 we were more than interested.

You rarely get something for nothing and this printer is no exception — it cannot do everything more sophisticated types can. It uses a 60mm wide paper which allows 32 characters per line, and the paper is a special metallized type. However it is still a very useful printer, especially for the hobbyist who doesn't have a grand to spare.

Design Features

As we seem to have standardised on the S100 bus this was the obvious choice for mechanical construction and electrical interfacing. People do offer an interface for the printer; however it requires the computer to be dedicated to it during the print cycle. The computer has to present and hold each character in sequence as »»»

Specification

| | |
|--------------------------------|-------------------------|
| Print format | 7 x 5 dot matrix |
| Number of different characters | 127 |
| Number of characters per line | 32 |
| Printing speed | 2 lines per second |
| Character height | 2.4 mm |
| Interface format | S100 bus compatible |
| Data entry time | 5µs per character |
| Character storage capability | 128 |
| Power supply | +16 V @ 100mA |
| motor stopped | +8 V @ 350mA |
| | -16 V @ 80mA |
| motor running | +16 V @ 200mA |
| | +8 V @ 350mA |
| | -16 V @ 180mA |
| Printer mechanism | EUY-10E023LE (Datac) |
| Paper | EUY-SUB006 |




Fig. 1a. The circuit diagram of the pickup coil and reed switch buffer.




Fig. 1d. The motor drive interface.




Fig. 1b. The — 24 volt power supply.




Fig. 1c. The circuit of the head drive. Although only one channel is shown there are 7 identical circuits.




Fig. 1e. The Main power supply.




Fig. 1f. The main logic diagram.




Fig. 1g. The circuit of the auxiliary memory which can be used to store some of your software.



Buylines

The printer mechanism is available from Datac Limited at Tudor Road, Broadheath, Altrincham, WA14 5TN. We understand that Transam, 12 Chapel Street, London will offer a ready pro-

grammed character generator PROM. The rest of the components are fairly standard and should appear in the catalogues of most large mail order firms.

How It Works

Before starting an explanation of the electronics we will give a description of the printer used. It has a 24 Vdc motor which drives both the paper feed and the head drive. The head is simply a set of seven fine contacts arranged in a vertical line and is moved across the paper from left to right. The "paper" is metallized with a thin coating of aluminium, and by applying a voltage pulse between one of the head contacts and the paper the metallization is burnt off at that point. By applying pulses to each of the seven heads in the correct sequence as the head moves across the paper characters and words can be formed in a 5×7 dot matrix. The pulse required is -24 V for 240-480 μ s with a peak current of around 3 A per head.

At the end of the left to right scan of the head it returns quickly to the left while advancing the paper feed. The head is lifted off the paper on the return pass.

Also in the printer mechanism is a toothed wheel and pickup coil which gives an AC output of about 1 V which is used to synchronise the printing, and a reed switch which closes on the left to right passage of the print head. This is used to indicate the start of the line when printing.

The Electronics

The circuit is designed to operate on the S100 bus, and a proportion of the electronics forms an interface to the bus. The principle of operation of the unit is to present the data representing the first character to an I/O port along with the S100 timing signals to tell the printer circuitry to accept the character, and then repeat this process for up to 128 characters. No characters are printed until 128 characters have been output to the printer or until it recognises a carriage return. Printing starts immediately either of these events occurs and during printing a busy signal is available on the I/O port as no data can be entered while printing is in progress.

The S100 bus has available $+8$ V and ± 16 V unregulated dc supplies, and from these we derive, using three-terminal regulators, both positive and negative 5 V and 12 V supplies. Also required for the printer is -24 V, and we derive this from the ± 16 V supply using a diode pump type circuit. This consists of IC1/4 which is connected as a square wave oscillator running at 400 Hz. Its output drives the transistor buffer stage Q22-Q25 the output of which is a square wave of 32 V p-p. The capacitors C7 and C8, and

the diodes D2 and D3 rectify this to give a negative voltage which if not limited would reach -30 V. However IC1/3 acts as a comparator and when the voltage on pin 6 drops below 0 V, which represents a voltage of -23.5 V, its output will go high, disabling IC1/4. This effectively regulates the -24 V supply.

Before we can print any data we must first store it. The data is presented to IC7 on the Data Out lines, then if the address presented to IC9 and IC10 is correct along with pin 10 (IC2) being high and a high pulse on pin 3 (IC14), the monostable IC2/2 is triggered. This produces a 500 ns wide pulse which enables the three-state buffer IC7, allowing the data to be written into the RAM IC8. At the end of this pulse, a second monostable (IC11/3) is triggered (about 5 μ s) and during this time the contents of the EPROM are examined. If the character just written into the RAM is not a carriage return, pin 9 of that IC (IC9) will remain high. At the end of this 5 μ s period, the address counter IC13 is incremented. The next character can now be entered.

If a carriage return is entered pin 9 of IC5 will go low during this 5 μ s wide pulse. This forces pin 10 of IC11 high resetting the address counter IC13 and clocking the flipflop IC12/2. If a carriage return is not detected but the 128th character has been entered pin 13 of IC13 will go low and this, via C9, will cause a positive pulse on the output of IC11/1 as well as causing the flipflop IC12/2 to be toggled.

Toggling this flipflop the first time causes pin 15 to go high and 14 low. This disables the monostable via IC14/2, and starts the motor. This is controlled by Q16-Q19; if point K is low Q16 and Q18 will turn on hard applying 24 V to the motor. When point K goes high, Q17 and Q19 will turn on, shorting out the motor and stopping it quickly.

Also reset by the carriage return is IC12/1, and a "0" will be applied to pins 1 and 2 of IC3 which holds IC4 reset. Once the motor starts, pulses are generated by the pickup coil. The output of the coil is filtered by R1, 2 and C1, 2 to remove any high frequency interference and is then buffered by IC1/1 which is connected as a schmitt trigger. The output of IC1/1 is used to clock the monostable IC2/1 which generates the 350 μ s wide pulse used for printing.

The reed switch is also filtered by R5, 6 and C3, 4 to remove contact bounce and noise, before being buffered by IC1/2 which is also

connected as a schmitt trigger. The output of this IC is high from the start of the printing line until the start of the head return.

Once the print stroke has commenced the closing of the reed switch toggles the flipflop IC12/1, allowing IC4 to be clocked, IC4 then scans the 3 least significant address lines of IC5 on each successive clock pulse the EPROM is interrogated for 350 μ s. The outputs from the EPROM are used to drive the print head circuitry.

After seven clock pulses IC3/2 detects this and resets IC4 back to zero so forming a divide by seven circuit. This pulse also clocks the RAM address counter IC13 to the next step. In this way, the RAM tells the EPROM what character it wants.

If a carriage return is detected the outputs of IC11/1 and IC11/2 will both go high, resetting IC12/1 preventing any further clocking of IC4. It also resets IC13 and clocks IC12/2 back to its original state where pin 14 is high and pin 15 low.

This allows data to be again entered, but as the reed switch is still closed the motor will continue to run due to the action of IC6/7, 3 until the reed opens. If more than 32 characters were entered before the carriage return, after the first 32 characters have been printed pin 11 of IC13 will go low and the mono formed by C10/R59 causes IC12/1 to be reset, stopping IC4 from being clocked. IC12/2 however is not affected and the motor will continue to run, even after the reed switch opens. The printer then starts a second print stroke and the re-closing of the reed switch clocks IC12/1 allowing printing to continue.

The print head requires a negative 24 V pulse of 240-480 μ s width with a peak current of about 3 A (for only 10 μ s) while the metallization is evaporated. The drive consists of seven identical circuits each with an interface transistor and a drive darlington transistor. One additional transistor is used (Q1) to disable the print head while the EPROM is active during the write mode.

The carriage return detection is performed by the EPROM as part of its programming. As there are only seven heads but eight bits in the memory, the least significant bit is always programmed as "1" except for the carriage return character. While the CR character ψ is programmed in the EPROM it cannot be accessed on this printer.

The auxiliary EPROMs use a standard address decoding and buffering circuit and do not require explanation.

requested by the printer. This involves a fairly lengthy program (124 steps for the MEK 6800D2) as well as tying up the processor.

We therefore chose a different approach using a dedicated memory on the interface to store the characters which can be entered at any speed (up to approximately 5 μ s apart) until either 128 characters (the limit of the memory) or a carriage return has been transmitted. At this point the print cycle starts and no further action is required from the processor. We initially tested the unit using only a keyboard, entering data manually

with the carriage return initiating printing.

This method simplifies the software required and only ties up the processor long enough for it to output data at its own rate.

As we had some space left over on the card we decided to make provision for two additional 2708 EPROMs and their associated decoding/buffering. These are completely independent of the printer logic and can be used to store any software the user wishes. We do use another 2708 as the character generator as we were unable to find a suitable commercial device at a

reasonable price. As this EPROM has 1024 locations, using eight bytes per character, we can have 128 characters. We therefore chose the full upper and lower case font with some Greek and mathematical symbols thrown in for good measure. As we are limited to a 5×7 dot matrix character some of the lower case characters are a bit strange (the ones with tails normally below the line) but are still quite legible.

Construction

As this is an economical printer, it was decided that the expense of a

Parts List

RESISTORS (All $\frac{1}{2}$ W 5%)

| | |
|----------|------------------|
| R1,2 | 10k |
| R3 | 1k |
| R4 | 100k |
| R5—R8 | 10k |
| R9 | 47k |
| R10 | 82k |
| R11,12 | 10k |
| R13—R19 | 470R |
| R20—R26 | 1k5 |
| R27—R33 | 10k |
| R34—R36 | Numbers not used |
| R37—R41 | 1k5 |
| R43 | 1k |
| R44 | 10k |
| R45 | 47k |
| R46 | 1k |
| R47—R50 | 100k |
| R51—R55 | 10k |
| R56 | 1k5 |
| R57 | 1k |
| R58,59 | 10k |
| R60 | 100k |
| R61 | 1k |
| R62 | 10k |
| R63 | 1k |
| R64 | 100k |
| R65 | 1k |
| R66—R73 | 10k |
| *R74—R78 | 10k |

CAPACITORS

| | |
|---------|-----------------------|
| C1—C6 | 10n polyester |
| C7 | 100 μ 25V electro |
| C8 | 220 μ 35V electro |
| C9—C13 | 100p ceramic |
| C14,15 | 10 μ 25V electro |
| C16—C22 | 33 μ 16V tantalum |

SEMICONDUCTORS

| | |
|----------|-------------------------|
| IC1 | LM324 quad op-amp |
| IC2 | 74LS123 dual mono |
| IC3 | 4023 three input NAND |
| IC4 | 4520 dual \div 16 |
| IC5 | 2708 8K EPROM |
| IC6 | 4001 two input NOR |
| IC7 | 81LS97 octal buffer |
| IC8 | 6810 128 \times RAM |
| IC9,10 | 74LS85 comparator |
| IC11 | 4011 two input NAND |
| IC12 | 4027 dual JK flipflop |
| IC13 | 4520 dual \div 16 |
| IC14 | 74LS10 three input NAND |
| IC15 | 74LS02 two input NOR |
| IC16 | 7812 positive 12V reg. |
| IC17 | 7912 negative 12V reg. |
| IC18 | 7805 positive 5V reg. |
| IC19 | 7905 negative 5V reg. |
| *IC20,21 | 2708 8K EPROM |

| | |
|----------|-----------------------|
| *IC22 | 74LS00 two input NAND |
| *IC23,24 | 74LS85 comparator |
| *IC25 | 81LS97 octal buffer |

| | |
|--------|--------|
| Q1—Q8 | BC558 |
| Q9—Q15 | BD675 |
| Q16 | BC548 |
| Q17 | BC558 |
| Q18 | BD140 |
| Q19 | BD139 |
| Q20 | BC548 |
| Q21 | BC558 |
| Q22 | BD140 |
| Q23 | BD139 |
| Q24 | 2N3643 |

| | |
|------|--------|
| D1 | 1N914 |
| D2,3 | 1N4001 |
| D4 | 1N914 |

MISCELLANEOUS

PC board
Datac printer EUY—10E023LE
Four 24 pin sockets
One 16 pin socket and header
Two 8 pole DIP switches
One 15 pin 0.156 inch edge connector

*These components are not required if the additional memory is not needed.

through-hole plated PCB was not warranted. This means that a lot of components are soldered on both sides of the board preventing the use of sockets except for the EPROMs and the 6810 RAM.

The board can be assembled with the aid of the overlay in fig. 2. If the additional EPROMs are not required these ICs and the associated components can be deleted. None of the components in this area are used as feedthroughs for the printer electronics. In the printer circuitry there are two links in the 0V rail and three more leading to the edge connector. If the additional EPROMs are used all the address and data lines are linked to the edge connector as it was not possible (without a plated-through board) to use copper tracks. We used thin enamelled wire of the type where the enamel will melt on soldering for all these links. The numbers on the PCB next to these points indicate the pins on the edge connector to which they are to be linked. Note that the connector is numbered 1-50 on the component side and 51-100 on the copper side.

Connection to the printer is made via a 16 pin IC socket using a piece of ribbon cable and a 16 pin DIP header. »





Fig. 3. The timing chart for the printer



CONNECTIONS

Header Pin No.

- 1 Head common
- 2 Motor -Ve
- 3 Motor +Ve
- 6 Coil-reed common
- 7 Pickup coil
- 8 Reed switch
- 10 Head 5
- 11 Head 4
- 12 Head 6
- 13 Head 3
- 14 Head 7
- 15 Head 2
- 16 Head 1

Printer Pin No.

- 1 Reed switch
- 2 Pickup coil
- 3 Coil-reed common
- 4 Motor +Ve
- 5 Motor -Ve
- 6 Head common
- 7 NC
- 8 Head 1
- 9 Head 2
- 10 Head 3
- 11 Head 4
- 12 Head 5
- 13 Head 6
- 14 Head 7
- 15 NC

Fig. 2. The component overlay. Note that there must be an insulating washer under IC17 and that no additional heat sinks are needed on the voltage regulators.

Table 1

| | | | | | |
|----|---------|---------------------------------|---|---------|-------------------------------------|
| α | 000:000 | 377 363 355 355 363 355 377 377 | @ | 002:000 | 377 203 175 105 125 207 377 377 |
| β | 000:010 | 377 377 201 155 155 223 377 377 | A | 002:010 | 377 201 157 157 157 201 377 377 |
| γ | 000:020 | 377 163 155 201 277 177 377 377 | B | 002:020 | 377 001 155 155 155 223 377 377 |
| δ | 000:030 | 377 223 155 155 163 377 377 377 | C | 002:030 | 377 203 175 175 175 273 377 377 |
| ε | 000:040 | 377 377 343 325 325 377 377 377 | D | 002:040 | 377 001 175 175 175 203 377 377 |
| θ | 000:050 | 377 203 155 155 155 203 377 377 | E | 002:050 | 377 001 155 155 155 175 377 377 |
| ι | 000:060 | 377 377 343 375 373 377 377 377 | F | 002:060 | 377 001 157 157 157 177 377 377 |
| λ | 000:070 | 377 335 353 367 373 375 377 377 | G | 002:070 | 377 203 175 175 155 141 377 377 |
| μ | 000:100 | 377 377 201 367 367 217 377 377 | H | 002:100 | 377 001 357 357 357 001 377 377 |
| ν | 000:110 | 377 337 301 373 367 317 377 377 | I | 002:110 | 377 377 175 001 175 377 377 377 |
| π | 000:120 | 377 357 301 337 301 337 377 377 | J | 002:120 | 377 373 175 175 003 177 377 377 |
| Σ | 000:130 | 377 175 071 105 155 175 377 377 | K | 002:130 | 377 001 357 327 273 175 377 377 |
| Φ | 000:140 | 377 347 333 001 333 347 377 377 | L | 002:140 | 377 001 375 375 375 375 377 377 |
| ψ | 000:150 | 376 316 366 000 366 316 376 376 | M | 002:150 | 377 001 277 317 277 001 377 377 |
| ω | 000:160 | 377 363 355 373 355 363 377 377 | N | 002:160 | 377 001 337 357 367 001 377 377 |
| Ω | 000:170 | 377 315 261 277 261 315 377 377 | O | 002:170 | 377 203 175 175 175 203 377 377 |
| 0 | 000:200 | 377 377 363 355 355 363 377 377 | P | 002:200 | 377 001 157 157 157 237 377 377 |
| 1 | 000:210 | 377 377 377 355 371 375 377 377 | Q | 002:210 | 377 203 175 165 173 205 377 377 |
| 2 | 000:220 | 377 377 355 331 325 355 377 377 | R | 002:220 | 377 001 157 147 153 235 377 377 |
| 3 | 000:230 | 377 377 333 335 325 353 377 377 | S | 002:230 | 377 235 155 155 155 163 377 377 |
| 4 | 000:240 | 377 377 237 157 157 237 377 377 | T | 002:240 | 377 177 177 001 177 177 377 377 |
| 5 | 000:250 | 377 377 267 147 127 267 377 377 | U | 002:250 | 377 003 375 375 375 003 377 377 |
| 6 | 000:260 | 377 333 333 213 333 333 377 377 | V | 002:260 | 377 007 373 375 373 007 377 377 |
| 7 | 000:270 | 377 357 357 253 357 357 377 377 | W | 002:270 | 377 003 375 343 375 003 377 377 |
| 8 | 000:300 | 377 267 157 267 333 267 377 377 | X | 002:300 | 377 071 327 357 327 071 377 377 |
| 9 | 000:310 | 377 367 373 001 177 177 377 377 | Y | 002:310 | 377 077 337 341 337 077 377 377 |
| √ | 000:320 | 377 373 375 203 177 277 377 377 | Z | 002:320 | 377 171 165 155 135 075 377 377 |
| ← | 000:330 | 377 377 377 001 377 377 377 377 | [| 002:330 | 377 377 001 175 175 377 377 377 |
| → | 000:340 | 377 357 307 253 357 357 377 377 | \ | 002:340 | 377 277 337 357 367 373 377 377 |
| ↑ | 000:350 | 377 357 357 253 307 357 377 377 |] | 002:350 | 377 377 175 175 001 377 377 377 |
| ↓ | 000:360 | 377 357 337 203 337 357 377 377 | ^ | 002:360 | 377 337 277 177 277 337 377 377 |
| ↖ | 000:370 | 377 357 367 203 367 357 377 377 | ~ | 002:370 | 377 375 375 375 375 375 377 377 |
| ↗ | 001:000 | 377 377 377 377 377 377 377 377 | ~ | 003:000 | 377 377 177 277 337 377 377 377 |
| ! | 001:010 | 377 377 377 015 377 377 377 377 | a | 003:010 | 377 373 325 325 325 341 377 377 |
| " | 001:020 | 377 377 037 377 037 377 377 377 | b | 003:020 | 377 001 355 355 355 363 377 377 |
| # | 001:030 | 377 327 001 327 001 327 377 377 | c | 003:030 | 377 377 343 335 335 335 377 377 |
| \$ | 001:040 | 377 333 253 001 253 267 377 377 | d | 003:040 | 377 363 355 355 355 001 377 377 |
| % | 001:050 | 377 073 067 357 331 271 377 377 | e | 003:050 | 377 377 343 325 325 347 377 377 |
| & | 001:060 | 377 363 215 145 233 365 377 377 | f | 003:060 | 377 377 357 201 157 277 377 377 |
| ' | 001:070 | 377 377 337 277 177 377 377 377 | g | 003:070 | 377 377 357 327 325 343 377 377 |
| (| 001:100 | 377 377 307 273 175 377 377 377 | h | 003:100 | 377 377 001 357 357 361 377 377 |
|) | 001:110 | 377 377 175 273 307 377 377 377 | i | 003:110 | 377 377 355 241 375 377 377 377 |
| * | 001:120 | 377 327 357 203 357 327 377 377 | j | 003:120 | 377 377 377 377 275 243 377 377 377 |
| + | 001:130 | 377 357 357 203 357 357 377 377 | k | 003:130 | 377 377 001 367 353 335 377 377 |
| - | 001:140 | 377 377 375 363 377 377 377 377 | l | 003:140 | 377 377 175 001 375 377 377 377 |
| . | 001:150 | 377 357 357 357 357 357 377 377 | m | 003:150 | 377 341 337 347 337 341 377 377 |
| / | 001:160 | 377 377 377 371 377 377 377 377 | n | 003:160 | 377 377 341 337 337 341 377 377 |
| 0 | 001:170 | 377 373 367 357 337 277 377 377 | o | 003:170 | 377 377 343 335 335 343 377 377 |
| 1 | 001:200 | 377 377 203 175 175 203 377 377 | p | 003:200 | 377 377 301 327 327 357 377 377 |
| 2 | 001:210 | 377 377 275 001 375 377 377 377 | q | 003:210 | 377 357 327 327 301 375 377 377 |
| 3 | 001:220 | 377 275 171 165 155 235 377 377 | r | 003:220 | 377 377 301 357 337 337 377 377 |
| 4 | 001:230 | 377 173 175 135 055 163 377 377 | s | 003:230 | 377 357 325 325 325 373 377 377 |
| 5 | 001:240 | 377 347 327 267 001 367 377 377 | t | 003:240 | 377 377 337 203 335 377 377 377 |
| 6 | 001:250 | 377 033 135 135 135 143 377 377 | u | 003:250 | 377 303 375 375 301 375 377 377 |
| 7 | 001:260 | 377 303 255 155 155 363 377 377 | v | 003:260 | 377 307 373 375 373 307 377 377 |
| 8 | 001:270 | 377 177 161 157 137 077 377 377 | w | 003:270 | 377 303 375 363 375 303 377 377 |
| 9 | 001:300 | 377 223 155 155 155 223 377 377 | x | 003:300 | 377 335 353 367 353 335 377 377 |
| 0 | 001:310 | 377 237 155 155 155 207 377 377 | y | 003:310 | 377 377 317 367 365 303 377 377 |
| 1 | 001:320 | 377 377 377 311 377 377 377 377 | z | 003:320 | 377 335 331 325 315 335 377 377 |
| 2 | 001:330 | 377 377 375 311 377 377 377 377 | ~ | 003:330 | 377 367 357 223 175 175 377 377 |
| 3 | 001:340 | 377 357 327 273 175 377 377 377 | ! | 003:340 | 377 377 377 021 377 377 377 377 |
| 4 | 001:350 | 377 327 327 327 327 327 377 377 | ~ | 003:350 | 377 175 175 223 357 357 377 377 |
| 5 | 001:360 | 377 377 175 273 327 357 377 377 | ~ | 003:360 | 377 357 337 357 367 357 377 377 |
| 6 | 001:370 | 377 277 177 145 137 277 377 377 | ~ | 003:370 | 377 125 253 125 253 125 377 377 |

Table 2

| | | | | | | |
|---------|-----|-----|-------|-----|---------|-------------------------|
| 001:000 | 333 | 031 | PRINT | IN | PRINTER | CHECK STATUS |
| 001:002 | 376 | 177 | | | CPI | 177Q |
| 001:004 | 312 | 000 | 001 | JZ | PRINT | BIT 7 ZERO? |
| 001:007 | 176 | | | MOV | A,M | LOOP IF YES |
| 001:010 | 043 | | | INX | H | FETCH CHAR |
| 001:011 | 376 | 004 | | CPI | 004Q | NEXT CHAR |
| 001:013 | 312 | 023 | 001 | JZ | END | EOT? |
| 001:016 | 323 | 031 | | OUT | PRINTER | END IF YES |
| 001:020 | 303 | 000 | 001 | JMP | PRINT | OUTPUT CHAR |
| 001:023 | 076 | 015 | END | MVI | A,015Q | ROUND AGAIN |
| 001:025 | 323 | 031 | | OUT | PRINTER | LOAD CR |
| 001:027 | 311 | | | RET | | PRINT CR |
| | | | | | | BACK TO CALLING ROUTINE |

Using the Printer

The CT 641 Printer has been designed to interface most easily to S100-based computer systems, although it can be used with other bus structures, or even no bus at all. If it is plugged into an S100 system, the printer appears to the system to be a single I/O port. To print, the processor simply writes a string of characters in sequence to the output port, terminating with a CR character, whereupon the printer will itself initiate the print cycle, freeing the processor from any housekeeping.



During the print cycle, however, the printer is unable to accept any characters, and signals this fact to the CPU by pulling bit 7 of the input port low for the duration of the print cycle (though this only appears when the input port is addressed). The printer driver routine should therefore check the status of the printer from this port before writing to it.

A general purpose printer driver which incorporates this feature is shown in Table 2. The calling program passes the starting address of the text to be output in the HL register pair, and the routine will then output all the text from there until it encounters an EOT character (004Q, 04H). When it finds an EOT, the routine substitutes a CR and outputs it to the printer to start the print cycle.



The printer input and output ports, although separate, share the same address, which can be set up on the 8-bit DIL switch SW1. In our example, the printer is set up for I/O address 031Q (19H). Although, the routine given is assembled at 001:000Q (0100H), it can easily be reassembled to any other address. Be sure when trying out the program, to initialise the Stack Pointer, as otherwise, the routine will return to 377:377Q and "gallop off into the wide blue yonder", possibly self-destructing for good measure.

Another common trick used to indicate the end of message text is to set the most significant bit of the last character — as this is 7-bit ASCII it will not affect the printer or the CPU. However, the printer driver should recognise this and insert a CR, otherwise nothing will be printed.


The two EPROM sockets are addressed as a contiguous 2 K block of memory — they cannot be split apart. Consequently only 5 bits of address information have to be set on SW2 — one more bit selects which 2708 is addressed, and the final 10 bits are decoded inside the 2708s. »



S100 Printer



CT



technical book service

NEW:

Adams, C. BEGINNERS GUIDE TO COMPUTERS AND MICROPROCESSORS WITH PROJECTS £5.60

Understanding building programming and operating your own microcomputer.

NEW:

Albrecht, B. BASIC FOR HOME COMPUTERS. A self teaching guide £4.75

Shows you how to read, write and understand basic programming language used in the new personal size microcomputers.

Albrecht B. BASIC. A self teaching guide (2nd edition) £4.50

Teach yourself the programming language BASIC. You will learn how to use the computer as a tool in home or office and you will need no special maths or science background.

Alcock, D. ILLUSTRATING BASIC £2.20

This book presents a popular and widely available language called BASIC, and explains how to write simple programs.

Altman, I. MICROPROCESSORS £10.65

Gives a general overview of the technology design ideas and explains practical applications.

Altman, L. APPLYING MICROPROCESSORS £12.00

Follow volume which takes you into the second and third generation devices.

Aspinall, D. INTRO TO MICROPROCESSORS £6.40

Explains the characteristics of the component.

NEW:

Barden, W. Z-80 MICROCOMPUTER HANDBOOK £7.65

Barden, W. HOW TO BUY AND USE MINI-COMPUTERS AND MICROCOMPUTERS £7.75

Discusses these smaller computers and shows how they can be used in a variety of practical and recreational tasks in the home or business.

Barden, W. HOW TO PROGRAM MICRO-COMPUTERS £7.00

This book explains assembly language programming of microcomputers based on the Intel 8080, Motorola MC6800 and MOS Technology MCS6502 micro-processor.

Barna, A. INTRODUCTION TO MICRO-COMPUTERS AND MICROPROCESSORS £7.50

Provides the basic knowledge required to understand microprocessor systems. Presents a fundamental discussion of many topics in both hardware and software.

Bibbero, R. J. MICROPROCESSORS IN INSTRUMENTS AND CONTROL £12.45

Introduces the background elements, paying particular regard to the dynamics and computational instrumentation required to accomplish real-time data processing tasks.

Lancaster, D. TV TYPEWRITER COOK-BOOK £7.75

An in-depth coverage of tv typewriters (tv's) the only truly low cost microcomputer and small display interface.

Lancaster, D. CHEAP VIDEO COOK-BOOK £6.50

Lesea, A. MICROPROCESSOR INTERFACING TECHNIQUES £7.50

NEW:

Leventhal. INTRO TO MICROPROCESSORS £16.70

NEW:

Lewis, T. G. MIND APPLIANCE HOME COMPUTER APPLICATIONS £4.75

NEW:

Libes, S. SMALL COMPUTER SYSTEMS HANDBOOK £5.75

The Primer written for those new to the field of personal home computers.

NEW:

Lippiatt. ARCHITECTURE OF SMALL COMPUTER SYSTEMS £4.35

NEW:

Moody, R. FIRST BOOK OF MICRO-COMPUTERS £3.85

(the home computer owners best friend).

McGlynn, D. R. MICROPROCESSORS — Technology, Architecture & Applications £8.40

This introduction to the 'computer-on-a-chip' provides a clear explanation of the important new device.

McMurrin, PROGRAMMING MICRO-PROCESSORS £5.50

A practical programming guide that includes architecture, arithmetic/logic operations, fixed and floating point computations, data exchange with peripheral devices computers and other programming aids.

NEW:

Nagin, P. BASIC WITH STYLE £4.00

Programming Proverbs. Principles of good programming with numerous examples to improve programming style and producing.

NEW:

Ogdin SOFTWARE DESIGN FOR MICRO-COMPUTERS £7.00

NEW:

Ogdin. MICROCOMPUTER DESIGN £7.05

Peatman, J. B. MICROCOMPUTER BASED DESIGN £19.00

This book is intended for undergraduate courses on microprocessors.

NEW:

Bursky, D. MICROCOMPUTER BOARD DATA MANUAL £5.40

Bursky, D. MICROPROCESSOR DATA £5.40

Includes complete description of the processor. Support circuits, Architecture, Software, etc.

Coan, J. S. BASIC BASIC £7.50

An introduction to computer programming in BASIC language.

Coan, J. S. ADVANCED BASIC £5.30

Applications and problems.

NEW:

Duncan. MICROPROCESSOR SOFTWARE ENGINEERING £13.50

NEW:

Freiberger, S. CONSUMERS GUIDE TO PERSONAL COMPUTING AND MICRO-COMPUTERS £5.50

NEW:

Frenzel, L. GETTING ACQUAINTED WITH MICROPROCESSORS £7.10

This is an invaluable book for those who want to know more about hobby and personal computing.

Gilmore, C. M. BEGINNERS GUIDE TO MICROPROCESSORS £4.75

Gosling, R. E. BEGINNING BASIC £3.25
Introduces BASIC to first time users.

Graham, N. MICROPROCESSOR PROGRAMMING FOR COMPUTER HOBBYISTS £7.00

Haviland, N. P. THE COMPUTATOR BOOK £6.20

Building super calculators and minicomputer hardware with calculator chips.

Heiserman, D. L. MINIPROCESSORS FROM CALCULATORS TO COMPUTERS £4.85

Hilburn, J. L. MICROCOMPUTERS, MICROPROCESSORS, HARDWARE, SOFTWARE AND APPLICATIONS £16.95

Complete and practical introduction to the design, programming operation, uses and maintenance of modern microprocessors, their integrated circuits and other components.

Klingman, E. MICROPROCESSOR SYSTEMS DESIGN £16.95

Outstanding for its information on real microprocessors, this text is both an introduction and a detailed information source treating over a dozen processors, including new third generation devices. No prior knowledge of microprocessors or microelectronics is required for the reader.

Kemeny, J. G. BASIC PROGRAMMING £6.10

A basic text.

Korn, G. A. MICROPROCESSOR AND SMALL DIGITAL COMPUTER SYSTEMS FOR ENGINEERS AND SCIENTISTS £19.00

This book covers the types, languages, design software and applications of microprocessors.

Rao, G. U. MICROPROCESSOR AND MICROPROCESSOR SYSTEMS £20.50

A completely up-to-date report on the state-of-the-art of microprocessors and microcomputers written by one of the leading experts.

Rony, P. H. THE 8080A BUGBOOK: Micro-computer Interfacing & Programming £8.15

The principles, concepts and applications of an 8-bit microcomputer based on the 8080 microprocessor IU chip. The emphasis is on a computer as a controller.

Scelbi. 6800 SOFTWARE GOURMET GUIDE AND COOKBOOK £7.80

Scelbi. 8080 SOFTWARE GOURMET GUIDE AND COOKBOOK £7.80

Scelbi. UNDERSTANDING MICROCOMPUTERS £7.60

Gives the fundamental concepts of virtually all micro-computers.

NEW:

Schoman, K. THE BASIC WORK-BOOK £3.70

Creative techniques for beginning programmers.

NEW:

Sirion, D. BASIC FROM THE GROUND UP £6.00

Soucek, B. MICROPROCESSORS AND MICROCOMPUTERS £18.80

Here is a description of the applications programming and interfacing techniques common to all microprocessors.

NEW:

Spracklen, D. SARGON £9.75

A computer chess program in Z-80 assembly language.

NEW:

Tracton. 57 PRACTICAL PROGRAMS & GAMES IN BASIC £6.40

Programs for everything from Space war games to Blackjack.

Waite. M. MICROCOMPUTER PRIMER £6.25

Introduces the beginner to the basic principles of the microcomputer.

Ward. MICROPROCESSOR / MICRO-PROGRAMMING HANDBOOK £6.00

Authoritative practical guide to microprocessor construction programming and applications.

NEW:

Veronis. MICROPROCESSOR £12.85

Zaks, R. INTRODUCTION TO PERSONAL AND BUSINESS COMPUTING £7.50

Zaks, R. MICROPROCESSORS FROM CHIPS TO SYSTEMS £7.50

Note that all prices include postage and packing. Please make cheques, etc, payable to Computing Today Book Service (Payment in U.K. currency only please) and send to:

Computing Today Book Service,
P.O. Box 79,
Maidenhead, Berks.

Card Sharp

T. Lusty has written a games program that proves to be quite a memory test.

Most successful computer games are simulations of games or activities which people enjoyed before the computer existed. However, many card games seemed to have escaped the programmers. This seems a great shame as computer bridge might be just as enjoyable as computer chess.

Pelmanism is a card game which, some people claim, trains the mind to think and remember. The original game is not easily computerised but CARD-SHARP is a game which is easy and enjoyable to play and for which the same educational claims might be made.

CARD-SHARP is a game for two players which requires not only a good memory but also an intelligent strategy to obtain the best possible score. The first player (the computer) has a pack of playing cards face-up in front of him, and the second player is either blindfolded or in a position where he cannot see the cards. The first player then names either a suit or a card value and the second player suggests a card of the given suit or value. If the card has not been given before the second player scores points and the first player turns the given card face-down. If the suggested card is already face down the second player loses points and has to suggest another card which fits the first player's requirements. The game continues until all the cards are face-down.

The Pack of Cards

It is necessary for the computer to have some means of representing the pack of cards. The data structure must enable it to find easily which cards have already been used and to check that it does not ask impossible questions. The computer simulates the pack of array P which has dimensions 4×13 . The array is initially set to zero to represent all the cards being face-up and then each element of the array is set to one as the required card is accepted. eg. If the value of P(3,11) is one, this would mean that you had already used the Jack of Hearts.

Two other array variables S and T are used to count the number of cards which have been given to the computer. The variable S with dimension 13 is used to count the number of cards of a particular value which the computer has received. eg. If the value of S(7) is three you have already given the computer 3 sevens. Variable T with dimension 4 is used to count the number of cards which have been given in a particular suit. eg. If the value of T(4) is 13 then you have already given the computer all the Spades.

Scoring

All good games must give the players a way of estimating how well they are doing, and the computer prints the score after every successful response. It has the decency not to gloat over how many points you have lost when your response was wrong!

The score is kept in variable K and points are added or subtracted depending upon whether or not the response is acceptable. Obviously, it gradually becomes more difficult to find a card which fits the computer's requirement and the scoring reflects this. If the computer asks for a card of a particular suit and receives an acceptable response the score is increased by one plus the number of cards already given in that suit; see line 810. If the computer receives an unacceptable response the score is debited by 20 minus the number of cards already given; see line 860. Similarly, if the computer asks for a card of a given value the score varies according to the prevailing situation; see lines 1090 and 1140.

Asking the Question

The computer's questions must obviously be unpredictable, but the random approach used here is not necessarily the best method. It must ask exactly 52 questions although some may be repeated when the response is incorrect, and there must be at least one possible answer.

The FOR . . . NEXT loop from line 570 to line 1180 is executed exactly 52 times and the NEXT statement can only be reached when an acceptable answer has been given. Within this loop the computer generates a random number X between 0 and 103 in line 600. If the number is greater than 51 a suit is required, if less, the computer asks for a card of a given value. There is, therefore, a 50-50 chance of either possibility occurring. If X is more than 51 it is divided by 4 and the remainder plus one gives the suit. (1=clubs, 2=diamonds, 3=hearts, 4=spades.) If X is less than 51 it is divided by 13 and the remainder plus one gives the value of the card required. (1=ace . . . 13=king.) Lines 640 and 920 check that there is a possible answer, and if there is not, the question is changed.

Input and Output

A possible reason why computers have remained a mystery to so many people for so long is their willingness to produce a hexadecimal dump rather than English. The quality of printout can vary greatly, from those programs which produce only the ubiquitous question mark to those which make witty comments after the input of rude words!

This program is fairly literate, if it asks for a spade it will accept 'ace' or 'an ace' as legitimate answers. If it requires a suit it accepts both the singular and the plural response. It also says 'please', but there is clearly room for improvement if you feel that way inclined.

The computer keeps its representation of the pack hidden away in memory, and the printout is designed so that it is not easy to look back for clues as to which cards have previously been played. If you want to see the cards you have already used, you can type 'status' but the computer then subtracts 10 from your score.

Running the Program

The program uses fairly standard BASIC and should run on most machines. The random number in line 600 might need some modification.

If you have a choice between working in half-duplex (ie. the printer or VDU responds directly to the keyboard) or full-duplex (ie. the computer is programmed to echo what

is typed on the keyboard back to the display) then you may try the following innovation. Set up the processor to work in half-duplex and the terminal in full-duplex. Your input will not be printed and it is then impossible to cheat, the output from the program will not be affected.

The following is a listing of the source program, together with part of a sample run.

```
00100 PRINT "THIS IS A MEMORY TEST!!"
00110 PRINT "_____"
00120 PRINT
00130 PRINT
00140 PRINT "IMAGINE YOU HAVE A PACK OF CARDS.";
00150 PRINT "I SHALL ASK YOU TO GIVE ME A CARD"
00160 PRINT "EITHER 1) OF A GIVEN SUIT OR";
00170 PRINT "2) OF A GIVEN VALUE."
00180 PRINT
00190 PRINT "IF YOU GIVE ME A NEW CARD YOU SCORE MORE POINTS,";
00200 PRINT "BUT IF YOU TRY TO"
00210 PRINT "GIVE ME A CARD YOU HAVE ALREADY USED";
00220 PRINT "I SHALL TAKE POINTS OFF."
00230 PRINT
00240 PRINT "IF YOU WANT TO SEE THE CARDS YOU HAVE";
00250 PRINT "USED TYPE 'STATUS' IN REPLY"
00260 PRINT "TO ANY QUESTION, BUT YOU LOSE 10 POINTS FROM YOUR SCORE."
00270 PRINT
00280 PRINT
00290 PRINT "O.K. LET'S START."
00300 PRINT
00310 DIM P(4,13), N$(13), S$(4), T(4), S(13), M$(13), T$(4)
00320 REM ***** TURN ALL CARDS FACE-UP *****
00330 FOR I = 1 TO 4
00340 FOR J = 1 TO 13
00350 LET P(I,J) = 0
00360 NEXT J
00370 NEXT I
00380 REM ***** READ IN THE NAMES OF THE CARDS *****
00390 FOR I = 1 TO 13
00400 READ N$(I), M$(I)
00410 LET S(I) = 0
00420 NEXT I
00430 REM ***** READ IN THE SUIT NAMES *****
00440 FOR I = 1 TO 4
00450 READ S$(I), T$(I)
00460 LET T(I) = 0
00470 NEXT I
00480 REM ***** DATA FOR CARD NAMES *****
00490 DATA "ACE", "AN ACE", "TWO", "A TWO", "THREE", "A THREE", "FOUR"
00500 DATA "A FOUR", "FIVE", "A FIVE", "SIX", "A SIX", "SEVEN", "A SEVEN"
00510 DATA "EIGHT", "AN EIGHT", "NINE", "A NINE", "TEN", "A TEN", "JACK"
00520 DATA "A JACK", "QUEEN", "A QUEEN", "KING", "A KING"
00530 REM ***** DATA FOR SUIT NAMES *****
00540 DATA "CLUB", "CLUBS", "DIAMOND", "DIAMONDS"
00550 DATA "HEART", "HEARTS", "SPADE", "SPADES"
00560 REM ***** SET UP LOOP FOR 52 CARDS WITH COUNTER Z *****
00570 FOR Z = 1 TO 52
00580 REM ***** OBTAIN RANDOM NUMBER BETWEEN 0 AND 130 *****
00590 REM ***** AND CHOOSE TO ASK FOR CARD OR SUIT *****
00600 LET X = INT(104*RND(0))
00610 IF X<52 THEN 00910
00620 REM ***** SUIT CHOSEN --- X BETWEEN 52 AND 103 *****
00630 LET X = X-4*INT(X/4)+1
00640 IF T(X)>12 THEN 00630
00650 PRINT "PLEASE TYPE A"; S$(X); TAB(55);
00660 INPUT R$
00670 IF R$ <> "STATUS" THEN 00710
00680 GOSUB 01280
```

»»


```

00690 GOTO 00650
00700 REM ***** CHECK TO SEE IF REPLY IS A VALID CARD *****
00710 FOR I = 1 TO 13
00720 IF R$ = N$(I) THEN 00790
00730 IF R$ = M$(I) THEN 00790
00740 NEXT I
00750 PRINT "DON'T BE STUPID!!";
00760 GOTO 00650
00770 REM ***** CHECK TO SEE IF THE CARD HAS *****
00780 REM ***** ALREADY BEEN GIVEN *****
00790 IF P(X,I) = 1 THEN 00860
00800 LET P(X,I) = 1
00810 LET K = K+T(X)+1
00820 LET S(I) = S(I)+1
00830 LET T(X) = T(X)+1
00840 PRINT "O.K. SCORE = "; K; TAB (21);
00850 GOTO 01180
00860 LET K = K-(20-T(X))
00870 PRINT
00880 PRINT "THINK AGAIN!!";
00890 GOTO 00650
00900 REM ***** CARD CHOSEN --- X BETWEEN 0 AND 51 *****
00910 LET X = X+1-13*(INT(X/13))
00920 IF S(X)>3 THEN 00910
00930 PRINT "PLEASE TYPE THE SUIT OF"; M$(X); TAB(55)
00940 INPUT R$
00950 IF R$ <> "STATUS" THEN 00990
00960 GOSUB 01280
00970 GOTO 00930
00980 REM ***** CHECK TO SEE IF REPLY IS A VALID SUIT *****
00990 FOR I = 1 TO 4
01000 IF R$ = S$(I) THEN 01070
01010 IF R$ = T$(I) THEN 01070
01020 NEXT I
01030 PRINT "DON'T BE STUPID!!";
01040 GOTO 00930
01050 REM ***** CHECK TO SEE IF THE CARD HAS *****
01060 REM ***** ALREADY BEEN GIVEN *****
01070 IF P(I,X) = 1 THEN 01140
01080 LET P(I,X) = 1
01090 LET K = K+S(X)+1
01100 LET S(X) = 2(X)+1
01110 LET T(I) = T(I)+1
01120 PRINT "OK. SCORE = "; K; TAB(21);
01130 GOTO 01180
01140 LET K = K-(10-S(X))
01150 PRINT
01160 PRINT "THINK AGAIN!!";
01170 GOTO 00930
01180 NEXT Z
01190 PRINT
01200 PRINT
01210 PRINT "YOU HAVE NOW GIVEN ME ALL 52 CARDS — THANK YOU."
01220 PRINT
01230 PRINT "YOUR FINAL SCORE IS"; K
01240 PRINT
01250 STOP
01260 REM $$$$$$ SUBROUTINE TO PRINT CARDS THAT *****
01270 REM ***** HAVE ALREADY BEEN GIVEN *****
01280 PRINT
01290 PRINT
01300 PRINT T$(1), T$(2), T$(3), T$(4)
01310 PRINT "-----", "-----", "-----", "-----"
01320 PRINT
01330 FOR I = 1 TO 13
01340 FOR J = 1 TO 4
01350 IF P(J,I) = 0 THEN 01370

```



```

01360 PRINT TAB(15*(J-1)+1); N$(I);
01370 NEXT J
01380 PRINT
01390 NEXT I
01400 PRINT
01410 LET K = K-10
01420 RETURN
01430 END

```

THIS IS A MEMORY TEST!!

IMAGINE YOU HAVE A PACK OF CARDS. I SHALL ASK YOU TO GIVE ME A CARD EITHER 1) OF A GIVEN SUIT OR 2) OF A GIVEN VALUE.

IF YOU GIVE ME A NEW CARD YOU SCORE MORE POINTS, BUT IF YOU TRY TO GIVE ME A CARD YOU HAVE ALREADY USED I SHALL TAKE POINTS OFF.

IF YOU WANT TO SEE THE CARDS YOU HAVE USED TYPE 'STATUS' IN REPLY TO ANY QUESTION, BUT YOU LOSE 10 POINTS FROM YOUR SCORE.

O.K. LET'S START.

PLEASE TYPE THE SUIT OF AN EIGHT

| | |
|----------------|---------------------------------|
| OK. SCORE = 1 | PLEASE TYPE THE SUIT OF A THREE |
| OK. SCORE = 2 | PLEASE TYPE A HEART |
| OK. SCORE = 4 | PLEASE TYPE THE SUIT OF A SIX |
| OK. SCORE = 5 | PLEASE TYPE A CLUB |
| OK. SCORE = 8 | PLEASE TYPE A SPADE |
| OK. SCORE = 9 | PLEASE TYPE A HEART |
| OK. SCORE = 12 | PLEASE TYPE THE SUIT OF A SEVEN |
| OK. SCORE = 13 | PLEASE TYPE A HEART |
| OK. SCORE = 18 | PLEASE TYPE A DIAMOND |
| OK. SCORE = 19 | PLEASE TYPE THE SUIT OF A SEVEN |
| OK. SCORE = 21 | PLEASE TYPE A HEART |
| OK. SCORE = 27 | PLEASE TYPE THE SUIT OF A SEVEN |
| OK. SCORE = 30 | PLEASE TYPE A HEART |
| OK. SCORE = 37 | PLEASE TYPE THE SUIT OF A FOUR |
| OK. SCORE = 38 | PLEASE TYPE THE SUIT OF A TWO |
| OK. SCORE = 40 | PLEASE TYPE THE SUIT OF A KING |
| OK. SCORE = 41 | PLEASE TYPE A SPADE |
| OK. SCORE = 44 | PLEASE TYPE A DIAMOND |
| OK. SCORE = 48 | PLEASE TYPE THE SUIT OF AN ACE |
| OK. SCORE = 50 | PLEASE TYPE THE SUIT OF A QUEEN |
| OK. SCORE = 52 | PLEASE TYPE A DIAMOND |

THINK AGAIN!!

? HEART
 ? CLUB
 ? ACE
 ? CLUB
 ? TWO
 ? JACK
 ? JACK
 ? HEART
 ? THREE
 ? TEN
 ? SPADE
 ? QUEEN
 ? CLUB
 ? NINE
 ? DIAMOND
 ? DIAMOND
 ? CLUB
 ? NINE
 ? FIVE
 ? DIAMOND
 ? SPADE
 ? FOUR
 ? STATUS

CLUBS

DIAMONDS

HEARTS

SPADES

TWO
THREE

ACE

ACE

FOUR
FIVE

THREE

SIX
SEVEN

TEN

SEVEN
EIGHT
NINE

SEVEN

NINE

JACK
QUEEN

JACK
QUEEN

KING

PLEASE TYPE A DIAMOND

| | |
|----------------|----------------------------------|
| OK. SCORE = 33 | PLEASE TYPE A DIAMOND |
| OK. SCORE = 40 | PLEASE TYPE THE SUIT OF A KING |
| OK. SCORE = 42 | PLEASE TYPE THE SUIT OF A QUEEN |
| OK. SCORE = 45 | PLEASE TYPE A CLUB |
| OK. SCORE = 51 | PLEASE TYPE A DIAMOND |
| OK. SCORE = 61 | PLEASE TYPE THE SUIT OF AN EIGHT |
| OK. SCORE = 63 | PLEASE TYPE THE SUIT OF A THREE |

? THREE
 ? SIX
 ? DIAMOND
 ? DIAMOND
 ? ACE
 ? SEVEN
 ? SPADE
 ? SPADE

| DIODES/ZENERS | | | | |
|---------------|-------|--------------|-----|--|
| QTY. | | | | |
| 1N914 | 100v | 10mA | .05 | |
| 1N4005 | 600v | 1A | .08 | |
| 1N4007 | 1000v | 1A | .15 | |
| 1N4148 | 75v | 10mA | .05 | |
| 1N4733 | 5.1v | 1 W Zener | .25 | |
| 1N753A | 6.2v | 500 mW Zener | .25 | |
| 1N758A | 10v | " | .25 | |
| 1N759A | 12v | " | .25 | |
| 1N5243 | 13v | " | .25 | |
| 1N5244B | 14v | " | .25 | |
| 1N5245B | 15v | " | .25 | |

| SOCKETS/BRIDGES | | | | |
|-----------------|-----|--------------|----|------|
| QTY. | | | | |
| 8-pin | pcb | .20 | ww | .35 |
| 14-pin | pcb | .20 | ww | .40 |
| 16-pin | pcb | .20 | ww | .40 |
| 18-pin | pcb | .25 | ww | .95 |
| 20-pin | pcb | .35 | ww | .95 |
| 22-pin | pcb | .35 | ww | .95 |
| 24-pin | pcb | .35 | ww | .95 |
| 28-pin | pcb | .45 | ww | 1.25 |
| 40-pin | pcb | .50 | ww | 1.25 |
| Molex pins | .01 | To-3 Sockets | | .25 |
| 2 Amp Bridge | | 100-prv | | .95 |
| 25 Amp Bridge | | 200-prv | | 1.50 |

| TRANSISTORS, LEDS, etc. | | | | |
|-------------------------|---------------------------|--|--|------|
| QTY. | | | | |
| 2N2222 | (2N2222 Plastic .10) | | | .15 |
| 2N2222A | | | | .19 |
| 2N2907A | PNP | | | .19 |
| 2N3906 | PNP (Plastic Unmarked) | | | .10 |
| 2N3904 | NPN (Plastic Unmarked) | | | .10 |
| 2N3054 | NPN | | | .45 |
| 2N3055 | NPN 15A 60v | | | .60 |
| T1P125 | PNP Darlington | | | 1.95 |
| LED Green, | Red, Clear, Yellow | | | .15 |
| D.L.747 | 7 seg 5/8" High com-anode | | | 1.95 |
| MAN72 | 7 seg com-anode (Red) | | | 1.25 |
| MAN3610 | 7 seg com-anode (Orange) | | | 1.25 |
| MAN82A | 7 seg com-anode (Yellow) | | | 1.25 |
| MAN74 | 7 seg com-cathode (Red) | | | 1.50 |
| FND359 | 7 seg com-cathode (Red) | | | 1.25 |

| 9000 SERIES | | | | |
|-------------|------|------|--|-----|
| QTY. | | QTY. | | |
| 9301 | .85 | 9322 | | .65 |
| 9309 | .35 | 9601 | | .20 |
| 9316 | 1.10 | 9602 | | .45 |

| MICRO'S, RAMS, CPU'S, E-PROMS | | | | |
|-------------------------------|-------|-----------|--|-------|
| QTY. | | QTY. | | |
| 8T13 | 1.50 | 2107B-4 | | 4.95 |
| 8T23 | 1.50 | 2114 | | 9.50 |
| 8T24 | 2.00 | 2513 | | 6.25 |
| 8T97 | 1.00 | 2708 | | 10.50 |
| 74S188 | 3.00 | 2716 D.S. | | 34.00 |
| 1488 | 1.25 | 2716 (5v) | | 59.00 |
| 1489 | 1.25 | 2758 (5v) | | 23.95 |
| 1702A | 4.50 | 3242 | | 10.50 |
| AM 9050 | 4.00 | 4116 | | 11.50 |
| | | 6800 | | 13.95 |
| | | 6850 | | 7.95 |
| MM 5314 | 3.00 | 8080 | | 7.50 |
| MM 5316 | 3.50 | 8212 | | 2.75 |
| MM 5387 | 3.50 | 8214 | | 4.95 |
| MM 5369 | 2.95 | 8216 | | 3.50 |
| TR 1602B | 3.95 | 8224 | | 3.25 |
| UPD 414 | 4.95 | 8228 | | 6.00 |
| Z 80 A | 22.50 | 8251 | | 7.50 |
| Z 80 | 17.50 | 8253 | | 18.50 |
| Z 80 PIO | 10.50 | 8255 | | 8.50 |
| 2102 | 1.45 | TMS 4044 | | 9.95 |
| 2102L | 1.75 | | | |

| C MOS | | | | |
|------------|--|-------|--|--|
| QTY. | | | | |
| 4000 | | .15 | | |
| 4001 | | .15 | | |
| 4002 | | .20 | | |
| 4004 | | 3.95 | | |
| 4006 | | .95 | | |
| 4007 | | .20 | | |
| 4008 | | .75 | | |
| 4009 | | .35 | | |
| 4010 | | .35 | | |
| 4011 | | .20 | | |
| 4012 | | .20 | | |
| 4013 | | .40 | | |
| 4014 | | .75 | | |
| 4015 | | .75 | | |
| 4016 | | .35 | | |
| 4017 | | .75 | | |
| 4018 | | .75 | | |
| 4019 | | .35 | | |
| 4020 | | .85 | | |
| 4021 | | .75 | | |
| 4022 | | .75 | | |
| 4023 | | .20 | | |
| 4024 | | .75 | | |
| 4025 | | .20 | | |
| 4026 | | 1.95 | | |
| 4027 | | .35 | | |
| 4028 | | .75 | | |
| 4029 | | 1.15 | | |
| 4030 | | .30 | | |
| 4033 | | 1.50 | | |
| 4034 | | 2.45 | | |
| 4035 | | .75 | | |
| 4037 | | 1.80 | | |
| 4040 | | .75 | | |
| 4041 | | .69 | | |
| 4042 | | .65 | | |
| 4043 | | .50 | | |
| 4044 | | .65 | | |
| 4046 | | 1.25 | | |
| 4048 | | .95 | | |
| 4049 | | .45 | | |
| 4050 | | .45 | | |
| 4052 | | .75 | | |
| 4053 | | .75 | | |
| 4066 | | .55 | | |
| 4069/74C04 | | .35 | | |
| 4071 | | .25 | | |
| 4081 | | .30 | | |
| 4082 | | .30 | | |
| 4507 | | .95 | | |
| 4511 | | .95 | | |
| 4512 | | 1.10 | | |
| 4515 | | 2.95 | | |
| 4519 | | .85 | | |
| 4522 | | 1.10 | | |
| 4526 | | .95 | | |
| 4528 | | 1.10 | | |
| 4529 | | .95 | | |
| MC 14409 | | 14.50 | | |
| MC 14419 | | 4.85 | | |
| 74C151 | | 1.50 | | |

| LINEARS, REGULATORS, etc. | | | | |
|---------------------------|------|--------------|------|----------------------|
| QTY. | | QTY. | | QTY. |
| MCT2 | .95 | LM323K | 5.95 | LM380 (8-14 Pin)1.19 |
| 8038 | 3.95 | LM324 | 1.25 | LM709 (8-14 Pin) .35 |
| LM201 | .75 | LM339 | .75 | LM711 .45 |
| LM301 | .45 | 7805 (340T5) | .95 | LM723 .40 |
| LM308 | .65 | LM340T12 | .95 | LM725 2.50 |
| LM309H | .65 | LM340T15 | .95 | LM739 1.50 |
| LM309K (340K-5) | 1.50 | LM340T18 | .95 | LM741 (8-14) .35 |
| LM310 | .85 | LM340T24 | .95 | LM747 1.10 |
| LM311D | .75 | LM340K12 | 1.25 | LM1307 1.25 |
| LM318 | 1.75 | LM340K15 | 1.25 | LM1458 .65 |
| LM320H6 | .79 | LM340K18 | 1.25 | LM3900 .50 |
| LM320H15 | .79 | LM340K24 | 1.25 | LM75451 .65 |
| LM320H24 | .79 | LM373 | 2.95 | NE555 .45 |
| 7905 (LM320K5) | 1.65 | LM377 | 3.95 | NE556 .85 |
| LM320K12 | 1.65 | 78L05 | .75 | NE565 .95 |
| LM320K24 | 1.65 | 78L12 | .75 | NE566 1.25 |
| LM320T5 | 1.65 | 78L15 | .75 | NE567 .95 |
| LM320T12 | 1.65 | 78M05 | .75 | |
| LM320T15 | 1.65 | | | |

| - T T L - | | | | | |
|-----------|------|-------|------|---------|------|
| QTY. | | QTY. | | QTY. | |
| 7400 | .10 | 7482 | .75 | 74221 | 1.00 |
| 7401 | .15 | 7483 | .75 | 74367 | .95 |
| 7402 | .15 | 7485 | .55 | 75108A | .35 |
| 7403 | .15 | 7486 | .25 | 75491 | .50 |
| 7404 | .10 | 7489 | 1.05 | 75492 | .50 |
| 7405 | .25 | 7490 | .45 | 74H00 | .15 |
| 7406 | .25 | 7491 | .70 | 74H01 | .20 |
| 7407 | .55 | 7492 | .45 | 74H04 | .20 |
| 7408 | .15 | 7493 | .35 | 74H05 | .20 |
| 7409 | .15 | 7494 | .75 | 74H08 | .35 |
| 7410 | .15 | 7495 | .60 | 74H10 | .35 |
| 7411 | .25 | 7496 | .80 | 74H11 | .25 |
| 7412 | .25 | 74100 | 1.15 | 74H15 | .45 |
| 7413 | .25 | 74107 | .25 | 74H20 | .25 |
| 7414 | .75 | 74121 | .35 | 74H21 | .25 |
| 7416 | .25 | 74122 | .55 | 74H22 | .40 |
| 7417 | .40 | 74123 | .35 | 74H30 | .20 |
| 7420 | .15 | 74125 | .45 | 74H40 | .25 |
| 7426 | .25 | 74126 | .35 | 74H50 | .25 |
| 7427 | .25 | 74132 | .75 | 74H51 | .25 |
| 7430 | .15 | 74141 | .90 | 74H52 | .15 |
| 7432 | .20 | 74150 | .85 | 74H53 | .25 |
| 7437 | .20 | 74151 | .65 | 74H55 | .20 |
| 7438 | .20 | 74153 | .75 | 74H72 | .35 |
| 7440 | .20 | 74154 | .95 | 74H74 | .35 |
| 7441 | 1.15 | 74156 | .70 | 74H101 | .75 |
| 7442 | .45 | 74157 | .65 | 74H103 | .55 |
| 7443 | .45 | 74161 | .55 | 74H106 | .95 |
| 7444 | .45 | 74163 | .85 | 74L00 | .25 |
| 7445 | .65 | 74164 | .60 | 74L02 | .20 |
| 7446 | .70 | 74165 | 1.10 | 74L03 | .25 |
| 7447 | .70 | 74166 | 1.25 | 74L04 | .30 |
| 7448 | .50 | 74175 | .80 | 74L10 | .20 |
| 7450 | .25 | 74176 | .85 | 74L20 | .35 |
| 7451 | .25 | 74180 | .55 | 74L30 | .45 |
| 7453 | .20 | 74181 | 2.25 | 74L47 | 1.95 |
| 7454 | .25 | 74182 | .75 | 74L51 | .45 |
| 7460 | .40 | 74190 | 1.25 | 74L55 | .65 |
| 7470 | .45 | 74191 | 1.25 | 74L72 | .45 |
| 7472 | .40 | 74192 | .75 | 74L73 | .40 |
| 7473 | .25 | 74193 | .85 | 74L74 | .45 |
| 7474 | .30 | 74194 | .95 | 74L75 | .85 |
| 7475 | .35 | 74195 | .95 | 74L93 | .55 |
| 7476 | .40 | 74196 | .95 | 74L123 | .85 |
| 7480 | .55 | 74197 | .95 | 74LS00 | .30 |
| 7481 | .75 | 74198 | 1.45 | 74LS01 | .30 |
| | | | | 74LS02 | .30 |
| | | | | 74LS04 | .30 |
| | | | | 74LS05 | .35 |
| | | | | 74LS08 | .35 |
| | | | | 74LS09 | .35 |
| | | | | 74LS10 | .35 |
| | | | | 74LS11 | .35 |
| | | | | 74LS20 | .30 |
| | | | | 74LS21 | .35 |
| | | | | 74LS22 | .35 |
| | | | | 74LS32 | .35 |
| | | | | 74LS37 | .35 |
| | | | | 74LS38 | .45 |
| | | | | 74LS40 | .40 |
| | | | | 74LS42 | .75 |
| | | | | 74LS51 | .45 |
| | | | | 74LS74 | .45 |
| | | | | 74LS76 | .50 |
| | | | | 74LS86 | .45 |
| | | | | 74LS90 | .65 |
| | | | | 74LS93 | .65 |
| | | | | 74LS107 | .50 |
| | | | | 74LS123 | 1.20 |
| | | | | 74LS151 | .85 |
| | | | | 74LS153 | .85 |
| | | | | 74LS157 | .85 |
| | | | | 74LS160 | .95 |
| | | | | 74LS164 | 1.20 |
| | | | | 74LS193 | 1.05 |
| | | | | 74LS195 | .95 |
| | | | | 74LS244 | 1.70 |
| | | | | 74LS367 | .95 |
| | | | | 74LS368 | .95 |
| | | | | 74S00 | .35 |
| | | | | 74S02 | .35 |
| | | | | 74S03 | .25 |
| | | | | 74S04 | .25 |
| | | | | 74S05 | .35 |
| | | | | 74S08 | .35 |
| | | | | 74S10 | .35 |
| | | | | 74S11 | .35 |
| | | | | 74S20 | .25 |
| | | | | 74S40 | .25 |
| | | | | 74S50 | .25 |
| | | | | 74S51 | .25 |
| | | | | 74S64 | .15 |

CABLE ADDRESS: ICUSD

TELEX #

HOURS: 9 A.M. - 6 P.M. MON. thru SUN.

INTEGRATED CIRCUITS UNLIMITED

7889 Clairemont Mesa Blvd. • San Diego, California 92111 U.S.A.

NO MINIMUM

COMMERCIAL AND MANUFACTURING ACCOUNTS INVITED

ALL PRICES IN U.S. DOLLARS. PLEASE ADD POSTAGE TO COVER METHOD OF SHIPPING.

ORDERS OVER \$100 (U.S.) WILL BE SHIPPED AIR NO CHARGE.

PAYMENT SUBMITTED WITH ORDER SHOULD BE IN U.S. DOLLARS.

ALL IC'S PRIME/GUARANTEED ALL ORDERS SHIPPED SAME DAY RECEIVED.

CREDIT CARDS ACCEPTED:

Phone (714) 278-4394 BarclayCard / Access / American Express / BankAmericard / Visa / MasterCharge

SPECIAL DISCOUNTS

| Total Order | Deduct |
|--------------|--------|
| \$35-\$99 | 10% |
| \$100-\$300 | 15% |
| \$301-\$1000 | 20% |

| | |
|---------------|------|
| 74S74 | .35 |
| 74S112 | .60 |
| 74S114 | .65 |
| 74S133 | .40 |
| 74S140 | .55 |
| 74S151 | .30 |
| 74S153 | .35 |
| 74S157 | .75 |
| 74S158 | .30 |
| 74S194 | 1.05 |
| 74S257 (8123) | 1.05 |
| 8131 | 2.75 |

Asian Resource

We look at the first examples of Home Computers produced in the Far East.

CAST YOUR MIND back about how consumer electronic products have shifted their geographic origins from the US or Europe to the Far East. The transistor radio, cassette recorder, calculator, TV games and so on were developed originally in the countries each side of the North Atlantic but today we *expect* these products to come from Japan, Hong Kong, Taiwan or Korea. We mention Japan here because this is regarded as a major source but in the last few years the land of the Rising Sun has found it harder and harder to compete with their still-low wage neighbours.

The electronics manufacturing companies in the Far East are not known for their original design skills but once a market appears, they jump in with both feet and prices tumble. Many of the larger companies are already using MPU's in advanced TV games; they also have expertise in keyboards and printers so it is a natural step for them to start the production of home computers. There is a lot of evidence that within a year we'll be able to buy in Britain home computers carrying the 'Made in Hong Kong' label.

A report in the January 1979 issue of *Asian Sources Electronics* makes it clear that electronics companies in Hong Kong and Taiwan are showing a keen interest in entering this rapidly growing and profitable market.

Few companies are actually producing at this moment. The American company APF are producing the *PeCos-I* in the Far East, the TV monitor being made in Hong Kong with the rest of the unit being made in Japan but high labour costs may lead to production being moved elsewhere in the area.

A Hong Kong company, *EACA Electronic Products Ltd*, are producing the *EG-2001 Video Genie* for an exclusive customer in the US. The system is S-100 bus compatible and comes with 4K ROM.


At least half a dozen other companies admit to some development work but many will also own up to the fact that they are weak on the necessary software. Far East companies have always fallen badly behind on instructions, whilst this is excusable with a transistor radio, the




The PeCos One which is made in the Far East for a US customer. It includes 24K ROM and 16K RAM.

instructions are absolutely vital with any small computer system.

So far the very high technology necessary has proved a stumbling block but all the signs are that a number of home computers will soon be available. The implications are enormous. It was once thought that pocket calculators would always be a high-priced, small-production-run products but once manufacture started in the Far East, costs fell to fraction of even the most optimistic (pessimistic?) forecast. This in turn drove the original makers either into bankruptcy or into more and more sophisticated designs to keep ahead. This could happen in the home/small system computer field. **CT**



The Samson-1 is designed by the makers, Termbray Electronics Ltd of Hong Kong as a Microcomputer. This uses a 6502 with 4K ROM resident monitor and 1K of RAM; output is to a 6-digit HEX display.



The Hong Kong based EACA International Ltd have introduced the EG-2001 Video Genie for an exclusive US customer. Apart from being S-100 bus compatible and having 4K ROM, few details are available.

PETALECT

ELECTRONIC SERVICING LTD.

WANTED

Good Homes for Intelligent Pets

THE

PET 2001 Computer

£643.52 plus VAT



This unbelievably versatile, compact, portable and self-contained unit has many varied applications and offers tremendous benefits in the worlds of

● BUSINESS and COMMERCE:

Can be used efficiently for Trend Analysis, Stock Control, Payroll, Invoicing, Inventory Control, etc.

● SCIENCE and INDUSTRY:

The 'PET' has a comprehensive set of scientific functions useful to scientists, engineers and industry.

● EDUCATION:

An ideal tool for teaching and it can be used to keep records, exam results, attendance figures, etc.

● ENTERTAINMENT:

Games including Backgammon, Noughts and Crosses, Pontoon, Black Jack and Moon Landing. Possesses all usual alphanumerics PLUS 64 graphic characters for plots, artwork, etc., a printer, 2nd cassette deck and software available AND IN THE NEAR FUTURE 'Floppy Disc' data and programme storage system.

We have six years' experience in servicing electronic calculators, mini-computers in S.E. England. 24-hour service contract available at £69.50 per annum. Credit and leasing terms available.

For full details and demonstration contact Peter Watts . . . Now!

PETALECT

ELECTRONIC SERVICING LTD

(Authorised Commodore Pet Dealer) Specialists in Electronic Servicing, Programming, Electronic Design and Prototype Manufacture

33 PORTUGAL ROAD, WOKING, SURREY GU21 5JE.

Tel: Woking (04862) 69032/68497

MICROSPEECH

Does your computer speak to you?


'WHEL IHT KAN DOO WIHTH MEE!'

Features

- Single PCB plugs directly into an SWPTc 6800 bus.
- 9 parameter vocal tract model.
- Realtime software converts any stored phonetic code to speech.
- Computer Games.
- External input for special musical effects.
- Adds speech output to existing BASIC programs.

Make your computer talk

Just by entering phonetic text (as in the sentence at the top of the page). Microspeech with the MSP2 software can make your computer speak. MSP2 uses only 4K of memory. Every extra 1K of buffer space can store 90 seconds of speech.



Microspeech package


- Speech synthesizer board (assembled & tested).
- MSP2 Software on floppy disc or cassette.
- Hardware & Software manual.
- Speaking BASIC software option.

TIM ORR DESIGN CONSULTANT

55 Drive Mansions, Fulham Road, London, SW6

LOW COST R.F. MODULATOR Only £ 2.—

includes p.&p.!



Converts ordinary T.V. into Video-Monitor. Use it for computing or video-games. This board has a special Video-IC and is easy to build (ten minutes). No special adjustments, works always. Tuning by turning potentiometer. Low Power 5 volt. Kit includes all parts, epoxy p.c. board and assembly instructions written in English.

How to order: Send your order and remittance to the address below. Or, send us your undersigned Barclays or Eurocheque for a value of £2.


Address to: Musicprint Computer Products B.V., ARKELSE ONERWEG 31, 4200 AK GORINCHEM, THE NETHERLANDS.

dealer inquiries invited

Your video R.F. Modulator will be shipped the same day we receive your order

LOW COST CASSETTE INTERFACE includes p.&p.!

Only £ 8.75



Convert your cassette-recorder into a digital-recorder. Easy to build, no adjustments! Uses Kansas City Standard. High speed, full 1200 Baud. Full Duplex, which means that you can (if necessary) use the interface with 2 cassette-recorders at one time. Audio in- and outputs connects directly to cassette-recorder. Data in- en outputs are T.T.L. compatible. Low Power, only 5 volt needed. Kit includes all parts, heavy epoxy p.c. board with edge connector and clearly written manual in English. Board also available assembled and tested for £11.75 incl. p.&p.

How to order: Send us your Barclays, Eurocheque or other remittance in an envelope, put your name in capitals on the back. Kit £8.75 includes p.&p. Assembled and tested (guaranteed for 90 days) £11.75 incl. p.&p. Send your order to: Musicprint Computer Products b.v., ARKELSE ONERWEG 31, 4200 AK GORINCHEM, THE NETHERLANDS. Phone 010-31 18 30-24693. Your cassette interface will be shipped the same day we receive your order.

dealer inquiries invited

Microbiography:

6800 Series

In the first installment of this series we have covered the 8000 series mpus and their assorted support chips. This month we move on to the "other" processor which is very popular in the hobbyist field, the Motorola 6800, and its close relatives in MOS Technology's 6500 series.


6800 hardware

The 6800 hardware is very straightforward, at least in block diagram form, figure 1. There are a number of registers shown attached to the internal bus, each with a specific function in mind, in contrast with the 8080, which includes several general purpose registers. Some of 6800 registers can however be used as general storage if not otherwise in use. To summarise: the two byte (16 bit) program counter of course keeps track of the current or next location in the program, and may be incremented, or

otherwise altered in case of branches or subroutines. The stack pointer (16 bits) is used to record the next available space in the "Stack", an area in memory used for saving processor contents while performing subroutines, etc. The contents of the index register (16 bits) may be used to "offset" the address of the operand in index mode instructions (see below).

Two accumulators are included, these are the registers upon which the arithmetic and logical functions operate. The instruction register is used to hold the instruction while the instruction decoder is deciding what to do about it. Finally, the arithmetic logic unit (ALU) is the device which performs the arithmetic and logic functions. Associated with the ALU is the condition code register, whose individual bits indicate such conditions as zero, negative, carry, half-carry and interrupt. These conditions may be tested for conditional branches. »

Fig 1. Block diagram of 6800 chip architecture and pinouts.



Interface to the rest of the microprocessor system is quite simple also. Sixteen bits of buffered address (1 TTL load, 139pF) and 8 bits of bidirectional data bus (same capability) are all present, plus an assortment of control inputs and outputs. A non-overlapping two phase clock with fairly strict requirements is used, for which purpose the MPQ6842 clock buffer is available. The other lines are as follows:

Three-State Control and Data Bus Enable: Inputs which control whether the address and data bus drivers are enabled. These allow possible external control of the buses by turning off the processor outputs (example — Direct Memory Access). They are rarely used for this purpose since almost all systems large enough to warrant this employ external buffers on the data and address buses, which are themselves controllable.

Reset: Initialises processor registers.

Interrupt Inputs: See below.

Halt: Causes processor to stop after current instruction completed, and all bus drivers turn off. May be used with some logic to achieve single instruction operation.

Bus Available: Indicates that the address bus is indeed available.

Valid Memory Address: Due to the internal workings of the mpu, miscellaneous signals may appear on the address outputs. To avoid inadvertently activating some unsuspecting device, VMA is used to tell every chip on the bus when to pay attention to the address, and when to ignore it.

Read/Write: Tells all devices whether to input or output to microprocessor. Power supply requirements are just 5V, and the original 1MHz model has been joined by 1.5 and 2MHz chips, with instructions taking 2 to 12 cycles.

Software

The instruction set for 6800 is shown in figure 2. For instructions involving an accumulator, either may be used. Seven addressing modes are available in various combinations.

Accumulator: One byte instructions operating on the accumulator.

Fig 2. The instruction set of the 6800 mpu.

| | | | | | |
|-----|---------------------------------|-----|--------------------------|-----|--|
| ABA | Add Accumulators | CLR | Clear | PUL | Pull Data |
| ADC | Add with Carry | CLV | Clear Overflow | ROL | Rotate Left |
| ADD | Add | CMP | Compare | ROR | Rotate Right |
| AND | Logical And | COM | Complement | RTI | Return from Interrupt |
| ASL | Arithmetic Shift Left | CPX | Compare Index Register | RTS | Return from Subroutine |
| ASR | Arithmetic Shift Right | DAA | Decimal Adjust | SBA | Subtract Accumulators |
| BCC | Branch if Carry Clear | DEC | Decrement | SBC | Subtract with Carry |
| BCS | Branch if Carry Set | DES | Decrement Stack Pointer | SEC | Set Carry |
| BEQ | Branch if Equal to Zero | DEX | Decrement Index Register | SEI | Set Interrupt Mask |
| BGE | Branch if Greater or Equal Zero | EOR | Exclusive OR | SEV | Set Overflow |
| BGT | Branch if Greater than Zero | INC | Increment | STA | Store Accumulator |
| BHI | Branch if Higher | INS | Increment Stack Pointer | STS | Store Stack Register |
| BIT | Bit Test | INX | Increment Index Register | STX | Store Index Register |
| BLE | Branch if Less or Equal | JMP | Jump | SUB | Subtract |
| BLS | Branch if Lower or Same | JSR | Jump to Subroutine | SWI | Software Interrupt |
| BLT | Branch if Less than Zero | LDA | Load Accumulator | TAB | Transfer Accumulators |
| BMI | Branch if Minus | LDS | Load Stack Pointer | TAP | Transfer Accumulators to Condition Code Reg. |
| BNE | Branch if Not Equal to Zero | LDS | Load Stack Pointer | TBA | Transfer Accumulators |
| BPL | Branch if Plus | LDX | Load Index Register | TPA | Transfer Condition Code Reg. to Accumulator. |
| BRA | Branch Always | LSR | Logical Shift Right | TST | Test |
| BSR | Branch to Subroutine | NEG | Negate | TSX | Transfer Stack Pointer to Index Register |
| BVC | Branch if Overflow Clear | NOP | No Operation | TXS | Transfer Index Register to Stack Pointer |
| BVS | Branch if Overflow Set | ORA | Inclusive OR Accumulator | WAI | Wait for Interrupt |
| CBA | Compare Accumulators | PSH | Push Data | | |
| CLC | Clear Carry | | | | |
| CLI | Clear Interrupt Mask | | | | |

Immediate: The second (or second and third for LDS and LDX) byte, following the op code, contains the operand.

Direct: The second byte of the instruction contains the address in zero page (lowest 256 bytes) of memory of the operand.

Extended: Second and third bytes contain the operand's address.

Indexed: The second byte is added to the index register, the result (held in a temporary register so as not to affect the index register) is used as the address of the operand. This mode is particularly useful for accessing tables, etc.

Implied: The instruction (one byte) applies to a particular internal register.

Relative Addressing: The second byte is used to branch forward or backwards from the current location up to +129 or -125.

The instruction set itself contains quite a comprehensive list of arithmetic and logic functions, branches with tests for all conditions, branch and jump to subroutine, plus manipulation of condition code bits. Versatility of the index register(s) and stack pointer is increased by several instructions.

Interrupts

In the 6800, four interrupt-like modes are possible. The first is RST which initialises the machine, and which causes a read from (hex) addresses FFFE, FFFF.

At these locations the processor fetches the address of the first routine to execute, presumably an initialisation routine.

During normal operation, a signal on the Non-Maskable Interrupt line will cause execution to stop after the current instruction, the next address is saved on the stack, and the address of the interrupt service routine is fetched from FFFC,D.

Operation of the Interrupt Request line is similar, except that by setting the interrupt mask bit in the condition code register, the mpu will ignore an IRQ signal. The IRQ address is FFF8,9. Finally there is an instruction, software interrupt (SWI) which causes an interrupt type action to take place, using addresses FFFA,B.

The 6800 interrupt mechanism means that interrupt servicing will generally be by "polling". That is to say, if several chips are all attached to an interrupt line, then the service routine "asks" each one in turn (by reading the device's status register) who interrupted. The order of asking determines the priority of each device. This is cheap but slow. Vectored interrupt capability is possible with complex, non standard hardware.

6500

The 6500 series of processors are in many respects very similar to the 6800, but incorporate what MOS Technology feel are numerous improvements. The series is not as widely known as the 6800, its main exposure being through the KIM and PET.

The biggest and "best" of the line is the 6502, and to encourage the use of this mpu the 6501 was introduced.

The 6501 is hardware compatible with the 6800, ie a plug in replacement, but incorporates the instruction set of the 6502 which is significantly different. The user is thus provided with a means to sample the 6500 series instructions (not compatible) without needing a complete system.

6501

As stated the 6501 is externally very similar to the 6800, the main difference being that VMA is not needed, since all addresses from the 6501 are valid.

The internal block diagram for the 6500 series processors is shown in figure 3. In contrast with the 6800, the 6501 contains only one 8 bit accumulator, two 8 bit index registers, a 16 bit program counter and 8 bit stack pointer. The status (condition code) register is again similar to the 6800 with the addition of one bit to set "decimal mode" of operation (BCD arithmetic) and one bit associated with software interrupts.




Fig 3. Block diagram of 6500 series chips. The pinout is for a 6502 mpu.

The switch from two to one accumulator might hamper some, but the change from one 16 bit index register to two eight bit ones is often advantageous. Index registers are generally used for table operations, where the base of the table is given with the op code, and the index register is added and incremented for each table access. Few tables are longer than 256 entries, but two tables might easily be used.

6500 software

A complete listing of instructions is given in figure 4 most of which are self explanatory. What is most interesting is the multitude of addressing modes. There are two major categories of addressing modes. The first of these, "direct" covers all the same address modes as those in the 6800. One small difference to the programmer does occur however. Where two bytes of address information follow the op code, in the 6800 system one writes them high order then low order. For the 6500 processors they are placed low order byte first, which at first looks odd but there is a good reason. Example: in a normal instruction execution, the address of the op-code is placed on the bus, and the op-code input to the instruction register. In the second cycle the op-code is being interpreted, while the next byte is loaded into an internal low order address register. Now if the interpretation of the op-code shows that it was a one byte instruction, the second byte was not necessary and is ignored. If a zero page instruction then the byte is already in the low address register, and if an absolute (two byte

address needed) instruction another byte will be needed but at least the first one (low order) is already in the correct register. In the 6800 the op-code must be interpreted before the second byte can be put in the high or low register. This points out an important feature of the 6500 series, that every cycle is used for mpu input whether needed or not, (which is why no VMA is needed) but which often saves time.

The second category of addressing modes is the indirect category wherein the 6500s really shine.

This mode is a little complicated, so keep in mind that the objective is to get the operand. In plain indirect addressing the location following the op-code contains the address (in zero page) where two consecutive locations contain the address of the operand. Figure 5 shows the relationship. It is generally used where the final address (CB) is to be calculated at a later date, but the place to find that calculated address (A) can be established. To further beautify (complicate) matters, we can add indexing to either the second address (indirect indexing) or first address (indexed indirect). In the first case we may be accessing a table at a remote location, in the second perhaps accessing a table of remote locations, either way the final address is in some way to be left open for the program to calculate and insert. These modes are also most useful in subroutines.

6502

The 6502 includes a number of features over the 6501 and of course the same software features.

Fig. 4. The instruction set of the 6500 series mpus.

| | | | |
|------------|--|------------|--|
| ADC | Add Memory to Accumulator with Carry | JSR | Jump to New Location Saving Return Address |
| AND | "AND" Memory with Accumulator | LDA | Load Accumulator with Memory |
| ASL | Shift Left One Bit (Memory or Accumulator) | LDX | Load Index X with Memory |
| BCC | Branch on Carry Clear | LDY | Load Index Y with Memory |
| BCS | Branch on Carry Set | LSR | Shift Right One Bit (Memory or Accumulator) |
| BEQ | Branch on Result Zero | NOP | No Operation |
| BIT | Test Bits in Memory with Accumulator | ORA | "OR" Memory with Accumulator |
| BMI | Branch on Result Minus | PHA | Push Accumulator on Stack |
| BNE | Branch on Result not Zero | PHP | Push Processor Status on Stack |
| BPL | Branch on Result Plus | PLA | Pull Accumulator from Stack |
| BRK | Force Break | PLP | Pull Processor Status from Stack |
| BVC | Branch on Overflow Clear | ROL | Rotate One Bit Left (Memory or Accumulator) |
| BVS | Branch on Overflow Set | ROR | Rotate One Bit Right (Memory or Accumulator) |
| CLC | Clear Carry Flag | RTI | Return from Interrupt |
| CLD | Clear Decimal Mode | RTS | Return from Subroutine |
| CLI | Clear Interrupt Disable Bit | SBC | Subtract Memory from Accumulator with Borrow |
| CLV | Clear Overflow Flag | SEC | Set Carry Flag |
| CMP | Compare Memory and Accumulator | SED | Set Decimal Mode |
| CPX | Compare Memory and Index X | SEI | Set Interrupt Disable Status |
| CPY | Compare Memory and Index Y | STA | Store Accumulator in Memory |
| DEC | Decrement Memory by One | STX | Store Index X in Memory |
| DEX | Decrement Index X by One | STY | Store Index Y in Memory |
| DEY | Decrement Index Y by One | TAX | Transfer Accumulator to Index X |
| EOR | "Exclusive-Or" Memory with Accumulator | TAY | Transfer Accumulator to Index Y |
| INC | Increment Memory by One | TSX | Transfer Stack Pointer to Index X |
| INX | Increment Index X by One | TXA | Transfer Index X to Accumulator |
| INY | Increment Index Y by One | TXS | Transfer Index X to Stack Pointer |
| JMP | Jump to New Location | TYA | Transfer Index Y to Accumulator |

Hardware

The block diagram figure 3 again applies, and the pinouts are shown in figure 3. The improvements are significant. A simple crystal or RC TTL single phase clock input is all that is required, the chip provides phase one and two outputs. A very important feature to hobbyists and prototype builders is the function of the RDY line. Similar to the HALT of the 6800, the difference is that the 6502 will stop with the addresses available on the bus, rather than in high impedance state. The advantage is that in debugging and single stepping it is very simple to stop and see where you are, and what data is at the location in memory. To do the same thing with a 6800 needs extra logic and latches.

Others in the 6500 series:

In addition several other processors are available, all "subsets" of the 6502. The 6503, 4, 5, 6 are 28 pin versions, with reduced addressing, control and interrupt combinations, on chip clock, and reduced cost. The 6512 is a 40 pin model with two phase clock but otherwise like the 6502. The 6513, 14, 15 are similar to the 6512 and again are 28 pin versions. 1MHz and 2MHz versions are available of each one.

Support chips

Since the buses for the two families are so similar, support

ICs for one will generally work for the other.

The popular system staples are:

6810: 128 × 8 static RAM

6820: Peripheral Interface Adapter: provides two 8 bit parallel I/O ports, each bit programmable as in or out plus "handshaking". The two ports provide different input and drive capabilities, giving TTL and CMOS compatibility.

6830: 1024 × 8 ROM

6850: Asynchronous Communications Interface Adapter: Provides buffering and control for reception and transmission of serial data, eight and nine bit, with various code options.

6852: Synchronous Serial Data Adapter.

6860: Digital Modem for use with the ACIA, this unit provides the modulator, demodulator, and control signals for telephone communication.

6520: Peripheral Interface Device: similar to 6820.

6530: Peripheral Interface/Memory Device: includes 1K ROM, 64 bytes RAM plus two 8 bit bidirectional ports, and programmable interval timer with interrupt.

6522: Similar to 6520, plus timers, serial-parallel, parallel serial shift register, and input data latching, plus expanded handshaking.

6532: Includes 128 byte RAM, two 8 bit bidirectional ports and timer.

Plus an assortment of special purpose interface adapters and memory items.

CT

| Program | | | |
|----------|----------|----------|----------|
| Location | Contents | Location | Contents |
| X | Op-code | 00,A | B |
| X+1 | A | 00,A+1 | C |

Fig 5. Indirect addressing on the 6500 series mpus.




Fig 6. The Peripheral Interface Adapter provides two 8-bit bidirectional points.

**ORDER BY POST
FROM THE WIDEST
RANGE OF
MICRO-COMPUTERS
IN BRITAIN...
OR VISIT OUR
STORES**

the **BYTE** SHOP Ltd

**IT'S
APPLE
EX-STOCK** **APPLE
2**

SOUTHWEST TECHNICAL PRODUCTS — FOR 6800 USERS



| | |
|--|--------|
| MP-68CPU, 4K RAM | £355 |
| 8K additional RAM | £140 |
| 560KB twin disk system | £1,400 |
| 160KB twin mini floppy system | £860 |
| CT-64 V.D.U. upper/lower case, monitor | £455 |
| PR-40 40-column printer | £250 |
| Cassette interface | £100 |
| GT-61 Graphics Terminal | £105 |

A favourite with schools and colleges —
low priced system that can grow.

Attractive low-priced software!

FOR THE PROFESSIONAL — CROMEMCO



| | |
|--|------------|
| Z-2 system: fully assembled | £575 |
| Z-2 system: Kit | £395 |
| Disk system from | £1,425 |
| CS-3 System 3, 32K, dual disk, expandable | £4,175 |
| 4 MHZ Single card computer | £345 |
| Bytesaver board with PROM Programmer | £135 |
| 16K PROM card | £135 |
| Analogue Interface | £135 |
| Disk — BASIC, FORTRAN, ASSEMBLER, COBOL, etc. etc. | each — £85 |

A rugged well-engineered system designed for
hard use. Expandable to 512K, 21 Boards.
Excellent software support CP/M AVAILABLE

PROCESSOR TECHNOLOGY SOL 20/16




| | |
|--|--------|
| Computer system, 16K, V.D.U. etc. | £1,785 |
| Additional memory, 16K dynamic | £275 |
| Mini-floppy disk (first) | £635 |
| High quality word processing printer from | £1,800 |

A quality 8080 based system.
Over 7,000 sold! Excellent word processing
software available.

Also... Printers for all the above systems...
extra software... diskettes... cassettes...
Chess Challenger 10... games... etc...

Branches in Birmingham, Manchester & Glasgow



THE BYTE SHOP V.D.U.

| | |
|---------------------------------------|------|
| 16 x 64 Display | |
| Upper/Lower Case | |
| Separate Keyboard | |
| Clear 7 x 9 Dot Matrix | |
| British Design & Manufacture | |
| CC1TTV24 or Current loop interface | £359 |
| VDU without keyboard | £299 |

BOOKS GALORE!

| | |
|--|--------|
| Introduction to Microcomputers | |
| Vol. 0 | £5.95 |
| Vol. 1: Basic Concepts | £5.95 |
| Vol. 2: Some Real products | £11.95 |
| Some Common BASIC Programs | £5.95 |
| Instant BASIC | £7.50 |
| Understanding microcomputers | £7.95 |
| Your Home computer | £4.95 |
| 6800 Assembly language programming | £6.95 |
| 808A Assembly language programming | £6.95 |
| Z-80 programming for logic design | £5.95 |
| etc. etc. | |
| Also most U.S. magazines available... | |
| Personal Computing, BYTE, Interface Age, Dr. Dobbs etc. | |

NORTH STAR COMPUTER PRODUCTS



| | |
|--|--------|
| Horizon-1 system, 16K, 1 mini floppy | £1,265 |
| Additional mini floppy | £325 |
| Additional 16K static memory 4MHZ | £315 |
| Printer interface | £70 |
| Extended BASIC and DOS included in above | |

| | |
|-----------------------|------|
| Release 4 BASIC & DOS | £25 |
| CP/M Horizon | £130 |

A value-for-money system using the advanced
Z-80 clip and S100 Bus.

92a Upper Parliament St NOTTINGHAM
Tel: Nottingham (0602) 40576
48 Tottenham Court Rd London W1
Tel: (01) 636 0647

COMMODORE SYSTEMS

| | |
|--|---------|
| Pet personal computer, including V.D.U. | |
| BASIC interpreter + 8K user memory | £643.52 |
| Built-in cassette, ready-to-go | £55.00 |
| Pet 2nd cassette deck | £3.00 |
| Pet software, large selection, from | |
| Joystick, video monitor attachment, now available! | |
| Expander printer, Pet Interface and power supply | £414.00 |
| A very popular and adaptable system, excellent value! | |
| KIM-1 system 2K ROM, 1K RAM etc. | £149.00 |
| KIM-3 additional 8K RAM | £179.00 |
| KIM-4 Motherboard | £89.00 |
| KIM-5 Assembler and Editor | £129.00 |



Send for
FREE catalogue

MAIL ORDER

Please send me

(if preferred, attach order on separate
sheet to coupon)

Name

Address

- ☐ I enclose cheque for £
- ☐ Please debit my Diners Club/
American Express/Access/Barclaycard
Account no.

Please add 8% VAT to all items except books

The Byte Shop Ltd
426-428 Cranbrook Road, Gants Hill,
Ilford Essex. Tel: (01) 554 2177 CT3
All prices correct at time of going to Press

Since the publication of our TRITON ONE BOARD COMPUTER in the November 1978 issue of ETI hundreds of readers have successfully completed the project and we have been inundated with requests for hardware extensions which will allow system expansion for more ambitious applications. We are pleased to be able to publish the first essential peripheral which will allow almost unlimited extensions. This is the MOTHERBOARD. Elsewhere in this issue we give the design of our first, and perhaps most important, peripheral board — an 8K static RAM card. This will shortly be followed by other peripherals all of which will be designed to plug into the motherboard without any changes to internal wiring.

YOUR MOTHER WOULD LIKE IT


In some respects the motherboard is a fairly uninteresting project in itself but it is a means to an end in that it opens the door for a whole host of possible additions to the TRITON. Although we shall be publishing what we feel to be the most generally useful additions individual users will be able to use the motherboard as an interface for any more specialised additions of their own design.

In order to keep the cost within bounds and to avoid too much in the way of redundant circuitry for the bulk of our readers we have designed the motherboard in such a way that when it is in use it will no longer be possible to carry out DMA operations on the TRITON system as a whole. This should only adversely affect a small number of readers but we feel sure that they would be able to embody the necessary modifications and additional circuitry to re-enable this feature if they particularly need it.

When you have read the accompanying article you will note that we have adopted a busbar pinning configuration which we shall now consider to be standard for the TRITON. Any further extensions that we publish will be based on this specification. If any readers eventually design interesting peripherals of their own we would be delighted to publish these for the benefit of others. We beg you, however, to keep any such designs to a single EUROCARD format (custom built or Veroboard pcbs can be used) and adhere strictly to the busbar format. Ideally the designs should allow flexibility in the selection of board or port addresses and provide a correctly

TRITON

Designed by Mike Hughes, complete kits will be available from Transam



Motherboard

formatted DINE signal (see how the motherboard works for details of this).

TAKE CARE OF MOTHER


The motherboard is a high quality double sided board with plated through holes with all closely packed busbar wiring on the topside — well away from the soldering iron. Because of this it is extremely simple and easy to assemble. Space is provided for eight peripheral boards plus an output socket — which will allow one motherboard to be cascaded into another should the need ever arise. As the 64 pin sockets are quite expensive most readers will not wish to insert all of them in the first instance but the bare minimum will be the input socket and a further socket for one peripheral board. As we already have a design for an 8K Static RAM card and are well advanced with the design of an 8K EROM extender board it might be worth considering the insertion of three peripheral board sockets but this

is entirely up to the individual.

Start assembly by inserting all board pins (including all those required for the I/O lands). It is also sensible to drill out all fixing holes to suite your screws but do not, under any circumstances, attempt to drill out electrical connection holes.

Insert all the electronic components according to the overlay drawing taking great care that you observe the correct polarity of the electrolytic capacitors. You should then insert, and bolt into place the board's input socket. **Note** that this is inserted from the **underside** of the board unlike all the other sockets. **It is crucial** that this is inserted from beneath otherwise the whole of the busbar integrity will be reversed with possibly disastrous results. If you get this wrong you will, at best, ruin the PCB when you try to remove the 64 pins after they have been soldered!

To finish off the board you should insert and solder in as many board **»**



SCHEMATIC OF TRITON MOTHERBOARD

TRITON OUTPUT SOCKET

| SIGNAL | PIN |
|--------|-----|
| READY | C1 |
| RESET | C2 |
| Ø2 | C3 |
| A15 | C4 |
| A11 | C5 |
| A14 | C6 |
| A10 | C7 |
| A13 | C8 |
| A12 | C9 |
| INTA | C10 |
| INTE | C11 |
| WAIT | C12 |
| TOW | C13 |
| IOR | C14 |
| HOLD | C15 |
| INT4 | C16 |
| INT5 | C17 |
| INT6 | C18 |
| INT7 | C19 |
| D4 | C20 |
| D3 | C21 |
| D2 | C22 |
| D1 | C23 |
| A9 | C24 |
| A8 | C25 |
| MEMW | C26 |
| MEMR | C27 |
| D5 | C28 |
| D6 | C29 |
| D7 | C30 |
| D8 | C31 |
| GROUND | C32 |
| A7 | A23 |
| A6 | A24 |
| A5 | A25 |
| A0 | A26 |
| A1 | A25 |
| A2 | A28 |
| A4 | A29 |
| A3 | A30 |
| DBIN | A31 |
| HOLA | A32 |

MOTHERBOARD INPUT SOCKET

| PIN | SIGNAL |
|-----|--------|
| C20 | READY |
| A20 | RESET |
| C15 | Ø2 |
| C12 | A15 |
| C10 | A11 |
| A12 | A14 |
| A10 | A10 |
| C11 | A13 |
| A11 | A12 |
| C16 | INTA |
| A15 | INTE |
| A16 | WAIT |
| A18 | TOW |
| A21 | IOR |
| A17 | HOLD |
| A13 | INT4 |
| C13 | INT5 |
| A14 | INT6 |
| C14 | INT7 |
| C24 | D4 |
| A24 | D3 |
| C23 | D2 |
| A23 | D1 |
| C9 | A9 |
| A9 | A8 |
| C18 | MEMW |
| C21 | MEMR |
| A25 | D5 |
| C25 | D6 |
| A26 | D7 |
| C26 | D8 |
| A1 | GROUND |
| C8 | A7 |
| A8 | A6 |
| C7 | A5 |
| A5 | A0 |
| C5 | A1 |
| A6 | A2 |
| A7 | A4 |
| C6 | A3 |
| A19 | DBIN |
| C17 | HOLA |

WIRING DIAGRAM OF TRITON / MOTHERBOARD COUPLING CABLE

NOTE

Once prepared this cable is NOT reversible so the respective sockets should be clearly marked TRITON and MOTHERBOARD.

Keep cable length as short as possible, preferably not more than 75cm.

sockets as are necessary. Note that the socket lands at the extreme end of the board are for a right angled fixing socket for use as an output connector. **Take special care** to ensure you insert the board sockets the right way round so that the pin numbers conform with those shown on the overlay drawing. Excess length of the wire wrap pins can be clipped off when soldering is complete.

It only remains to mount the board within the metal chassis using suitable spacers (ensure that the height of the input socket will match the aperture of the cabinet's cover) and complete the wiring with the transformer and bridge rectifier.

Testing time

Now comes the more tedious job of wiring up the interconnection cable which links the TRITON main board with the motherboard. Do not make this cable too long (preferably keep it less than 75cms). We used two sockets-identical to the type used as board sockets on the motherboard — but cut the wire wrap pins to about 5mms length to avoid the possibility of shorts. Remember to slide the socket covers on to your wiring loom **before** you solder up both ends of the cable! We forgot and lived to regret it when we had to unsolder and resolder 42 connections!

Take great care in making up this cable to ensure that you follow the pin to pin wiring chart precisely and when you have completed it you should

How It Works

The motherboard's function is to permit extensions of memory or input/output peripherals for the TRITON main board. These additions can be built on single Eurocards and plugged into one of the eight socketed locations on the motherboard. Each card which is added can draw power from a common unregulated busbar which is fed to specified pins on each socket. These power rails carry raw d.c. of +18V (1A), -18V(1A), +10V (6A) and -10V(1A). These voltages have been chosen to give standard ±12 and ±5V after regulation-it being assumed that most current will be needed at +5V and the least at -12V. Whether or not these currents are sufficient will depend very much on the types of board plugged in but it is assumed that there will be sufficient power availability for most applications. If, for very large systems, more current is required (typically at +5V) it is only necessary to upgrade the transformer and the respective rectifiers. This will probably not be necessary but anyone who intends designing his own extensions should remember to take note of current consumptions.

Apart from providing power to its sockets the motherboard also contains a minimal number of integrated circuits. IC1 contains buffer for the seven unbuffered outputs from the TRITON

main board and IC2 is a bi-directional buffer (with tristate outputs) to interface the data busbar with the motherboard. A small amount of logic is needed to control the enabling of this data buffer when it is transmitting towards the TRITON main board. This logic is provided by a simple AND gate. The DBIN (Data Bus In) signal controls the direction of the buffer and when this is "0" (i.e. indicating an output from the CPU) the motherboard's data bus is enabled irrespective of any other conditions. When DBIN is "1" the buffer is **not** enabled unless the special DINE line is at "0". The DINE signal (Data In Enable) is obtained by wired oring of a suitable signal from each of the peripheral boards. This signal should be obtained from the decoded board select address in the case of memory boards but in the case of Input/Output port addressing it should be obtained by ANDING the respective Board/Port Select with IOR. The gate supplying this signal from each board **must** be of the open collector type.

Apart from the foregoing the motherboard acts as an interconnection between the TRITON main board and the peripheral boards by carrying the complete address and control busbars which are adequately buffered within

TRITON itself.

The respective signals on TRITON's main board extender socket are not organised in any particular order and it is necessary to feed these to the input socket of the motherboard via a 42 way cable. Note that DINE does not connect back to the TRITON main board. It is most important to adhere precisely to the pin numbering configurations for this cable the details of which are shown in Fig 0. We do not claim that the TRITON BUS conforms to any other standard but the pin configurations for power, address and data lines are the same as those specified for Eurobus.

Each peripheral board socket has eight spare connections brought out to soldering lands on the edge of the motherboard. These are to provide Input or Output lines from specific boards which can be wired to output sockets on the end panel of the cabinet. These are user definable but we shall be making use of some of these in future projects involving peripherals. Readers will note that there are two spare Bus lines running through the motherboard — these are on pins C19 and C22 — they may be used for special applications or the bus track can be broken and the pins used to provide an extra couple of I/O outlets.

Parts List

RESISTORS

R1 4k1 10% 1/4W

CAPACITORS

C1 470n polyester

C2 4700uF 25V

C3 4700uF "

C4 4700uF "

C5 4700uF "

SEMICONDUCTORS

D1 to D12 1N4001 (25V 1A rectifiers)

BRIDGE 25V 6A

IC1 74LS244

IC2 74LS245

IC3 74LS08

IC4 7805C +5V plastic regulator

MISCELLANEOUS

T1 Mains transformer 15V, 1A; 15V, 1/2A;

9V, 1A; 9V, 6A secondaries.

F1 panel fuse holder (1A)

Printed Circuit Board

Input socket (Plus optional output socket)

1 (or more) board sockets

2 interconnecting cable sockets and covers

Metal chassis and cover


2 off 20 pin DIL sockets

1 off 14 pin DIL socket

permanently mark each socket to show which end of the cable is which — **it is not reversible.**

Our suggested test of the motherboard is rather negative because — on its own — it does not do anything. None the less it is worth doing the following to ensure that nothing particularly wrong has happened.


With TRITON switched off plug in the motherboard to TRITON making sure you have used the cable the right way round and apply power to the motherboard. Check that you have +5V at the respective pins of the three



IMPORTANT

This socket is inserted from **UNDERSIDE** of board.

Insert as many sockets as required



integrated circuits. Check also that you have approximately the correct nominal voltages on the four power busbars. Because there is no load at present these might read a little high. You should see around ± 19 and ± 11 volts.


When you are satisfied that all this is well you should switch on the TRITON and it should initialise as if nothing had happened. If you get normal initialisation followed by the repeating message "INVALID" check that you have put in the modifying link taking the +5V rail straight to



pin 28 of IC6 on the TRITON main board (we have drawn attention to this elsewhere in the magazine).

If your TRITON has always operated satisfactorily until now but refuses to initialise you can be pretty sure that you have a short circuit between tracks of the data, address, or control busbars on, or feeding to, the motherboard. If this is the case you should switch off and disconnect the linking cable and systematically check every possible combination of the 42 wires for continuity (going from the right pin of one plug to the right pin of

the other) and shorts between adjacent pins. Following on from this you should carefully check every combination of bus line pairs on both sides of the mother board buffers.



When all is well and your computer initialises you can be pretty certain that the motherboard is working correctly but you cannot know this for sure until you have a peripheral board plugged into it. When using TRITON with the motherboard you must always make sure that power is applied to the motherboard **before** you switch on the TRITON. »





THIRD ANGLE PROJECTION
all dimensions in mm

MOTHERBOARD CHASSIS
Fabricate from 2mm aluminium
Supply complete with 4 rubber
feet and cover (attached with
self-lapping screws)
See second drawing for details
of cover and LEFT END drilling



RAM Card

REMEMBER, REMEMBER

This 8K static RAM card contains 8192 contiguous bytes of read write memory organised in blocks of 1K. For reasons of economy some people might wish to expand their system in easy stages in which case the chips can be added to this board in units of 1K. The board itself can have its start point address selected by means of a jumper wire (or DIL switch) and can be positioned at the start of any 8K region in a 64K memory map. In the case of TRITON the lowest order 8K region is entirely taken up by the main board so it is assumed that the first RAM extension card should be positioned to start at 2000H to make it contiguous with existing memory.


The card is designed to plug directly into the TRITON MOTHERBOARD and draws, typically, 1A from the +10V unregulated power bus. It is designed specifically to interface with the TRITON BUS configuration and provides the correct DINE signal; no claim is made that it will operate in other systems without modification.

It is built on a specially designed double sided Euro card and assembly is extremely straightforward — average building time being about 3 hours.

Insert and solder all integrated circuit sockets **one at a time** ensuring that no connections are missed. Start with the larger sockets — this will prevent you accidentally soldering in an 18 pin socket where there ought to be one having 20 pins etc! We suggest using a 16 pin DIL socket to carry the board select jumper wire so that this can be altered to reposition the board's address should the need arise. Where expense is no object and for development systems you could, as we did, use plug in DIL switches in this socket.

When all sockets are in position make sure you solder in the two pull up resistors.

The next stage is to bolt and solder in the 64 way Eurosocket. This is inserted from the component side of the board. Move on to the two +5V regulators making sure you insert them the right way round and then



How It Works

IC1 is a bidirectional buffer for the 8 bit data busbar and receives and transmits data to the motherboard. Its direction of operation is controlled by the DBIN signal but its outputs are not enabled unless the board recognises its own address (decoded by IC4) — this enabling signal is a "0" on pin 19 of IC1. The 16 bits of the address busbar are buffered by ICs 2 and 3 which are permanently enabled.

The three highest order bits of the address busbar (A15, A14 and A13) are used to decode which 8K region the board sits in. There are 8 possibilities so we are using a three to eight line decoder. Only one of the eight possible outputs will go to "0" for a given high order address and we can select one of these outputs to identify the board's starting address. This is done by means of a wire link. We anticipate that all our memory extension cards will be of 8K capacity therefore it is convenient to think of the 8 possible regions of 8K being designated 0, 1, 2 etc. up to 7. The memory map of the TRITON system can then be simply defined by the following chart:

| Region | Address limits | Description |
|--------|----------------|---|
| 0 | 0000H—1FFFF | TRITON main board embracing EROM, VDU and RAM |
| 1 | 2000H—3FFFF | User definable |
| 2 | 4000H—5FFFF | User definable |
| 3 | 6000H—7FFFF | User definable |
| 4 | 8000H—9FFFF | User definable |
| 5 | A000H—BFFFF | User definable |
| 6 | C000H—DFFFF | User definable |
| 7 | E000H—FFFFH | User definable |

Region 0 is already spoken for by the TRITON main board so none of the extension cards must sit in this area. We would expect that most people will wish to have contiguous memory (i.e. an unbroken sequence of addresses) starting from 1600H which is the start of work area on the main board so the first RAM extension card should be situated in Region 1, the next in region 2 etc. Any specialised memory could then be sited at the high order end of the map (regions 6 and 7). These comments are, of course, generalisations and individual users can arrange their memory in any order they wish using the 8K regions as building bricks.

In the case of this static RAM card we are using pairs of 1K x 4 memory chips type MCM21L14 (note we are specifying the low power version to economise on total current consumption — the higher power versions CAN be used but board dissipation might get uncomfortably near the limit of the voltage regulators). This allows us to organise the memory within the board into 8 blocks of 1K apiece. These can be conveniently and individually selected by the three next lower address lines (A12, A11 and A10) through a further three to eight line decoder (IC6). We have to use the board select signal to enable this decoder so that the blocks are selected ONLY when the board as a whole is addressed. This enabling signal is fed into pins 4 and 5 of IC6. We have designated the eight block selects signals (active low) as S0 to S7. S0 represents the lowest order block of the board so for contiguous memory you should insert memory chips into locations IC7 and 8 in the first


instance and then works upwards (that is if you do not intend to put a complete load of RAM into the board in the first instance).

As the RAM chips are organised as 4 bit wide "nibbles" we have to use two Integrated circuits for each block. Odd number component designations (IC7,9 11 etc) represent the low order nibbles and even numbers (IC8, 10 12 etc) the high order.

The ten lowest order address lines are paralleled to all the RAM chips on the board in the usual way but please note that we are NOT using the data sheet's designations for the addresses. The reason for this is tied into the convenience of the board's layout. It makes no difference to the operation but some people might query why we have done this. A small amount of logic is needed to organise the MEMR and MEMW command signals to interface these with the RAM's writing and select inputs. This is provided for by the NAND gate (IC5d). The logic ensures that a select line becomes active whenever either the MEMR or MEMW lines go low but the WRITE input of the RAM is only taken low when MEMW is active.

ICs 5a and 5b take the board select signal and output this as an active low through the open collector gate (IC5b). This is the DINE (Data In Enable) which can be wired or with similar signals from other boards on to the motherboard busbar. This is used to enable the motherboard's data bus buffer during memory or I/O read operations.

Two 1A regulators are used to provide +5V.



insert all the capacitors checking the polarity of C12.

Assemble the special heat sink to the regulators making sure that the fixing bolts are really tight — quite a lot of heat is dissipated and the heat sink size is a bare minimum. If you

make your own from our drawing we recommend that you paint it black to increase its radiating efficiency. Check that no parts of the heatsink touch any components (particularly the three capacitors in close proximity) or any of the topside foil tracks (one of the +5V

rails goes fairly close to the board mounting hole of the heatsink). Insert all integrated circuits with the RAM starting at block "0".

To test the board make up a DIL pin header with a jumper wire bridging the "1" position (this positions the

Further thoughts on Triton

From talks with TRITON users and feedback from the hundreds of people who have their systems up and running we are now able to pin point one or two features which might help those who are just about to start the project.

- 1) By far the greatest cause of systems not working in the first instance is that integrated circuits have not been correctly inserted into their sockets. The most common fault is in having a pin bent under (this happens during insertion and is difficult to notice unless the ICs are systematically removed, checked and replaced).
- 2) The second cause is the missing of one or two soldered connections. We repeat, again, the suggestion that you solder in ONE socket at a time and check it thoroughly BEFORE going on to the next.
- 3) If the system works satisfactorily with the Monitor plugged in but fails as soon as the two BASIC chips are inserted this is probably due to the design error we have already referred to. You should make sure that

R1 is a 39 ohm 1½W resistor and ZD1 is up-rated to 5V1 at 1W.

- 4) From experience we have noticed that one or two systems suffer from a power line "glitch" which affects the system control chip (IC6). The symptom of this is when the computer occasionally prints a "-" of its own accord and, when under the control of the Monitor in its initialisation condition, follows this with the statement "INVALID". This problem can be easily cured with an insulated wire link (as short as possible) from the top side track feeding pin 28 of IC6 to the wide +5V track (on the topside) adjacent to R1. Even if you do not, at present, suffer from this problem you would be well advised to put this link in.
- 5) We recommend that you do NOT use the board mounting hole situated next to RV1 because it is rather too close to one of the underside tracks of the data busbar. If you use a nut instead of a stand-off you might short this track to ground. The symptom of this is that the system initialises but instead of printing the normal message a weird selection of letters and graphics is presented.
- 6) If you have trouble with the Tape I/O and are using a

board to start at address 2000H). Plug the board into any slot of the motherboard and connect the motherboard to TRITON.

Test with Triton

Do not apply power to TRITON at this stage but switch on the motherboard's supply. Check that +5V exists on both main rails of the RAM card and wait a few minutes for the heat-sink to get up to temperature. It will run fairly hot — up to about 50°C.


We will assume that you have completely filled the 8 blocks of RAM of the card for the following tests. While the motherboard is switched on you should now apply power to TRITON. (NOTE always switch the motherboard on BEFORE you switch on TRITON). You should notice a slightly longer delay before the VDU screen is cleared and you get the normal initialisation message.

Using the P function check the contents of address locations 1481 and 1482. If you have a full main board and have inserted all 16 RAM chips on the RAM card the data contained in these two locations should be 00 and 40 respectively. This indicates that the first address where there is no RAM starts at 4000H. If any other data is found in these positions it will tell you the address at which your memory has failed and this should be of help in finding the fault (probably an IC incorrectly inserted).

If all is well you can try writing and reading within the memory region 2000H and 3FFFH.

If you make up more than one RAM board you must make sure that you use different address selections for them or else very strange things will happen!

CT



Parts List

RESISTORS

R1 4k7 10% 1/4W
R2 4k7 " "

CAPACITORS

C1-C9 47n ceramic
C10-C11 470n polyester
C12 220u 16V electrolytic

SEMICONDUCTORS

IC1 74LS245
IC2 74LS244
IC3 74LS244
IC4 74LS138

IC5 74LS03

IC6 74LS138

IC7-IC22 MCM21L14 (or similar)

IC23-IC24 7805C (+5V 1A regulators)

MISCELLANEOUS

PCB
64 way Eurosocket
Heat sink for regulators (see drawing)
3 off 20 pin DIL sockets
16 off 18 pin DIL sockets
3 off 16 pin DIL sockets
1 off 14 pin DIL socket
16 pin DIL header (for wire link)

mains driven tape recorder it is quite likely that you are suffering from an "Earth loop" problem which introduces a high level of hum on the tape input line. This is simply cured by breaking the mains earth connection on the tape recorder — thus relying on the braid of your coaxial cable to bond the system together.

- 7) RLY1 is only a small reed relay and is not rated to switch more than 1A at LOW VOLTAGE. Excessive voltage and current could cause the contacts to weld together!
- 8) If, when operating in BASIC, you get "Sorry" every time you enter an instruction it means that the BASIC INTERPRETER thinks it hasn't any memory. This could be a fault associated with ICs 29 and 30 or, more likely, is because you have — previously — been playing around in machine code and have inadvertently altered the table area of RAM which tells BASIC how much memory there is. You can check this by looking at address locations 1481 and 1482 (Hex) these should contain the address of the first location where RAM ceases to exist — for a board full of RAM the data contained therein should be 00 and

20 respectively. You can either manually enter this data or switch the system off and on again to carry out a new "power on initialisation".

- 9) There is a very minor bug in the Monitor which means that when you initially jump to BASIC and immediately ask it to PRINT SIZE without there being any program present it MIGHT give an erroneous answer if address locations 1600 and 1601 do not contain any valid end of text address. The simplest way of avoiding this bug is to enter "NEW" before starting to write any program in BASIC. This problem does not occur if BASIC is used immediately after switch on, only if you have been doing other things in machine code before jumping to BASIC.
- 10) You can get a very much higher resolution display by using a video monitor instead of a conventional television set. A suitable signal can be extracted from the negative end of C23. Together with a common ground connection this should be fed to a 75 ohm terminated video monitor input. UNDER NO CIRCUMSTANCES feed this signal to a modified domestic television set unless you are certain the television ground is properly isolated from mains!

Hard Lines

Richard Straker has sent us this hardware tip.

Having plucked up enough courage to go for a byte from the everswelling microprocessor apple it soon became apparent that there was more than one obstacle between me and the fruit tree. How to provide the eight bits in a row for the CPU without using DIL switches and probably losing some of the fingernails to which I have become so attached, was the first problem and the one that started this article.


IC4 and 5 are programmable 4 bit latches with active LOW load lines. Data on the four input lines transfers to the output lines when the load line goes low and is latched there when the load line goes high. Therefore if the load lines are made to go low in turn and the appropriate data is fed to the input lines, then an 8 bit byte is produced by combining the two 4 bit outputs. IC2, 3, and IC1 in conjunction with the Key line from the keyboard cause the access of firstly IC4 and then IC5 and then back again to IC4 and so on. IC2a, b, c make up a monostable and inverter fed from a negative going pulse from the Key line. The monostable avoids keybounce problems. The positive going pulse from IC2b is fed to the joined gates of IC1d and IC2d and the clock of the JK flip flop IC3 which toggles. Thus in the reset/clear condition with Q=1, IC1d and hence IC4 are ready to receive a data load pulse. On the 1st key operation a pulse is produced which causes a low on the load line of IC4 and data is latched. On the downward slope of the pulse from IC2b, IC3 toggles to Q=1 and Q=0. Therefore IC2d and hence IC5 are now ready for their data load pulse. This occurs on the second key operation. However as IC3 toggles to its original reset

condition Q goes low causing monostable IC1a, b, c, to produce a positive pulse which fires the flag line and the associated flag LED, indicating a full 8 bits worth of data. This flag can be used to drive the CPU equipment. These flag pulses are inhibited when the reset/clear is operated by the earthing of D1 which holds low the input on IC1a. This holds the output of IC1a at 1 despite the charging of C1.

The reset/ready LED is lit when IC3 is in the reset condition, that is before or after a full keyboard operation. It may be considered superfluous as an indication of data present is given by the 8 output line LEDs themselves. (Except at 0000 0000 of course).

The keyboard encoding is self-explanatory, the ABCD data lines being held high until taken low by the appropriate key to earth. Hence to encode 0 requires 4 diodes and F none. Each key requires a diode to Key line. Construction of the matrix, because the whole of the circuit was to be inserted into an old LED calculator case incorporating the keypad, had to be small. Therefore the diodes were sandwiched between two pieces of Vero board with tracks at right angles to each other, facing outwards. The diodes were soldered to the main board on 16 tracks first and then the other ends fed carefully through the smaller piece of Vero with 5 tracks. BEFORE the other ends are soldered positioning and continuity must be checked as replacement of diodes later would be next to impossible. This fiddly chore is worth it as the final construction is only about .4 inch deep (including solder blobs).

CT



Britain is a nation of PET lovers

**THE No. 1
Personal
Computer
in the
U.K.**

**Hobbyist
Commercial
Scientist
Education**

**Affordable
£695
inc. VAT**

for the first time
user and the professional
check out the PET, the world's
most popular personal computer

- * **CAPABLE** - just like a traditional computer.
- * **UNDERSTANDABLE** - fast, comprehensive and powerful - BASIC is one of the easiest computer languages to learn, understand and use. Machine language accessibility for the professionals.
- * **PERSONAL** - easily portable and operated - just "plug in" and go. Unique graphics make fascinating displays.
- * **EXPANDABLE** - built in IEEE-488 output, 8K RAM expandable to 32K, parallel user port 2nd. Cassette interface.
- * **SERVICEABLE** - easily serviced - only 3p.c. boards all readily accessible.

Features of PETS extended BASIC include

Integer, floating point and string variables; A full set of scientific functions, Logical operators, Multi-statement lines. String functions, Left \$, Right \$, Mid \$, Chr \$, Val, Str \$, Peek, Poke, Usr, Sys, to interface to memory and machine language subroutines. Time of day variable.

Future Commodore developments * FLOPPY DISC * PRINTER
* MEMORY EXPANSION * MODEM

Extensive software readily available.

Contact your nearest PET dealer, call today for a demonstration

AUTHORISED PET COMMODORE DEALERS

Birmingham

Taylor-Wilson Systems Ltd.
(05645) 6192

Bristol

Sumlock Tabdown Ltd
0272-26685

Derby

Davidson-Richards (Int) Ltd
0332-366803

Durham

Dyson Instruments
0385-66937

Grimsby

Allen Computers
0472-40568

Guildford

P.P.M.
0483-37337

Hemel Hempstead

Data Efficiency Ltd
0442-57137

Liverpool

Dams Office Equipment Ltd
051-227-3301

London E.C.1

Sumlock Boudain Ltd
01-253 2447

Manchester

Cytek (UK) Ltd
061-832-7604

Sumlock Electronic
Services
061-228-3507

Newport

G.R. Electronics Ltd
0633-67426

Northern Ireland

Medical & Scientific
08462-77533

Nottingham

Betos (Systems) Ltd
0602-48108

Reading

C.S.E. (Computers)
0734-61492

Southampton

Business Electronics
0703 738248

Southampton

Symtec Systems Ltd
0703-37731

Thame, Oxon

Memec Systems Ltd
084-421-2149

Woking

Petalect Ltd
048-62-69032

**In case of difficulty call COMMODORE SYSTEMS DIVISION
360 Euston Road, London. Tel. 01-388-5702**

Airamco Ltd.

MICRO COMPUTER PRODUCTS

Distributors for JADE COMPUTER PRODUCTS
All products brand new with full industrial specification

NEW LOW PRICE!

SD SALES Z-80 STARTER KIT

Single card development system — like a KIM or D2 but uses Z80, on board PROM PROG up to 2K RAM. 2 x 5100 sockets provided for on board — plus many new features.

KIT PRICE £145.00
ASSEMBLED + GUARANTEE £249.95

| S100 COMPUTER CARDS KIT | ASSEMBLED | BARE BOARD |
|--|-----------|------------|
| Mother Board | £82.50 | £26.25 |
| Desk Top Rack, 12 slot mother board + 15A at 8V, 2A at ± 16V | £259.00 | £149.00 |
| Jade 8080A CPU BOARD | £122.50 | £22.50 |
| Jade 8K static RAM BOARD 450nS | £112.50 | £19.95 |
| Jade 8K static RAM BOARD 350nS | £119.96 | £19.95 |
| Jade 8K static RAM BOARD 250nS | £142.50 | £19.95 |
| S.D.Sales "EXPANDORAM" Dynamic Memory 375nS access time 16K | £274.95 | — |
| Memory 375nS access time 32K | £347.95 | — |
| Memory 375nS access time 48K | £424.95 | — |
| Memory 375nS access time 64K | £499.95 | £513.00 |
| VERSAFLOPPY DISK CONTROLLER (up to 4 drives 5 1/4 or 8) | £169.00 | — |
| SHUGART 8" Drive SA800/801 | £355.00 | — |
| SHUGART 5 1/4" Drive SA400 | £190.00 | — |

Components

2708 1024 x8 EPROM £6.99
2516 2048 x8 EPROM £29.90
(equivalent of above) T.I. £4.85
1702 256 x8 EPROM £4.85
2104 4096 x1 DRAM £3.50
8 for £26.00
2107B-4 4096 x1 DRAM £3.50
8 for £26.00

Yet again Note New Low Prices 16K Dynamic Memory

4116 16K x 1 DRAM £9.90
4215 8 for £69.00

AY 51013 UART £4.50
AY51014 UART(5V) £6.50
AY53600 ENCODER £9.99
8080A CPU £8.99
2114 (450ns) £6.75

AY-5-2736 £9.50
21L02-1 450nS £1.20
8 for £7.92
21L02 250nS £1.40
8 for £9.60
2112-1 256 x4 (450) £2.25
4044 4K x 1 (450) £7.45
4045 1K x 4 (450) £8.25
New Device MK4118 P4 (24 pin)
1k x8 bit static RAM 250 NS.
Similar pin out to 2708 EPROM.
Price £18.90 each. Data available
(ceramic device)
8212 £2.49
8216 £2.75
8224-4 £7.46
8226 £2.95
3881 £9.50
3882 £9.50
S100 Skts. £3.30
Textool 24 pin Zero
force Skt. £5.60
81LS95 £1.25
81LS97 £1.25

Secondhand Research machines 280Z 20K

Memory plus software...
offers Shugart Floppy Disc Drive Controller, 8-inch and 5-inch

All Prices EXCLUDE VAT at 8%.

Trade discounts on Quantity.

Please add £1.00 P&P for S100 items then add VAT at 8%.

24-hr. Ansaphone order service with ACCESS or BARCLAYCARD.
MAIL ORDER ONLY.


For components please add 40p P&P, then add VAT at 8%.

AIRAMCO LTD.
30 WITCHES LINN
ARDROSSAN
AYRSHIRE
KA22 8BR
TEL. 0294 65530
TELEX 779808 RAMCO

Semiconductor prices are always changing and the trend is generally downwards. So ring for latest up-to-date details.



NON-SUBSCRIBERS START HERE



It can be a nuisance can't it, going from newsagent to newsagent? "Sorry, Squire, don't have it — next one should be out soon."

Although CT is monthly, it's very rare to find it available after the first week. If it is available, the newsagent's going to be sure to cut his order for the next issue — but we're glad to say it doesn't happen very often.

Do yourself, your newsagent and us a favour. Place a regular order for CT; your newsagent will almost certainly be delighted. If not, you can take out a postal subscription so there's nothing for you to remember — we'll do it for you.

For a subscription, send us £8.00 (£9.00 overseas) and tell us which issue you want to start with. Please make your payment (in Sterling please for overseas readers) to CT Subscriptions and keep it separate from any other services you want at the same time.

CT Subscriptions

Computing Today International,
25-27 Oxford Street, London W1R 1RF.

Softspot

STOMPER is a program by Pete Howells which should appeal to the meaner side of us all. The object of the game is to chase an insect around the screen and kill it.

The program, as listed, is suitable for running in 4K on a PET. It is the result of sitting down at the machine and doing it, and, as you can see, in no way have the most efficient or elegant solutions to the problem been used.

```

1 PRINT "DO YOU WANT INSTRUCTIONS (Y
  OR N)
2 GETA$
3 IFA$="" THEN GOTO 2
4 IFA$="Y" THEN GOTO 700
5 DIM B$(8),C(8)
6 YY=160:MM=102:SS=46:SY=32
7 DATA "7",-41,"8",-40,"9",-39,"4",-1,"6",1,
  "1",39,"2",40,"3",41
8 FOR K=1 TO 8:READ B$(K),C(K):NEXT
10 REM
15 INPUT "SET SPEED (1 TO 10) ";DF
16 IF DF>10 OR DF<1 THEN GOTO 10
20 DF=DF/50
100 J=32768
105 PRINT ""
110 I=33267
111 POKE J,YY

```

This is the initialisation bit i.e. printing instructions if required, setting the graphics characters for the target etc., setting up a table for "key pressed"/"direction of move" and setting the delay for the speed. J is the position of the cursor, I for the target. Line 105 is to clear the screen, but the clear screen character is not reproduced by the printer.

```

200 GETA$
210 IFA$="" THEN GOTO 260
212 IFA$="S" THEN GOTO 500
213 IFA$="N" THEN GOTO 900
215 POKE J,SS
220 FOR K=1 TO 8
230 IFA$=B$(K) THEN J=J+C(K)
235 NEXT K
240 IF J>33767 THEN J=J-40
250 IF J<32768 THEN J=J+40
260 POKE J,YY


```

Moving the cursor; the direction depending on which key was pressed — the main action takes place in the loop on lines 220-235. Lines 240 and 250 stop you from going off the top and bottom of the screen.

```

265 IF RND(TI)>DF THEN 200
270 X=RND(TI)

```



```

271 POKE I-41,32
272 POKE I-40,32
273 POKE I-39,32
274 POKE I-1,32
275 POKE I,SY
276 POKE I+1,32
277 POKE I+2,32:POKE I+3,32
278 POKE I+39,32
279 POKE I+40,32
280 POKE I+41,32
281 IF X<.25 THEN I=I-40
290 IF X>.25 AND X<.5 THEN I=I-1
300 IF X>.5 AND X<.75 THEN I=I+1
310 IF X>.75 THEN I=I+40
320 IF I>33767 THEN I=I-40
330 IF I<32768 THEN I=I+40
340 POKE I,MM
341 POKE I-41,77
342 POKE I-40,66
343 POKE I-39,78
344 POKE I-1,87
345 POKE I+1,64:POKE I+2,64:POKE I+3,64
346 POKE I+39,78:POKE I+40,66
347 POKE I+41,77
350 GOTO 200

```

Moving the target; the speed delay takes place at 265. Lines 271-280 blank the target, lines 281-330 move the target and lines 340-350 restore the image on the screen.

```

500 IF I=J THEN GOTO 600
510 POKE J,YY:POKE I,MM
520 PRINT "          MISSED"

```



```

521 MX=MX+1
522 PRINT " ";100*(N/(N+MX+1E-30));"%HITS"
523 FORKK=1TO1000:NEXTKK
525 PRINT ""
530 GOTO270
600 N=N+1
605 POKEI-2,19:POKEI-1,16:
    POKEI,12:POKEI+1,1:POKEI+2,20
606 POKEI-3,64
610 PRINT " HIT";N
613 PRINT " ";100*(N/(N+MX+1E-30)):
    "%HITS"
614 FORKK=1TO1000:NEXTKK
615 PRINT ""
616 J=32768
620 GOTO200

```

The test for a "hit" (the position of the cursor and the position of the target coincide) is made at line 500. If they don't a message is displayed which is kept on the screen for the duration of the delay at line 523. The game then continues from where it was left off. If a "hit" has been scored then again a message is displayed, but the cursor position is reset (line 616) before continuing.

```

700 PRINT "THE OBJECT OF THE GAME IS TO
'STOMP' "
710 PRINT "ON THE INSECT. TO DO THIS YOU
MUST"
720 PRINT "MOVE YOURSELF (WHITE) OVER
THE INSECT'S"
730 PRINT "BODY AND, ONCE OVER IT, PRESS
THE"
740 PRINT " 'S' KEY. THE INSECT, HOWEVER
DOES"
750 PRINT "NOT STAY STILL: THE SPEED IS SET
AT"
760 PRINT "THE START OF THE GAME TO A
VALUE OF"
770 PRINT "BETWEEN 1 AND 10. TO MOVE
YOURSELF"
780 PRINT "USE THE NUMBER KEYS (1-9, BUT
NOT 5)"
790 PRINT "'N' RESTARTS THE GAME AT ANY
TIME"
800 PRINT "PRESS ANY KEY TO START"
810 GET A$
820 IFA$=""THEN GOTO810
830 GOTO5
900 N=0: MX=0
950 GOTO10

```


This displays the instructions. The lines, along with lines 1-4, can be omitted if the facility is not required.

```

THE OBJECT OF THE GAME IS TO 'STOMP'
ON THE INSECT. TO DO THIS YOU MUST
MOVE YOURSELF (WHITE) OVER THE INSECT'S
BODY AND, ONCE OVER IT, PRESS THE
'S' KEY. THE INSECT, HOWEVER, DOES
NOT STAY STILL: THE SPEED IS SET AT
THE START OF THE GAME TO A VALUE OF
BETWEEN 1 AND 10. TO MOVE YOURSELF
USE THE NUMBER KEYS (1-9, BUT NOT 5)
'N' RESTARTS THE GAME AT ANY TIME

PRESS ANY KEY TO START

```



The program leaves plenty of room for improvement, and not only in its logical structure. The scoring system could easily be made more imaginative, for instance, and the intricacy of the game increased — a suggestion is to have the insect slow down if a leg is stomped off.

Geography test program

The program shown will test the geographical knowledge of the user.

The program will first prompt with a request for the area of the world that will be tested — options are Europe, South America and Asia. After this the machine will prompt with a request that the user enters the name of the capital city of one of the countries within the chosen continent. After ten questions the computer will show the score for the session and enquire whether or not the user wishes the test to continue.

The program was written for TRITON but should be suitable for implementation on most small BASIC systems.

```

10 PRINT "GEOGRAPHY TEST—CAPITAL
CITIES"
20 LET R=0,W=0
30 PRINT
40 PRINT "1.EUROPE 2.SOUTH AMERICA
3.ASIA"
50 PRINT
60 INPUT "PLEASE TYPE NUMBER OF CONTI-
NENT CHOSEN" A
70 IF A=1 GOTO 100
80 IF A=2 GOTO 180
90 IF A=3 GOTO 260
100 PRINT
110 FOR I=1 TO 12: at(I)=0: NEXT I
120 FOR L=1 TO 12
130 PRINT
140 PRINT "WHAT IS THE CAPITAL OF"; GOSUB
340
150 GOSUB 500; INPUT "THE ANSWER IS
NUMBER" B; GOSUB 910
160 NEXT L

```



```

170 GOTO 940
180 PRINT
190 FOR J=1 TO 10; at (J)=0; NEXT J
200 FOR M=1 TO 10
210 PRINT
220 PRINT "WHAT IS THE CAPITAL OF"; GOSUB
    550
230 GOSUB 690; INPUT "THE ANSWER IS
    NUMBER" B; GOSUB 910
240 NEXT M
250 GOTO 940
260 PRINT
270 FOR K=1 TO 10; at(K)-0; NEXT K
280 FOR N=1 TO 10
290 PRINT
300 PRINT "WHAT IS THE CAPITAL OF"; GOSUB
    730
310 GOSUB 870; INPUT "THE ANSWER IS
    NUMBER" B; GOSUB 910
320 NEXT N
330 GOTO 940
340 Z=RND(12)
350 IF at(Z) #0 GOTO 340
360 at(Z)=1
370 IF Z=1 PRINT "ITALY"
380 IF Z=2 PRINT "GREECE"
390 IF Z=3 PRINT "DENMARK"
400 IF Z=4 PRINT "E.GERMANY"
410 IF Z=5 PRINT "NORWAY"
420 IF Z=6 PRINT "PORTUGAL"
430 IF Z=7 PRINT "SPAIN"
440 IF Z=8 PRINT "SWEDEN"
450 IF Z=9 PRINT "W.GERMANY"
460 IF Z=10 PRINT "BELGIUM"
470 IF Z=11 PRINT "POLAND"
480 IF Z=12 PRINT "AUSTRIA"
490 RETURN
500 PRINT "1.ROME 2.ATHENS 3.COPENHAGEN
    4.BERLIN 5.OSLO",
510 PRINT "6.LISBON",
520 PRINT "7.MADRID 8.STOCKHOLM 9.BONN
    10.BRUSSELS 11.WARSAW",
530 PRINT "12.VIENNA"
540 RETURN
550 Z=RND(10)
560 IF at(Z) #0 GOTO 550
570 at(Z)=1
580 IF Z=1 PRINT "GUYANA"
590 IF Z=2 PRINT "PARAGUAY"
600 IF Z=3 PRINT "COLUMBIA"
610 IF Z=4 PRINT "PERU"
620 IF Z=5 PRINT "VENEZUELA"
630 IF Z=6 PRINT "ARGENTINA"
640 IF Z=7 PRINT "ECUADOR"
650 IF Z=8 PRINT "BOLIVIA"
660 IF Z=9 PRINT "URUGUAY"
670 IF Z=10 PRINT "CHILE"
680 RETURN
690 PRINT "1.GEORGETOWN 2.ASUNCION
    3.BOGOTA 4.LIMA 5.CARACAS"
700 PRINT "6.BUENOS AIRES 7.QUITO 8.LA PAZ
    9.MONTEVIDEO",
710 PRINT "10.SANTIAGO"
720 RETURN
730 Z=RND(10)
740 IF at(Z) #0 GOTO 730
750 at(Z)=1
760 IF Z=1 PRINT "MALAYSIA"

```

```

770 IF Z=2 PRINT "BURMA"
780 IF Z=3 PRINT "BANGLADESH"
790 IF Z=4 PRINT "PHILIPPINES"
800 IF Z=5 PRINT "THAILAND"
810 IF Z=6 PRINT "INDONESIA"
820 IF Z=7 PRINT "LAOS"
830 IF Z=8 PRINT "CAMBODIA"
840 IF Z=9 PRINT "IRAN"
850 IF Z=10 PRINT "IRAQ"
860 RETURN
870 PRINT "1.KUALA LUMPUR 2.RANGOON
    3.DACCA 4.MANILA 5.BANGKOK"
880 PRINT "6.JAKARTA 7.VIENTIANE 8.PHOM
    PENH 9.TEHRAN",
890 PRINT "10.BAGHDAD"
900 RETURN
910 IF B=Z PRINT "CORRECT"; LET R=R+1
920 IF B#Z PRINT "WRONG. THE ANSWER IS
    NUMBER", #3, Z; LET W=W+1
930 RETURN
940 PRINT "END OF TEST"
950 PRINT "YOUR SCORE IS", #3, R, "RIGHT
    AND", #3, W, "WRONG"
960 PRINT "OUT OF", #3, (R+W), "TURNS"
970 LET Y=0, N=1
980 INPUT "DO YOU WISH TO CONTINUE? Y OR
    N" C
990 IF C=0 GOTO 10
1000 IF C=1 PRINT "END OF PROGRAMME"
1010 STOP

```

CT

Written for the Nascom

Among the programs written to run on the Nascom-1 and available now are:

ICL Dataskil Letter Editor

This software provides a comprehensive set of data operations. Text can be input, displayed, edited, stored on tape, retrieved and further amended. Control functions include cursor, character, word, line, scrolling, tabbing, tape store and retrieve, text printing. All in less than 2K byte plus workspace for up to almost two full screens. Price on 2 x 2708 EPROM £70 plus VAT.

TINY BASIC

A 2K BASIC Interpreter in 2x2708 EPROM. Normal commands: 1-32767 MSL/single array/arithmetic constant/ <>≤≥=≠ /strings valid in PRINT/supplied with user manual/additional three level keyboard control/compatible with NASBUG and B.Bug Price £25 Plus VAT.

An extended version of the above is our SUPER TINY BASIC which has all the TINY BASIC functions plus full editing features and additional operator command. Price in 3x2708 EPROM £35 plus VAT.

ZEAP

An editor assembler which runs under NASBUG and provides the powerful advantages of writing programs in Z80 assembly language instead of directly in machine code. Uses less than 3K bytes of memory and is supplied on cassette priced £30 plus VAT.



Nascom Microcomputers

121 High Street,
Berkhamsted,
Herts.

Tel: (04427) 74343

computing today marketplace



DIGITAL ALARM CLOCK MK2

Our sister magazines ETI and Hobby Electronics have sold a lot of digital alarm clocks — over 10,000 in fact — maybe that's something to do with the fact that we sell real bargains. In Computing Today we can offer you a truly modern, space age model.

It includes all the facilities expected in a good design — fast, slow setting, snooze facility, etc plus two unusual features — automatic brightness control and a weekend alarm cancel.

A version of this clock can be seen and examined at our Oxford Street Offices.

£10.50

(inclusive of VAT and Postage)



ALARM/CHRONO LCD WATCH

Although this is our first issue of Computing Today, we have had considerable experience of marketing digital watches through our sister magazines ETI and Hobby Electronics — this is by far the most advanced and best watch we've offered to readers.

Currently it is being discounted elsewhere for typically £39.95 (we don't quote RRP as this is meaningless) and the watch is a 'chinese copy' of a very famous one in the £100 range!

The facilities are exceptional:

- Normal hours and minutes
- Continuous seconds or data display
- Day of the week
- Stopwatch with 0.1 secs resolution
- Lap time facility with automatic return to stopwatch after 6 seconds
- Different time zone setting with independent date, day of week settings
- Good sleeping alarm
- Easy time correcting: on the sixth 'pip', press a button and it's reset to 00 seconds as long as watch is plus or minus 29 seconds.

It comes with a full guarantee of course.

A sample of this watch can be seen and examined at our Oxford Street Offices.

£27.95

(inclusive of VAT and Postage)

DIGITAL ALARM CLOCK MK2

TO: DIGITAL ALARM CLOCK MK2
OFFER
Computing Today
25-27 Oxford Street
London W1R 1RF

Please find enclosed my cheque/PO for £10.50 (payable to Computing Today) for my digital alarm clock.

Name

Address

.....

.....

Please allow 28 days for delivery.

LCD ALARM/CHRONO WATCH

TO: ALARM/CHRONO LCD WATCH
OFFER
Computing Today
25-27 Oxford Street
London W1R 1RF

Please find enclosed my cheque/PO for £27.95 (payable to Computing Today) for my Alarm/Chrono LCD watch.

Name

Address


.....

.....

Please allow up to 28 days for delivery.

HANIMEX Electronic LED Alarm Clock

Same as ETI offer
Thousands sold



Feature and Specification

- ★ Hour minute display
- ★ Large LED display with p.m. and alarm on indicator
- ★ 24 Hours alarm with on-off control
- ★ Display flashing for power loss indication
- ★ Repeatable 9-minute snooze
- ★ Display bright dim modes control

Size 5.15 x 3.93 x 2.36 (131mm x 100mm x 60mm)

Weight: 1.43 lbs (0.65 kg)

Guaranteed same day despatch

£8.65

LADIES LCD

Only 25 x 20 mm and 6 mm thick. 5 function: hours, mins, secs, day, date. + back light and auto cal. Elegant metal bracelet in silver or gold. State preference.



£9.95

Guaranteed same day despatch

5 FUNCTION LCD

Hours, mins, secs, month, date, auto calendar, back-light, quality metal bracelet.



£7.65

Guaranteed same day despatch Very slim, only 6mm thick.

THOUSANDS SOLD 11 FUNCTION SLIM CHRONO

6 digit 11 functions

Hours, mins, secs, Day, date, day of week, 1/100, 1/10, secs, 10 x secs, mins, Split and lap modes, Back light, auto calendar, Only 8 mm thick.

This same watch is being sold for £22.00 in newspaper and magazine special offer ads.



**Metac Price
£12.65**

Guaranteed same day despatch

All products carry full 12 months guarantee. Please add 30p p&p with all orders. All prices include VAT.

Shops open 9.30 to 6.00 daily.

Trade enquiries welcome. **Delivery:** One week. Except where same day delivery is stated.

ALARM CHRONOGRAPH WITH DUAL TIME ZONE FACILITY

- Constant LCD display of hours and minutes, plus optional seconds or date display, plus day of the week and am/pm indication.
- Perpetual calendar, day, date, month and year.
- 24-hour alarm with on/off indication.
- 1/10 second chrono-graph measuring net, lap and first and second place times.
- Dual time zone facility. Night light.



£27.95

PLEASE NOTE

All our products carry full money back 10-day reassurance.

Watches are despatched by **FIRST-CLASS POST**. They are fitted with new batteries, and include guarantee and instructions. Battery fitting service is available at our shops for no extra charge. We stock most watch batteries and this service is available to all.

Metac have been selling electronic watches probably longer than anyone else in the UK. We take care of your watch not just this year but next year and the years after that.

Telephone Special


24-hour phone service
Credit-card customers are welcome to buy by phone—simply phone 01 723 4753 with your credit card number to place your order.

METAC Electronics & Time Centre

67 HIGH STREET
DAVENTRY, NORTHANTS
Tel. (032 72) 76545

327 EDGWARE ROAD
LONDON W2
Tel. (01) 723 4753

Barclay & Access welcome
Phone or Send Card Number with order



THE TOTAL SOLUTION FROM ALMARC OF COURSE!

Now Almarc & Vector Graphic offer the complete solution to your computing needs for £2300.00*. The Vector MZ needs only the addition of a V.D.U. and it's ready to go. Completely assembled and fully tested, the Vector MZ offers the following features as standard:—

- S-100 bus
- 4 MHz Z80A processor
- 158 instructions
- Two quad density Micropolis floppies — over 630k bytes on line
- Serial port
- Two parallel ports
- 32K static ram
- 12K prem/ram board with extended monitor
- Extended disc Basic

Simply connect your peripherals (Elbit V.D.U.s & Centronics printers are available from Almarc) and you're up and running and, because the MZ uses the S-100 bus, you can plug in a massive range of add-on units.

STOP PRESS: CPM now available for NZ


Ring or write for a demonstration to:—

ALMARC DATA SYSTEMS LTD.

29 Chesterfield Drive
Burton Joyce, Nottingham
Tel: 0602 248565

*Discount terms available

Computer standard



3A PSU

Computers require a reliable and even power supply. The redesigned and uprated Nascom 3A PSU meets these requirements. Its output voltages are +5V 3A; +12V 1A; -12V 1A; -5V 1A. And are sufficient to drive the Nascom-1, buffer board and up to 32K of RAM. It has LED displays on all the outputs and will fit into the Nascom frame to be announced soon. Price of PSU kit—£24.50 plus VAT.

A buffer board kit with edge connectors suitable for the NASBUS and with edge connectors and interconnectors to attach directly to the Nascom-1 is available at £25.00 plus VAT.



Nascom Microcomputers

121 High Street,
Berkhamsted,
Herts.
Tel: (04427) 74343

UNREPEATABLE OFFER

EPROMS

UNTESTED ERASED EPROMS
1702A (2K BITS) **£3.00**
2758 (8K BITS) (limited qty)
£10.00

TRIACS

T2800D 8A 400V **£1.00**
T2302B 2.5A 200V **£0.60**
TIC225A 8A 100V **£0.45**

CMOS

CD4001BE (NOR GATE) **£0.14**
CD4049UBE (HEX INV BUFFER)
£0.30
CD4050BE (HEX BUFFER)
£0.30

TRANSISTORS

BD175 **£0.40**
2N4921 **£0.40**
BC300 **£0.25**

DIODES

1N4001 **£0.04**
1N4002 **£0.04**
1N4004 **£0.06**

MICROCOMPUTER BARGAINS

We have a stock of untested microcomputer PCB's which are surplus to our requirements. Each PCB contains an Intel 4040 (CPU), 4201 (clock), 4289 (standard memory interface), 5MHZ crystal, zero crossover detector CCT, power on reset CCT sockets for 5 x 1702A Eprom and on board power supply (50V 50 HZ input) regulated to provide 15v DC supply. These PCB's are sold as untested units with data on all chips and CCT diagram at the bargain price of **£19.00**.

Also available: —
1702A (programmed to your hexadecimal requirements)

£5.00

4265 (general purpose input output device suitable for use with the above PCB) **£5.00**

Please add 28 pence P&P to your order and VAT at 8%

Cheque/Postal Order to: —

RACE ELECTRONICS LTD.

54/64, Morfa Road, Swansea
Tel. (0729) 41241/462684

Mail Order supplies only

Please allow 21 days for delivery

ETCH RESIST TRANSFER KIT SIZE 1:1

Complete kit 13 sheets 6in x 4½in **£2.50** with all symbols for direct application to P.C. board. Individual sheets 25p each. (1) Mixed Symbols (2) Lines 0.05 (3) Pads (4) Fish Plates and Connectors (5) 4 Lead and 3 Lead and Pads (6) DILS (7) BENDS 90 and 130 (8) 8—10—12 T.O.5 Cans (9) Edge Connectors 0.15 (10) Edge Connectors 0.1 (11) Lines 0.02 (12) Bends 0.02 (13) Quad in Line.

FRONT AND REAR PANEL TRANSFER SIGNS

All standard symbols and wording. Over 250 symbols, signs and words. Also available in reverse for perspex, etc. Choice of colours, red, blue, black, or white. Size of sheet 12in x 9in. Price **£1**.

GRAPHIC TRANSFERS WITH SPACER ACCESSORIES

Available also in reverse lettering, colours red, blue, black or white. Each sheet 12in x 9in contains capitals, lower case and numerals ½in kit or ¼in kit. **£1** complete. State size.

All orders dispatched promptly.

All post paid

Ex U.K. add 50p for air mail
Shop and Trade enquiries welcome
Special Transfers made to order

E. R. NICHOLLS

P.C.B. TRANSFERS

Dept. CT1

46 LOWFIELD ROAD
STOCKPORT, CHES. 061-480 2179

Hard Copy



THE KIMBERLEY AZ-3 PRINTER

88 character set, ASCII coded
8cps; 11" carriage
Correspondence quality output
Price **£182.86**
plus **£3.50** carriage + VAT

Purpose built interfaces now
available for PET and TRS-80
Also text editing software

Send for full details

KIMBERLEY

Business Records

2, Hartington Road

Gosport

Hants, PO12 3AG

07017 86642

MINI-

WEST COUNTRY DEVON

CRYSTAL ELECTRONICS CC ELECTRONICS

FOR THE BEST IN SMALL COMPUTERS

Advice and back up on
Apple II, Nascom I,
Atari and Newbear

BOOKS — over 150 titles
COMPONENTS, ADD ENS ETC

Apple II Stock
control
(for disc &
printer)
for up to
10,000 items
£100 + Vat
(full update for
6 months)

NASCOM
Tape contain-
ing 6 games
etc
£6.00 + Vat

All products
stocked on
advice from
our engineers
as to quality,
value for
money and
reliability.



Shop open
0930-1800
Except
Wed & Sun

40 Magdalen Rd
Torquay
Devon
Tel: 0803 22699

UNREPEATABLE offer Motorola DI micro-processor kits **£32.50** incl. with milkbug, pa, ram, pcb and all components, RS232/20mA, loop, expandable, limited quantity. Also one only ready built Nascom, new **£145**.

C.T.S. Littleborough (0706) 79332 anytime.

EPROM PROGRAMMING prompt service
27 (1024 x 8) or 5204 (512 x 8) EPROMS
programmed in your Hex (or copy) **£12**
each or your chips erased and programed
£3 each. Special rates for batches. Pete
Marlow, "Rosslyn", Moorend Grove, Chel-
tenham, Glos. GL53 0EX. Phone (0242)
55133 evenings.

Triton (8080)

ASKREG (listing), displays registers whilst
debugging **£2**.
Software debugging service — send 2p per
byte and commented assembly listing.
Andover Software Kits, 15 Winchester Rd.,
Andover, Hants.

ETI Triton Computer, bought as kit, now
built and fully operational. Full 4k RAM,
complete with tape recorder. Offers over
£375. Tel. Nottingham (0602) 266563.

2111-2 Static Ram 1 ★**£2.15** 8 ★**£16** 16 ★**£30**
2112-2 Ram **£2** 52040 Rom **£7**.
Model KB756 ASCII keyboard with connec-
tor plus data **£50** limited quantity, prices
Inc. B. Mistry E0.8 Kenholmes Hall, Raw-
son Street, Leicester.

ADS & CLASSIFIED

BRITISH MOTOROLA 6800 SYSTEMS

6800S: 16K Dynamic RAM, 1K Mikbug compatible monitor, room for 8K BASIC in ROM, VDU with u/1 case and graphics, CUTS and Hi Speed tape interfaces. Single pcb with power supply components. Price of kit from £275 without kbd or £299.00 with keyboard.


Mini 6800, 1K user RAM, CUTS, VDU. Kit without keyboard from £120, with keyboard from £145.

NCU Board. This number cruncher using the MM57109 is supplied with our own Basic style program on tape (3K bytes) that will outperform any of the 8K Basics as a programmable calculator. Suitable for any 6800 system with Mikbug. Kit price £32.00.

8K RAM (2114) and 5 or 10K PROM board. This pcb is bus compatible with the above systems and has all the buffering and decoding that you need. PCB only, £13.00.

ALL PRICES WITHOUT VAT AND POST.
PLEASE SEND S.A.E. FOR LEAFLETS.

HEWART MICROELECTRICS
95 Blakelow Road, Macclesfield,
Cheshire.



LIVING LOGIC!

STICKIES are printed self-adhesive labels that stick to the top of ICs. They make dull, anonymous plastic blocks into diagrams that come ALIVE! See at-a-glance where to place your test probe or soldering iron — take the hassle out of ICs.

STICKIES are great for building and debugging prototypes, faultfinding, experimenting, teaching — even designing PCB layouts.

STICKIES come in packs for 7400- or 4000-series ICs. Each pack contains a sensible mix of more than 60 different IC types.

120-label pack—**80p**, 480-label pack—**£2.80**, or 2-10 packs at **£2.50** each, 11-plus **£2.20** each.

Prices include VAT and first-class postage. Official orders welcome. Please state whether TTL or CMOS required.

For your STICKIES by return of post
CONCEPT ELECTRONICS, 8 Bayham Road
Sevenoaks, Kent TN13 3XA
Phone: 0293 514110

Low Cost Ram

21L02 (450ns)

1-15 at 89p
16-63 at 86p
64 + at 83p

Ring for latest quantity discount prices
0243 42554

J. M. Evans
"Kimlas"
School Lane,
Nutbourne,
Chichester,
Sussex.

THIS SECTION IS A PRE-PAYMENT SERVICE ONLY

MINI-ADS: 31/4" x 21/8", 1-3 £38, 4-11 £36, 12 or more £34 per insertion. **CLASSIFIED DISPLAY:** 19p per word. Minimum 25 words. Boxed classifieds are £6.33 per col. centimetre. No P.O. Box Numbers can be accepted without full address.

Enquiries to: Advertising Department, 01-437 5982. 25-27 Oxford Street, London W1R 1RF

ATTENTION NASCOM USERS

GRAPHICS ADD ON BOARD £9.90

Complete kit to upgrade your NASCOM for graphics capability includes full documentation and demonstration program.

STOP PRESS: Just released —

Software for the big boys!

Star Ships **£5.00**

Pontoon **£5.00**

require Comp S100 expansion
plus tiny basic

Fruit Machine **£5.00**

Pilot **£5.00**

Othello **£2.00**

runs on a basic Nascom


For delivery information see our advert on the inside back cover of this magazine.

COMP COMPUTER
COMPONENTS

AD INDEX

| | | | |
|---------------------------|------------|------------------------|-------------|
| AIRAMCO | 66 | METAC | 71 |
| ALMARC | 71 | MICRODIGITAL | 6 |
| BETOS | 65 | MUSICPRINT | 48 |
| BYTE SHOP | 54 | NASCOM | 69, 71 & 73 |
| COMP, COMP, COMP | 73, 74, 75 | NEWBEAR | 76 |
| ELECTROVALUE | 19 | NICHOLLS | 72 |
| HAPPY MEMORIES | 17 | PETALECT | 48 |
| HENRYS | 17 | PETSOFT | 2 |
| H. L. AUDIO | 4 | RACE ELECTRONICS | 72 |
| INTEGRATED CIRCUITS | 46 | STRATHAND | 19 |
| JEFF WAYNE MUSIC | 8 | TANGERINE | 13 |
| KIMBERLEY BUS | | TECHNICAL BOOK | |
| RECORDS | 72 | SERVICE | 23 |
| LOTUS SOUND 28 & 29 | | TIM ORR DESIGN | 48 |
| LP ENTERPRISES | 10 | TRANSAM | 14 |
| | | VIDEOTIME | 28 |
| | | WARD JAMES | 23 |

The great RAM sale



The Nascom system offers major expansion at sale prices. To give you as much choice as possible we offer RAM boards in three configurations to accommodate up to 16 memory ICs of either MK4027 or MK4116, all socketed.

The memory board kit options are:

8K £85.00
16K £140.00
32K £200.00

Boards will also accommodate up to four EPROMS of type 2708 at £10.50 plus VAT each. And if you wish to upgrade 16K to 32K it will only cost you an additional £70.

Memory boards plug straight into a NASBUS and an edge connector is included for this. All boards must be used in conjunction with the buffer board which, like the memory boards, is available in kit form ex-stock from approved Nascom distributors.

nm

Nascom Microcomputers

121 High Street,
Berkhampsted,
Herts.

Tel: (04427) 74343

INTERESTED IN HOME COMPUTING?

Start now and don't get left behind **THE NASCOM 1** is here Ex-stock with full technical services

Plus the opportunity to join the fastest moving club of personal computer users enabling you to get the most out of your computer. You can OBTAIN and EXCHANGE programs and other software — many now available.

The Powerful Z80
Microprocessor
Professional Keyboard
1 Kbyte Monitor in EPROM
2 Kbyte RAM (expandable)
Audio Cassette interface
Plugs into your domestic TV
Easy construction from
straightforward instructions
— no drilling or special tools
— Just neat soldering
required

Only **£197.50** + 8% VAT (includes p & p + insurance)

Manuals separately **2.95**
Z80 programming Manual **6.90**
Z80 Technical Manual **2.95**
PIO Technical Manual **2.95**

(All prices add 8% VAT)

NEW LOW PRICE
£165.00

Power supply suitable for
NASCOM **19.90**

NASCOM AD ONS — Nascom improved monitor B Bug (2K)
featuring — *Four times tape speed *Direct text entry without
ASCII *Extended keyboard facility *Additional useful
subroutines **£23.00**

Nascom Vero Case
£22.50

Nascom Joy Stick Kit
£14.90

Nascom Music Box Kit **£9.90**
(write your own tunes and play
them on your Nascom.
Complete with full documentation).

FREE B BUG
valued at £23.00
plus 10 x C12 cassettes
valued at £4.00
plus Standard Modulator
valued at £2.25
WITH EVERY NASCOM



**SAVE
£60**

PET COSTS LESS AT COMP and it's a pedigree **RRP £695**

The No. 1 Personal Computer
in the U.K.

Affordable £590 **SAVE £100**

for the first time user and
the professional check out
the PET, the world's most
popular personal computer.



THE ATARI video computer system

Atari's Video Computer System now offers
more than 1300 different game variations
and options in twenty great Game
Program™ cartridges!

Have fun while you sharpen
your mental and physical
coordination. You can play
rousing, challenging, sophisticated
video games, the games that made
Atari famous.

You'll have thrill after thrill, whether
you're in the thick of a dogfight,
screaming around a racetrack, or
dodging asteroids in an alien
galaxy. With crisp bright color (on
color TV) and incredible, true-to-life
sound effects. With special circuits
to protect your TV.

Cartridges now available

Basic Maths, Airsea Battle, Black
Jack, Breakout, Surround, Spacewar,
Video Olympics, Outlaw, Basketball.

All at
£13.90
each.



Years and
years of fun and
satisfaction are
assured

SAVE £30

£139.00

NASCOM IMMEDIATE EXPANSION \$100 from COMP —strongly recommended

The only available \$100 motherboard kit (fully buffered) that
plugs directly into your Nascom. Designed for the insertion
of \$100 boards (e.g. Static RAM, EPROM and discs etc.).

\$100 Motherboard/Buffer **£47.50**
(Complete kit + documentation) } **Buy both and
get 2K Tiny
Basic On
cassette FREE.**
Suitable 8K Static RAM Memory **£110**
(fully assembled tested and guaranteed)

NASCOM LOW COST EXPANSION

Uses dynamic RAM and NASBUS
(please note this expansion does not support \$100 memory)

Tiny Basic in EPROM **£25.00**
8K Dynamic RAM board (in kit only) **£85.00**
Motherboard (in kit only) **£12.50**
Buffer board (in kit only) **£25.00**

All
plus
VAT

ATTENTION! TRS 80 USERS

**16K UP
GRADE KIT**

Half Radio **£99**
Shack Price + VAT

**LIFETIME
GUARANTEE**

**SAVE
£90**

Simple to fit—
only a screw-
driver is
required.

TRS 80 SOFTWARE **NEW**

100 MIXED PROGRAMMES **£49.00**
on cassette

OHIO SUPERBOARD II **NEW**

For electronic buffs. Fully assembled and tested. Requires +5V at
3 Amps and a video monitor or TV with RF converter to be up and
running.

STANDARD FEATURES

Uses the ultra powerful 6502 microprocessor
8K Microsoft BASIC-in-ROM

Full feature BASIC runs faster than currently
available personal computers and all
8080-based business computers.

4K static RAM on board expandable to 8K
Full 53-keyboard with upper/lower case and user
programmability

Kansas City standard audio cassette interface
for high reliability

Full machine code monitor and I/O utilities in
ROM

Direct access video display has 1K of dedicated memory (besides
4K user memory), features upper case, lower case, graphics and
gaming characters for an effective screen resolution of up to 256
by 256 points. Normal TV's with overscan display about 24 rows
of 24 characters; without overscan up to 30 x 30 characters.

EXTRAS

Available expander board features 24K static RAM (additional), dual
mini-floppy interface, port adapter for printer and modem and an
OSI 48 line expansion interface.

Assembler/editor and extended machine code monitor available.

~~£280.00~~ **£249.00** + VAT *Send £10 to reserve one—
pay balance on delivery.*

MODULATORS UHF Channel 36

Standard 6 meg band width **£2.25**
High Quality 8 meg band width **£4.90**

BULK PURCHASE ~~£99~~
VDU MONITORS **£69**
CAGED AND GUARANTEED **12"** + VAT



Teleplay presents the PROGRAMAGAME of all time!

TELEPLAY have produced a new product that will not go out of date. It is easy to assemble, cartridge games for you and all your family. It is as it becomes available and your colour video centre will be up to date the Teleplay way. You will save pounds in the long run. Works OK on Black and White TV.

EX STOCK IMMEDIATE DELIVERY

We offer all this to you for ONLY **Special Show Price £28.90** £2.31 VAT Fully Assembled £35.90

The Teleplay Kit consists of a Professional Finished Inject Moulded Box, Joystick Hand Controls, one cartridge which consists of 10 games: Football, Tennis, Soccer Squash, 1 & 2 Foot, Hockey, Basketball, 1 & 2 players, Shoot etc. Main Attractor. All players are included. No special holes are required. You'll be surprised how easy it is to assemble this professional kit. Instruction Manual supplied separately at 0.45. TELEPLAY GIVES YOU TWICE THE FUN BUILDING AND PLAYING THE MOST PROFESSIONAL TV GAME KIT EVER OFFERED.

Main Cartridge has 3 Facility Hand-capping Switches.

£14.90 + £1.14 VAT Fully assembled add £3.00

Cartridges and Hand Controls £18.90 + £1.51 VAT

Cartridge and Hand Controls £18.90 + £1.51 VAT

Cartridge and Hand Controls £18.90 + £1.51 VAT

NEW - WIPE OUT cartridge - 6 games £13.90 + £1.11 VAT

All parts fully guaranteed

OHIO C2-4P MINI FLOPPY

SAVE £100



20K RAM Basic + Assembler
Personal, Games, Small Business & Educational Disks
90K Mini Floppy Storage
Printer Interface
OS 65D V.30 Operating System
RRP £1595.00
Only £1,495.00 Complete + VAT.
Complete with monitor + disc drive
Economic expandable systems with good disk based software, available now.

THE EXIDY SORCERER.

SAVE £100

SORCERER COMPUTER SYSTEM

The Sorcerer Computer is a completely assembled and tested computer system. Standard configuration includes 63-key typewriter-style keyboard and 16-key numeric pad, Z80 processor, dual cassette I/O with remote computer control at 300 and 1200 baud data rates, RS232 serial I/O for communications, parallel port for direct Centronics printer attachment, 4K ROM operating system, 8K ROM composite video of 64 char/line 30 line/ screen, 128 upper/lower case ASCII set and 128 user defined graphic symbols, operation manual, BASIC programming manual and cassette/video cables, connection for S-100 bus expansion.



LOOK!

*32K RAM on board
*RS232 interface *8K BASIC ROM
*CUTS interface *4K MONITOR
*KANSAS CITY interface *\$100 BUS
*User defined graphic symbols *Z80 cpu

16K £900 £751 * 32K £950 £850 * Credit facilities available. * + VAT

COMPUTER COMPONENTS

Send for our Spring 1979 catalogue, 0.60p Full of Computer Components, Peripherals and systems.

| | | |
|------------------|----------------|---------------|
| 4116 — £9.90 | 6800 — £11.90 | 6852 — £9.90 |
| Z80 P10 — £9.90 | 6820 — £5.00 | 6502 — £9.90 |
| Z80 CPU — £14.90 | 8T26 — £2.90 | 1702A — £4.90 |
| Z80 CTC — £9.90 | 6810P — £4.95 | 2102 — £1.00 |
| 2350 — £4.90 | 6852P — £11.25 | 2708 — £9.90 |
| 6828 — £6.90 | | |

VIDEO GAME COMPONENTS

| | | |
|-------------------------------------|---|-----------------|
| 8603 — Video Road Race Chip — £3.90 | 8710 — Tank Chip (with no upwards firing, otherwise OK) — £3.50 | ETI PCB — £1.50 |
| 8500 — 6 Game Chip — £3.90 | | |
| 8610 — 10 Game Chip — £4.90 | | |

BOOK SHELF

| | |
|--|-------|
| LOW PRICES FAST SERVICE! | £5.40 |
| Vol 0 The Beginner's Book | £5.90 |
| Vol 1 Basic Concepts + | £9.90 |
| Vol 2 Some Real Products (June 1977) | £7.50 |
| Microprocessor series, by Rodney Zaks | £7.50 |
| C207 Interfacing Techniques | 16.40 |
| Microprocessor Systems Design by Edwin Klingman ISBN 0-135-81413-8 (1977) 480 pages hard cover | £6.90 |
| CMOS Cookbook by Don Lancaster | £6.50 |
| 6800 Assembly Language Programming | £7.90 |
| 6800 Software Guide & Cookbook from Scelbi | £7.90 |
| 8080 Software Guide & Cookbook from Scelbi | £6.50 |
| 8080 A/8085 Assembly Language Programming | £6.90 |
| 8080A Bugbook Interfacing & Programming by Rony, Larsen & Titus (1977) 416 pages | £5.90 |
| Z80 Programming for Logic Design by Adam Osborne | £7.20 |
| Z80 Microcomputer Handbook by William Barden | |
| Structured Programming & Problem Solving with Pascal ISBN 0-138-54869-2 (1978) 365 pages by Kiebertz "When will your microcomputer speak Pascal" | £9.50 |
| BASIC Computer Games — Microcomputer edition | £5.40 |
| Best of BYTE Vol 1 (1977) 376 pages | £8.90 |
| Best of CREATIVE COMPUTING Vol 1 (1977) 326 pages | £6.90 |
| Vol 2 (1977) 323 pages | £6.90 |
| MOI OTHELLO Game for 2 players on NASCOM 1 cassette | £2.00 |
| MOI MINO PILOT powerful text editor and interpreter in 1/2 KB | £5.00 |

MAGS.

BYTE — £2.00

INTERFACE AGE — £2.00

KILO BAUD £2.00

MANY RECENT BACK ISSUES

WE CAN SUPPLY YOUR SHOP

All prices include VAT except where shown. Orders over £5 post and packing free otherwise add 20p. Please make cheques and postal orders payable to COMP, or phone your order quoting BARCLAYCARD or ACCESS number.

COMP COMPUTER COMPONENTS

14 STATION ROAD, NEW BARNET, HERTFORDSHIRE TEL: 01-441 2922 (Sales) 01-449 6596
CLOSE TO NEW BARNET BR STATION — MOORGATE LINE TELEX: 298755
OPEN — 10am to 7pm — Monday to Saturday CONTINUOUS DEMONSTRATIONS
£6 EXTRA FOR SECURICOR DELIVERY



NewBear



Computing Store

Keyboards

* Star Devices capacitive touch keyboard
£37.50 inc VAT + p&p*
63 Key Ascii Encoded Kit £56.00
63 Key 'ASR 33' Style Hitex Keyboard unencoded
£27.50
U.V. Prom Eraser £56.00
77-68 The best supported hobbyist 6800 system
in the U.K. available as complete kits or as
individual components.

| | | |
|-------------------|--|----------|
| Bearbag 1 | 77-68 CPU PCB and components | £ 45.00 |
| Bearbag 2 | 77-68 LEDS and Switches | £ 14.95 |
| Bearbag 3 | 77-68 Power Supply | £ 17.95 |
| Bearbag 4 | 77-68 19" Rack and Backplane | £ 27.70* |
| Bearbag 5 | 77-68 4K Ram PCB and Components | £ 75.00 |
| Bearbag 6 | 77-68 Mon 1 PCB and Components | £ 50.70 |
| Bearbag 12 | 77-68 VDU PCB and Components | £ 69.50 |
| Bearbag 13 | 77-68 Mon 2 PCB and Components | £ 64.10 |
| Bearbag 16 | 77-68 Rom A (Eprom Board) and Components | £ 29.50 |
| Bearbag 17 | 77-68 P10 board and Components | £ 45.00 |

Other Bearbags Available

| | | |
|-------------------|--|---------|
| Bearbag 7 | 4K Ram PCB and components Exorciser compatible | £ 71.50 |
| Bearbag 8 | 8K Ram PCB and components Exorciser compatible | £160.00 |
| Bearbag 9 | Petiterid VDU Kit | £ 85.00 |
| Bearbag 10 | Kansas City Cassette Interface | £ 18.95 |
| Bearbag 11 | UHF Modulator | £ 3.50 |
| Bearbag 14 | 2708 Prom Programmer (6800) | £ 35.00 |
| Bearbag 18 | Cottis Blandford Cassette Interface | £ 17.25 |

SPECIAL OFFER!
Buy a Shugart disc drive, get the controller chip (INS 1771) for only £30.

Horizon

(S100 bus Z80 based micro)
16K RAM with Single Disc Drive £1250
32K RAM with Double Disc Drive with 2 Serial and 1 parallel port £1975

SYM-1

The 6502 based Micro from Synertek
* 4K monitor
* Up to 4K RAM on board
* High speed cassette interface
* Fully assembled and tested £199.00 + 8% VAT
8K Basic for SYM-1 in ROM £147.00

Sorcerer from Exidy

8K RAM with cassette interface £650.00
Extensive range of 6800 Software on cassette, Hardware components and Books — Send or phone for up-to-the-minute information!
Quantity discounts available on memories!

Floppy Disc Drives

8" DRI Model 7100 £325.00
Single Sided Disc Drive carriage £5
8" DRI Model 7200 £365.00
Double Sided Disc Drive carriage £5.00
5 1/4" Shugart SA400 Disc Drive £225.00
carriage £4.50

S100 Microbox £195.00

(6 Slot card cage with power supply and motherboard with 3 sockets fitted)

**ITHACA AUDIO S100 BOARDS
NOW IN STOCK!**



SEND FOR
AN UP TO
DATE
CATALOGUE

Postage and packing 50p
*Postage and packing £1.50

Minimum official order £10.00. Send for catalogue to Newbear Computing Store, Bone Lane, Newbury, Berks. Callers welcome Mon-Sat 9.00-5.30 but please phone us first on 0635 49223. Visit our Northern office at 2A Gatley Road, Cheadle Cheshire. Tel 061-491-2290.
ALL MAIL ORDER TO NEWBURY.
Barclaycard and Access Welcome.

